



# **GV600M Series @Track Air Interface Protocol**

**EGPRS/LTE Cat-M1/LTE Cat-NB1/GNSS Tracker**

**QSZTRACGV600MAN0106**

Version: 1.06

*International Telematics Solutions Innovator*

[www.queclink.com](http://www.queclink.com)

<b>Document Title</b>	GV600M Series @Track Air Interface Protocol
<b>Version</b>	1.06
<b>Date</b>	2019-02-15
<b>Status</b>	Released
<b>Document Control ID</b>	QSZTRACGV600MAN0106

### General Notes

Queclink offers this information as a service to its customers, to support application and engineering efforts that use the products designed by Queclink. The information provided is based upon requirements specifically provided to Queclink by the customers. Queclink has not undertaken any independent search for additional relevant information, including any information that may be in the customer's possession. Furthermore, system validation of this product designed by Queclink within a larger electronic system remains the responsibility of the customer or the customer's system integrator. All specifications supplied herein are subject to change.

### Copyright

This document contains proprietary technical information which is the property of Queclink. Copying of this document, distribution to others or using or communication of the contents thereof is forbidden without express authority. Offenders are liable to the payment of damages. All rights are reserved in the event of a patent grant or registration of a utility model or design. All specification supplied herein are subject to change without notice at any time.

**Copyright © Queclink Wireless Solutions Co., Ltd. 2019**

## Contents

0. Revision History.....	4
1. Overview .....	5
1.1. Scope of This Document.....	5
1.2. Terms and Abbreviations .....	5
2. System Architecture .....	6
3. Message Description .....	7
3.1. Message Format .....	7
3.2. Command and Acknowledgement .....	8
3.2.1. Server Connection .....	8
3.2.2. Device Configuration .....	14
3.2.3. Position Related Report .....	26
3.2.4. Alarm Settings .....	31
3.2.5. IO Application .....	56
3.2.6. Main Serial Port Application .....	68
3.2.7. Other Settings .....	76
3.3. Reports .....	95
3.3.1. Position Related Reports .....	95
3.3.2. Device Information Report .....	110
3.3.3. Report of Real Time Querying .....	112
3.3.4. Event Report .....	158
3.3.5. Data Report.....	183
3.3.6. Buffer Report .....	183
3.3.7. Transparent Data Transmission.....	184
3.3.8. Report Google Maps Hyperlink .....	186
3.4. Heartbeat .....	188
3.5. Server Acknowledgement .....	189
4. HEX Format Report Message.....	190
4.1. Hex Report Mask .....	191
4.2. Acknowledgement +ACK .....	197
4.3. Location Report +RSP .....	201
4.4. Information Report +INF .....	216
4.5. Event Report +EVT .....	220
4.6. Data Report +DAT .....	256
4.7. Heartbeat Data +HBD .....	257
4.8. Buffer Report in HEX Format .....	258
Appendix: Message Index .....	259

## 0. Revision History

Version	Date	Author	Description of Change
1.00	2018-07-26	Parker Xu	Initial
1.01	2018-09-03	Parker Xu	1.Add +RESP:GTVGN, +RESP:GTVGF 2.Modify "No ignition" comments in AT+GTDIS 3.Modify "Sensor wakeup device debounce" <b>4.Add "ICCID" in +RESP:GTINF,</b> 5.Add "Time Unit" in AT+GTSSR 6.Add AT+GTIDA, +RESP:GTIDA report 7.Add AT+GTACD
1.02	2018-09-25	Parker Xu	1.Add AT+GTBTE,+RESP:GTBST Report 2.Add +RESP:GTBTA Report.
1.03	2018-10-26	Parker Xu	1.Add "manual_netreg" in AT+GTBSI 2.Modify AT+GTPDS 3.Modify the description of AT+GTBTE command
1.04	2018-11-26	Kerwin Shen	1.Modify the AT+GTDOG command
1.05	2018-12-18	Parker Xu	1.Modify the AT+GTGAM command 2.Add "IDA" and "ACD" in the AT Configuration Mask 3.Modify the AT+GTTMA command 4.Modify the AT+GTFRI command 5.Modify GTERI report 6.Modify "Network Type" in the GTAIF report
1.06	2019-02-15	Parker Xu	1. Added GTUFS, GTFSD and GTEXP Reports. 2. Modify AT+GTMUT, AT+GTFSC, AT+GTEFS、AT+GTCFG commands. 3. Added AT+GTUFS command.

## 1. Overview

### 1.1. Scope of This Document


The @Track Air Interface Protocol, a digital communication interface based on printable ASCII characters over SMS or network, is used for communication between the backend server and the terminal. The backend server sends a command to the terminal and then the terminal confirms with an acknowledgement message. If necessary, the terminal also sends messages to the backend server.

The purpose of this document is to describe how to build up the backend server based on the @Track Air Interface Protocol.

### 1.2. Terms and Abbreviations

Abbreviation	Description
APN	Access Point Name
ASCII	American National Standard Code for Information Interchange
GSM	Global System for Mobile Communication
HDOP	Horizontal Dilution of Precision
ICCID	Integrated Circuit Card Identity
IMEI	International Mobile Equipment Identity
IP	Internet Protocol
LTE	Long Term Evolution
RSSI	Received Signal Strength Indication
SMS	Short Message Service
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
UTC	Coordinated Universal Time

## 2. System Architecture



The backend server can be accessed by multiple terminals and it should have the following abilities:

- ✧ The backend server should be able to access the internet and monitor the connection originating from the terminal.
- ✧ The backend server should be able to support TCP or UDP connection with the terminal. It should be able to receive data from the terminal and send data to the terminal.
- ✧ The backend server should be able to receive and send SMS.

### 3. Message Description

#### 3.1. Message Format

All of the @Track Air Interface Protocol messages are composed of printable ASCII characters. Each message has the following format:

Message format	Message type
AT+GTXXX=<parameter1>,<parameter2>,...\$	Command
+ACK:GTXXX,<parameter1>,<parameter2>,...\$	Acknowledgement
+RESP:GTXXX,<parameter1>,<parameter2>,...\$	Report

The entire message string ends with character '\$'.

The characters 'XXX' identify the transmitted messages.

The "<parameter1>, <parameter2>,..." carries the message's parameters. The number of parameters is different in different messages. The ASCII character ',' is used to separate the neighboring parameter characters. The parameter string may contain the ASCII characters: '0'-'9', 'a'-'z', 'A'-'Z'.

Detailed descriptions of each message format are located in the specific message sections.

The backend server can either configure and query the parameters of the terminal or control the terminal to perform specific actions by sending Commands to the terminal. When the terminal receives Commands over the air, it will reply with a corresponding Acknowledgement message.

The device can send other Reports to the server by configuring related parameters. Please see the following figure:




Figure 1: @Tracker Protocol messages flow

## 3.2. Command and Acknowledgement

### 3.2.1. Server Connection

#### 3.2.1.1. Bearer Setting Information

The command **AT+GTBSI** is used to configure the parameters for network data connection.

➤ **AT+GTBSI=**

Example: AT+GTBSI=gv600m,,ctnet@mynet.cn,vnet.mobi,,,,,0000\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	APN	<=64		
3	APN User Name	<=30		
4	APN Password	<=30		
5	Backup APN	<=64		
6	Backup APN User Name	<=30		
7	Backup APN Password	<=30		
8	Network Mode	1	0 1 2	0
9	LTE Mode	1	0-3	2
10	Manual netreg	1	0-1	0
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Password>: The valid character of password is '0'–'9', 'a' –'z', 'A' –'Z'. The default value is "gv600m".
- ✧ <APN>: Access point name (APN).
- ✧ <APN User Name>: The GPRS APN user name. If the parameter field is empty, the current value of this parameter will be cleared.
- ✧ <APN Password>: The GPRS APN Password. If the parameter field is empty, the current value of this parameter will be cleared.
- ✧ <Backup APN>: The Backup access point name (APN). If the <APN> does not useful, the <Backup APN> will be used.
- ✧ <Backup APN User Name>: The backup GPRS APN user name. If the parameter field is empty, the current value of this parameter will be cleared.
- ✧ <Backup APN Password>: The backup GPRS APN password. If the parameter field is empty, the current value of this parameter will be cleared.
- ✧ <Network Mode>: Mobile network modes of the device.
  - 0: Auto (LTE Frist & GSM).



- 1: GSM only.
- 2: LTE only.
- ✧ <LTE Mode>: Select Cat-M1 and Cat-NB1 work mode.
  - 0: Cat-M1 first (Cat-M1 & Cat-NB1).
  - 1: Cat-NB1 first (Cat-M1 & Cat-NB1).
  - 2: Cat-M1.
  - 3: Cat-NB1.
- ✧ <Manual netreg>: Manually register the network selection.
  - 0: Disable Manually register the network.
  - 1: Enable Manually register the network.
- ✧ <Serial Number>: The serial number for the command. It will be included in the ACK message of the command.
- ✧ <Tail Character>: A character to indicate the end of the command. And it must be "\$".

The acknowledgment message of **AT+GTBSI** command:

➤ **+ACK:GTBSI,**

Example: <b>+ACK:GTBSI,ED0101,862170019025640,,0000,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Protocol Version>: The protocol version that the terminal conforms to. The first two characters point out the device type. As in the example, "ED" means GV600M. The middle two characters point out the major version number of the protocol and the last two characters point out the minor version number of the protocol. All version numbers are hex digits. For example, "0101" means version 1.01.
- ✧ <Unique ID>: The IMEI of the terminal.
- ✧ <Device Name>: The specified name of the device.
- ✧ <Serial Number>: A serial number which is included in the corresponding command to distinguish which command the ACK message is for.
- ✧ <Send Time>: The local time to send the ACK message.
- ✧ <Count Number>: A self-increasing count number in each acknowledgment message and other messages. It counts from 0000 and increases by 1 for each message. And it rolls back after "FFFF".

✧ <Tail Character>: A character to indicate the end of the command. And it must be "\$".

#### Note:

Only after both of the command **AT+GTBSI** and **AT+GTSRI** are properly set can the ACK messages and other messages be sent to the backend server.

#### 3.2.1.2. Backend Server Register Information

The command **AT+GTSRI** is used to configure where and how to report the messages such as the server information and the communication method between the backend server and the terminal.

##### ➤ AT+GTSRI=

<b>Example:</b> <b>AT+GTSRI=gv600m,3,,1,116.226.44.17,7011,116.226.45.229,7012,+8613812341234,15,1,,,,,0001\$</b> <b>AT+GTSRI=gv600m,3,,1,some.host.name,7011,116.226.45.229,7012,+8613812341234,15,1,,,0001\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Report Mode	1	0 – 7	0
3	Reserved	0		
4	Buffer Mode	1	0 1 2	1
5	Main Server IP/Domain Name	<=60		
6	Main Server Port	<=5	0 – 65535	
7	Backup Server IP/Domain Name	<=60		
8	Backup Server Port	<=5	0 – 65535	
9	SMS Gateway	<=20		
10	Heartbeat Interval	<=3	0 5 – 360min	0
11	SACK Enable	1	0 1 2	0
12	Protocol Format	1	0 1	0
13	SMS ACK Enable	1	0 1	0
14	Reserved	0		
15	Reserved	0		

	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ *<Report Mode>*: This defines the communication method between the backend server and the terminal. Supported report modes are as following:

- 0: Stop reporting.
- 1: TCP short-connection preferred mode. The connection is based on TCP protocol. The terminal connects to the backend server every time it needs to send data and will shut down the connection when the terminal finishes sending data. If it fails to establish TCP connection to the backend server (both Main Server and Backup Server), it will try to send data via SMS to the SMS gateway.
- 2: TCP short-connection forced mode. The connection is based on TCP protocol. The terminal connects to the backend server every time it needs to send data and will shut down the connection when the terminal finishes sending data. And if it fails to establish TCP connection to the backend server (both Main Server and Backup Server), it will store the data in the memory buffer if buffer report function is enabled, otherwise the data is dropped.
- 3: TCP long-connection mode. The connection is based on TCP protocol. The terminal connects to the backend server and maintains the connection by using the heartbeat data. The backend server should respond to the heartbeat data from the terminals.
- 4: UDP mode. The terminal will send data to the backend server by UDP protocol. Receiving protocol commands via UDP is supported if network allows it. It is recommended to enable heartbeat sending when UDP receiving is the case.
- 5: Force on SMS. Only use the SMS for transmitting.
- 6: Reserved
- 7: TCP long-connection mode with the backup server. The connection is based on TCP protocol. The terminal connects to the backend server and maintains the connection by using the heartbeat data. The backend server should respond to the heartbeat data from the terminals. If the main server is lost, it will try to connect the backup server. And if the backup server is also lost, it will try to connect the main server again.

✧ *<Buffer Mode>*: The working mode the buffer report function. When buffer report function is enabled, if the device goes into areas without network covering, it will store all reports locally. When the device goes back to areas with network covering, then it will send all the buffered reports through network.

- 0: Disable the buffer report function.
- 1: Low priority. The buffer report function is enabled and the device will send the buffered messages after sending the normal messages.
- 2: High priority. The buffer report function is enabled and the device will send all the buffered messages before sending any normal message except the SOS message (+RESP:GTSOS).

✧ *<Main Server IP/Domain Name>*: The IP address or the domain name of the primary server. This field defines the header part of the URL. The whole URL for the HTTP GET method will

be header part plus the message to be sent. It excludes the header "HTTP://". For example: "[www.queclink.com:8080/reports/parse.php?str=](http://www.queclink.com:8080/reports/parse.php?str=)". If port is not included in the URL, the terminal will connect to the default port of HTTP protocol, 80.

- ✧ <Main Server Port>: The port of the primary server.
- ✧ <Backup Server IP/Domain Name>: The IP address or the domain name of the backup server.
- ✧ <Backup Server Port>: The port of the backup server.
- ✧ <SMS Gateway>: Maximum 20 characters (including the optional national code starting with "+"). Short code (for example: 10086) is also supported.
- ✧ <Heartbeat Interval>: the interval of sending heartbeat package message (+ACK:GTHBD) when report mode is TCP long-connection mode or UDP mode. If it is set to 0, there will be no heartbeat package message sending.
- ✧ <SACK Enable>: This defines whether the backend server should respond to the terminal with SACK messages when receiving messages from the terminal.
  - 0: The backend server does not reply SACK message after receiving message from the terminal.
  - 1: The backend server replies a SACK message when receiving a message from the terminal.
  - 2: The backend server replies a SACK message when receiving a message from the terminal, but the terminal does not check the serial number of the SACK message.
- ✧ <Protocol Format>: This defines the format of the message sent from the device to the backend server. 0 means using the ASCII format, and 1 means using the HEX format.
- ✧ <SMS ACK Enable>: This defines whether the ACK confirmation should be responded by SMS when the command was sent by SMS.
  - 0: The device will send the ACK confirmation according to the mode configured by the <Report Mode>.
  - 1: The device will send the ACK confirmation by SMS to the phone which sends the command by SMS.

The acknowledgment message of **AT+GTSRI** command:

➤ **+ACK:GTSRI,**

Example:			
+ACK:GTSRI, ED0101,862170019025640,,0001,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	

Tail Character	1	\$	\$
----------------	---	----	----

**Note:**

Only after both the command **AT+GTBSI** and **AT+GTSRI** are properly set can the ACK messages and other messages be sent to the backend server.

**3.2.1.3. Quick Start Setting**

The command **AT+GTQSS** is used to configure the parameters for network data connection and backend server information in one command if all these settings are within 160 bytes, otherwise use **AT+GTBSI** and **AT+GTSRI**.

➤ **AT+GTQSS=**

<b>Example:</b> <b>AT+GTQSS=gv600m,,,,,3,,1,116.226.44.17,7011,116.226.45.229,7012,+8613812341234,15,1,,,0002\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	APN	<=40		
3	APN User Name	<=30		
4	APN User Password	<=30		
5	Report Mode	1	0 – 8	0
6	Reserved	0		
7	Buffer Mode	1	0 1 2	1
8	Main Server IP/ Domain Name	<=60		
9	Main Server Port	<=5	0 – 65535	
10	Backup Server IP/ Domain Name	<=60		
11	Backup Server Port	<=5	0 – 65535	
12	SMS Gateway	<=20		
13	Heartbeat Interval	<=3	0 5 – 360min	0
14	SACK Enable	1	0 1 2	0
15	Protocol Format	1	0 1	0
16	SMS ACK Enable	1	0 1	0
	Serial Number	4	0000 – FFFF	

	Tail Character	1	\$	\$
--	----------------	---	----	----

The acknowledgment message of **AT+GTQSS** command:

➤ **+ACK:GTQSS,**

Example:			
<b>+ACK:GTQSS, ED0101,862170019025640,,0002,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2. Device Configuration

#### 3.2.2.1. Global Configuration

The **AT+GTCFG** command is used to configure the global parameters.

➤ **AT+GTCFG=**

Example:				
<b>AT+GTCFG=gv600m,123456,gv600m,,,,,,,,,,,,,,,,,,,,,0003\$</b>				
<b>AT+GTCFG=gv600m,,,1,123.4,0,,0,1,,2FF,0,1,1,300,0,1,1,,,0,0003\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	New Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	
3	Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	gv600m
4	ODO Enable	1	0 1	0
5	ODO Initial Mileage	<=9	0.0 – 4294967.0Km	0.0
6	Reserved	0		
7	Reserved	0	0	0
8	Report Composition Mask	4	0000 – FFFF	003F

9	Power Saving Mode	1	0 – 3	1
10	Reserved	0		
11	Event Mask	4	0000 – FFFF	3DEF
12	IO Mode	1	0-F	0
13	LED On	1	0 1	0
14	Info Report Enable	1	0 1	0
15	Info Report Interval	<=5	30 – 86400sec	300
16	Location Request Mask	2	00 20	00
17	Reserved			
18	Backup Battery Charge Mode	1	0 1	0
19	AGPS Mode	1	0 1	0
20	GSM Report	4	0000 – FFFF	001F
21	GPS Lost Time	2	0 – 30min	0
22	Reserved			
23	Reserved			
24	Reserved	0		
25	Reserved	0		
26	Reserved	0		
27	Wakeup hour interval	<=3	1-720(hour)	24
28	Sensor wakeup device debounce	<=2	0 10-60(s)	10
29	Work Time per Wakeup	<=2	5-60(min)	15
30	Power Output	1	0 1	0
31	Temperature sample timer	<=3	0 10– 255(s)	0
32	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <New Password>: Change the current password with a new one.
- ✧ <Device Name>: An ASCII string to represent the name of the device.
- ✧ <ODO Enable>: Enable/Disable the odograph function to calculate the total mileage. The current mileage is included in every position message.

- ✧ **<ODO Initial Mileage>**: The initial value for calculating the total mileage.
- ✧ **<Report Composition Mask>**: Bitwise report mask to configure the composition of message, especially the GPS message composition.
  - Bit 0 for **<Speed>**
  - Bit 1 for **<Azimuth>**
  - Bit 2 for **<Altitude>**
  - Bit 3 for Network data, including **<MCC>**, **<MNC>**, **<LAC>**, **<Cell ID>** and the **<reserved>** parameter "00"
  - Bit 4 for **<Mileage>**
  - Bit 5 for **<Send Time>**
  - Bit 6 for **<Device Name>**

For each bit, set it to 1 to enable corresponding component in the report and 0 to disable. This mask is effective to all messages.

- ✧ **<Power Saving Mode>**: Set the mode of power saving function. If the mode of power saving function is set to 0, the fixed report will follow **<IGF Report Interval>** when the engine is off. If the mode of power saving function is set to 1, the fixed report, geo-fence and speed alarm report functions are suspended when the device is static or the engine is off. If the mode of power saving function is set to 2, it is like mode 1 with the difference is that the fixed report will not be suspended and the fix and sending interval will be set to **<IGF Report Interval>** in **AT+GTFRI** when the engine is off.
  - 0: Disable power saving function
  - 1: GPS deep saving mode
  - 2: GPS low saving mode
  - 3: GSM deep saving mode
- ✧ **<Event Mask>**: Bitwise mask to configure which event report should be sent to the backend server.
  - Bit 0 for **+RESP:GTPNA**
  - Bit 1 for **+RESP:GTPFA**
  - Bit 2 for **+RESP:GTMPN**
  - Bit 3 for **+RESP:GTMPF**
  - Bit 4 is reserved
  - Bit 5 for **+RESP:GTBPL**
  - Bit 6 for **+RESP:GTBTC**
  - Bit 7 for **+RESP:GTSTC**
  - Bit 8 for **+RESP:GTSTT**
  - Bit 9 for reserved
  - Bit 10 for **+RESP:GTPDP**
  - Bit 11 for **+RESP:GTPNL**
  - Bit 12 for the ignition report **+RESP:GTIGN** and **+RESP:GTIGF**
  - Bit 13 for location report **+RESP:GTIGL** when ignition on or ignition off
  - Bit 14 for **+RESP:GTEXP**.

For each bit, set it to 1 to enable corresponding event report and 0 to disable.

- ✧ **<IO Mode>**: Configure the working mode of IO1-IO4 on the connector.
  - Bit0: 0-Input1, 1-Output1



- Bit1: 0-Input2, 1-Output2
- Bit2: 0-Input3, 1-Output3
- Bit3: 0-Input4, 1-Output4
- ✧ <LED On>: Configure the working mode of power LED and GPS LED.
  - 0: Each time the device powers on, both LEDs will work for 30 minutes and then are turned off deadly.
  - 1: Turn on Power LED and GPS LED if necessary.
- ✧ <Info Report Enable>: Enable/Disable the device information report function (**+RESP:GTINF**). The device information includes: state of the device, received signal strength, voltage of external power supply, battery voltage, charging status, Power and GPS LED working mode, the last known time of GPS fix, analog input voltage, all digit inputs and outputs status.
  - 0: Disable the device information report function.
  - 1: Enable the device information report function.
- ✧ <Info Report Interval>: The interval of reporting the device information.
- ✧ <Location Request Mask>: Bitwise mask for SMS request position. 4 high bits for SMS request and 4 low bits for reserved. Each bit, from bit 4 to bit 7, represents one kind of reports. Set to 1 to enable and 0 to disable corresponding report.
  - Bit 5: Report the current position with Google Map link through SMS to the original number when the device receives SMS Request Position message via SMS.
- ✧ <Backup Battery Charge Mode>: Control the charge mode of the backup battery.
  - 0: When the main power supply is connected, charge the backup battery on need.
  - 1: When the main power supply is connected, the backup battery will be charged only when ignition on is detected. The charge process will begin 3 minutes after the ignition on. The charge process is stopped after ignition off.
- ✧ <AGPS Mode>: A numeric to indicate the AGPS mode. AGPS is helpful to improve the chance to get GPS position successfully and reduce the time to get GPS position.
  - 0: Disable the AGPS function.
  - 1: AGPS Offline mode.
- ✧ <GSM Report>: It controls how or when to report cell information. The message **+RESP:GTGSM** is only sent via TCP short connection even if the report mode is Force on SMS.

The 2 high bits, Bit 14 – 15, represent the GSM report mode.

- 0: Do not allow the cell information report.
- 1: Allow the cell information report after failing to get GPS position if cell information is available.
- 2: Report the message **+RESP:GTGSM** after each successful GPS fix if cell information is available.
- 3: Report the message **+RESP:GTGSM** regardless of getting GPS position is successful or not if cell information is available.

Bitwise mask to configure which event report should be sent to the backend server.

- Bit 0 for **+RESP:GTRTL**
- Bit 1 for **+RESP:GTLBC**
- Bit 2 for **+RESP:GTFRI/+RESP:GTERI**
- Bit 3 for **+RESP:GTSOS**

- Bit 4 for **+RESP:GTTOW**
- Bit 5 – 13 are reserved

For each bit, set it to 1 to enable the corresponding event report, and 0 to disable the corresponding event report

- ✧ **<GPS Lost Time>**: A time parameter to monitor the GPS signal. If the device stays **<GPS Lost Time>** consecutively without GPS signal or without successful GPS fix, it will send the event report **+RESP: GTGSS** to indicate the GPS signal is lost. When the GPS signal is recovered or a successful fix is obtained again, the device will send the event report **+RESP:GTGSS** to indicate the recovery. 0 minute means to disable this function.
- ✧ **<Wakeup hour interval>**: A numeral to specify the interval to wake up the terminal. The value 24 means the terminal wakes up once per 24 hours.
- ✧ **<Sensor wakeup device debounce>**: A numeral to specify the debounce time for sensor for waking up the terminal in the GSM deep saving mode, 0 means no wakeup device.
- ✧ **<Work Time per Wakeup>**: Set work time per Wakeup, the value range 5 – 60 minutes and the default value is 15 minutes.
- ✧ **<Power Output>**: Set 5V(or 3.3V) output, enable or disable
- ✧ **<Temperature sample timer>**: Temperature sample interval. All sensors are read every time.

The acknowledgment message of **AT+GTCFG** command:

➤ **+ACK:GTCFG,**

Example: <b>+ACK:GTCFG, ED0101,862170019025640,,0003,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2.2. Auto-Unlock PIN

The **AT+GTPIN** command is used to unlock the USIM automatically.

➤ **AT+GTPIN=**

Example: <b>AT+ GTPIN=gv600m,1,1234,1,,,,,0011\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default

1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Auto Unlock PIN	1	0 1	0
3	PIN	4-8	'0'-'9'	
4	Reserved			
5	Reserved			
6	Reserved			
7	Reserved			
8	Reserved			
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Auto Unlock PIN>: A numeric to indicate whether to unlock the USIM-PIN for the device.
  - 0: Do not unlock USIM-PIN automatically.
  - 1: Each time the device powers on, it will detect whether the USIM card is locked with a PIN. If it is locked, the device will unlock the PIN automatically.
- ✧ <PIN>: The PIN code which is used to unlock the USIM automatically. If it is empty, the PIN code saved in the device will be cleared.

The acknowledgment message of **AT+ GTPIN** command:

➤ **+ACK: GTPIN,**

Example:			
<b>+ACK: GTPIN, ED0101,862170019025640,,0011,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2.3. Protocol Watchdog

The **AT+GTDG** command is used to reboot the device or network module in a time based manner or upon ignition. This helps the device avoid working in an abnormal status for a long time. Besides these two automatic reboot methods, the device also supports using the digital input to trigger the reboot manually.

➤ **AT+GTDG=****Example:**

AT+GTDG=gv600m,1,,1,0130,,1,1,,60,,0011\$

AT+GTDG=gv600m,2,30,,,,1,2,,60,,0011\$

AT+GTDG=gv600m,0,60,25,,,1,0,1,60,60,60,0011\$

SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2	1
3	Ignition Frequency	<=3	10 – 120 min	60
4	Interval	<=2	1 – 30 day/hour	7
5	Time	4	HHMM	0200
6	Reserved	0		
7	Report Before Reboot	1	0 1	1
8	Input ID	1	0 1 2 3 4	0
9	Unit	1	0 1	0
10	No Network Interval	<=4	0   5-1440 min	480
11	No Activation interval	<=4	0   5-1440 min	480
12	Send Failure timeout	<=4	0   5-1440 min	480
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ **<Mode>**: Working mode.

- 0: Disable this function
- 1: Reboot periodically according to the **<Interval>** and **<Time>** setting.
- 2: Reboot when ignition on.

✧ **<Ignition Frequency>**: When the working mode is 2, if the time interval between this ignition and last ignition is greater than the specified value in Ignition Frequency, the device will automatically reboot upon ignition on. If the function is enabled for the first time, the device will reboot at next ignition even if the interval is less than the value set in Ignition Frequency.

✧ **<Interval>**: The interval to reboot the device per days or hours.

✧ **<Time>**: At what time to perform the reboot when **<Interval>** is met.

✧ **<Report Before Reboot>**: Whether to report the **+RESP:GTDG** message before reboot. 0 means not to report and 1 to report. If this parameter is enabled, the device will obtain a real-time location and send it to the server.

✧ **<Input ID>**: ID of the digital input port which is used to trigger the manual reboot. 0 means

no manual reboot. Digital input ports 1 and 4 are supported.

- ✧ <Unit>: Unit
  - 0: Unit is day.
  - 1: Unit is hour.
- ✧ <No Network Interval>: The interval to reboot the device when in no network signal. 0 means no rebooting the device.
- ✧ <No Activation Interval>: The interval to reboot the device when PDP is unable to register or message interaction failed (such as no TCP Ack, Sever Ack). 0 means no rebooting the device.
- ✧ <Send Failure Timeout>: The device will reboot automatically if report sending time is greater than <Send Failure Timeout>. 0 minute means no rebooting the device.

The acknowledgment message of AT+GTDOG command:

➤ **+ACK:GTDOG,**

Example:			
+ACK:GTDOG, ED0101,862170019025640,,0011,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2.4. Time Adjustment

The **AT+ GTTMA** command is used to adjust local time.

➤ **AT+ GTTMA =**

Example:				
AT+ GTTMA =gv600m ,-,3,30,0,20090917203500,,,,,0006\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Sign	1	+ -	+
3	Hour Offset	<=2	0-12	00
4	Minute Offset	<=2	0-59	00

5	Daylight Saving	1	0 1	0
6	UTC Time	14	YYYYMMDDHHMMSS	
7	Reserved			
8	Reserved			
9	Reserved			
10	Reserved			
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Sign>: Indicate the positive or negative of the local time offset to UTC
- ✧ <Hour Offset>: UTC offset in hours
- ✧ <Minute Offset>: UTC offset in minutes
- ✧ <Daylight Saving>: Enable/disable daylight saving time.
  - 0: Disable daylight saving
  - 1: Enable daylight saving
- ✧ <UTC time>: The UTC time.

The acknowledgment message of **AT+ GTTMA** command:

➤ **+ACK: GTTMA,**

Example:			
<b>+ACK: GTTMA, ED0101,862170019025640,,0011,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2.5. Outside Working Hours

To protect the privacy of the drivers when they are off duty, the device could be configured to report empty location information during the outside working hours. The command **AT+GTOWH** is used to define the working hours and the working mode. When this function is enabled, the device will send empty latitude, empty longitude, empty LAC and empty Cell ID in all the messages except **+RESP:GTSOS**.

➤ **AT+GTOWH=****Example:****AT+GTOWH=gv600m,1,1F,0900,1200,1300,1730,,,3,1,1,0,,,,,0010\$**

SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2 3	0
3	Day of Work	<=2	0 – 7F	1F
4	Working Hours Start1	4	HHMM	0900
5	Working Hours End1	4	HHMM	1200
6	Working Hours Start2	4	HHMM	1300
7	Working Hours End2	4	HHMM	1800
8	Reserved	0		
9	Reserved	0		
10	Digital Input ID	1	0 – 4	0
11	Output ID	1	0 – 4	0
12	Output Status	1	0 1	
13	Duration	<=3	0 – 255(×100ms)	0
14	Toggle Times	<=3	0 – 255	0
15	Reserved	0		
16	Reserved	0		
17	Reserved	0		
18	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ **<Mode>: Working Mode.**

- 0: Disable this function.
- 1: Manual Mode. In this mode, location information will be hidden under two conditions: the device works at outside the working hours and digital input is triggered.
- 2: Full Manual Mode. In this mode, location information will be hidden under the following condition: the digital input is triggered.
- 3: Automatic Mode. In this mode, location information will be hidden under the

following condition: the device works at outside the working hours.

- ✧ *<Day of Work>*: Specify the working days in a week in a bitwise manner.
  - Bit 0 for Monday
  - Bit 1 for Tuesday
  - Bit 2 for Wednesday
  - Bit 3 for Thursday
  - Bit 4 for Friday
  - Bit 5 for Saturday
  - Bit 6 for Sunday

For each bit, 0 means off duty day and 1 means working day.
- ✧ *<Working Hours Start1>, <Working Hours End1>*: The first period of the working hours in a day.
- ✧ *<Working Hours Start2>, <Working Hours End2>*: The second period of the working hours in a day.
- ✧ *<Digital Input ID>*: The input ID used to trigger this function when mode is 1 or 2. The working parameters of the specified input must be set by **AT+GTDIS** first. If using interruptible digital input, please connect slide button instead of tact button to that input.
- ✧ *<Output ID>, <Output Status>, <Duration> and <Toggle Times>*: When this function is enabled and it is off duty time, the specified waveform will be output to the specified output.

The acknowledgment message of **AT+GTOWH** command:

➤ **+ACK:GTOWH,**

Example:			
<b>+ACK:GTOWH, ED0101,862170019025640,,0010,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.2.6. Preserve Special Device Logical State Setting

The command **AT+GTPDS** is used to preserve special device logical state for the terminal. According to the working mode, the function is enabled or disabled. According to the value of the MASK, specified logical state(s) will be saved.



➤ **AT+GTPDS=**

Example: AT+GTPDS=gv600m,1,0,,,,,,001A\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2	1
3	Mask	4	0000-07FF	7FF
4	Reserved			
5	Reserved			
6	Reserved			
7	Reserved			
8	Reserved			
9	Reserved			
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ **<Mode>**:

- 0: Disable this function
- 1: Preserve special device logical state according to the value of the MASK
- 2: Reset all the special logical states of the device that listed in the **<Mask>** after receiving the command, and then preserve the special logical state of the device according to the value of the **<Mask>**.

✧ **<Mask>**: Bitwise mask to configure which device states will be preserved. Each bit represents a state.

- Bit 0: States of GEO
- Bit 1: Reserved bit
- Bit 2: Reserved bit
- Bit 3: Information of last known position
- Bit 4: State of ignition
- Bit 5: State of waveform 1
- Bit 6: State of digital input
- Bit 7: State of SPD
- Bit 8: Reserved bit
- Bit 9: State of main power
- Bit 10: State of PEO

The acknowledgment message of AT+GTPDS command:

➤ **+ACK:GTPDS,**

Example:

+ACK:GTPDS, ED0101,862170019025640,,001A,20140511093254,FFFF\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.3. Position Related Report

#### 3.2.3.1. Fixed Report Information

The command **AT+GTFRI** is used to configure the parameters of scheduled report (**+RESP:GTFRI** or **+RESP:GTERI**).

#### ➤ AT+GTFRI=

Example:

AT+GTFRI=gv600m,0,,,,,,,,,,,,,0009\$

AT+GTFRI=gv600m,1,1,,1,1000,2300,,30,,,,,600,,,,,0009\$

AT+GTFRI=gv600m,2,1,,1,1000,2300,,,500,,,,,,,,,0009\$

AT+GTFRI=gv600m,3,1,,1,1000,2300,,,1000,,,,,,,,,0009\$

AT+GTFRI=gv600m,4,1,,1,1000,2300,,60,,300,,,,,,,,,0009\$

SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 – 5	0
3	Discard No Fix	<=2	0 1	1
4	Reserved	0		
5	Period Enable	1	0 1	1
6	Start Time	4	HHMM	0000
7	End Time	4	HHMM	0000
8	Reserved	0		
9	Send Interval	<=5	5 – 86400sec	30

10	Distance	<=5	50 – 65535m	1000
11	Mileage	<=5	50 – 65535m	1000
12	Reserved	0		
13	Corner Report	<=3	0 – 180	0
14	IGF Report Interval	<=5	0 5-86400sec	600
15	ERI Mask	8	00000000-FFFFFFFF	00000000
16	FRI enable for GSM DEEP	1	0 1	0
17	Reserved	0		
18	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: The working mode of the fixed report.

- 0: Disable this function.
- 1: Fixed Timing Report. The position message is sent to the backend server periodically according to the parameter <Send Interval>.
- 2: Fixed Distance Report. The position message is sent to the backend server when the straight-line distance between the current GPS position and the last sent GPS position is greater than or equal to the distance specified by parameter <Distance>.
- 3: Fixed Mileage Report. The position message is sent to the backend server when the path length between the current GPS position and the last sent GPS position is greater than or equal to the mileage specified by parameter <Mileage>. It requires connecting the vehicle ignition signal to the specified digital input port of the device to use this function.
- 4: Optimum Report. Optimum Report mode combines the Fixed Timing Report and Fixed Mileage Report. Only when the report time interval is greater than or equal to the <Send Interval> and the cumulative mileage is greater than or equal to the <Mileage> will the Optimum Report be sent to the server. It requires connecting the vehicle ignition wire to the specified digital input port of the device to use this function..
- 5: Fixed Time or Mileage Report. Fixed Time or Mileage Report mode combines the Fixed Timing Report and Fixed Mileage Report. The device will detect <Send Interval> and the <Mileage> at the same time. As long as one of them meets the conditions, the report will be sent to the server. It requires connecting the vehicle ignition wire to the specified digital input port of the device to use this function.

Note: If the engine is off, the positional message is sent to the backend server periodically according to the parameter <IGF Report Interval>.

✧ <Discard No Fix>: Disable/Enable reporting when there is no GPS fixing

- 0: Enable reporting
- 1: Disable reporting
- ✧ <Period Enable>: Disable/enable the time range specified by <Start time> and <End time>. If the time range is enabled, the position reporting is limited within the time range.
- ✧ <Start Time>: The start time of the scheduled fixed report. The valid format is "HHMM". The value range of "HH" is "00"–"23". The value range of "MM" is "00"–"59".
- ✧ <End Time>: The end time of the scheduled fixed report. The valid format and range are as same as <Start Time>.
- ✧ <Send Interval>: Period to send the position information. The value range is 5 – 86400 and the unit is second. If <Report Mode> in **AT+GTSRI** is set to Force on SMS, <Send Interval> should be greater than 15 seconds, otherwise the reports will be sent via TCP short connection.
- ✧ <Distance>: The specified distance to send the position information when <Mode> is 2. Unit: meter.
- ✧ <Mileage>: The specified length to send the position information when <Mode> is 3 and 4. Unit: meter.
- ✧ <Corner Report>: The threshold to determine whether the device is turning around a corner. 0 is to disable the corner report. For other values, the device will compare the current azimuth with the last known one, if the difference is greater than or equal to this value, the corner report is sent with **+RESP:GTFRI**.
- ✧ <IGF Report Interval>: Period to fix and send the position information when <Power Saving Mode> in **AT+GTCFG** is set to 2, the engine is off and <Mode> is set to 1 (Fixed Timing Report). Its value range is 0|5 – 86400 and the unit is second.
- ✧ <ERI Mask>: If the serial port is connected to peripherals and the mask is not 0x00000000, the device will send **+RESP:GTERI** instead of **+RESP:GTFRI**. This mask is used to configure whether to report the data from peripherals by **+RESP:GTERI**.
  - Bit 0 for reserved.
  - Bit 1 for temperature sensor.
  - Bit 2 for reserved.
  - Bit 3 for <Percentage> field in the report of **+RESP:GTERI**. If it is set to 1, the data block <Fuel Sensor Data> will be displayed.
  - Bit 4 for <Volume> field in the report of **+RESP:GTERI**. If it is set to 1, the data block <Fuel Sensor Data> will be displayed.
- ✧ <FRI enable for GSM DEEP>: This field is valid only for GSM deep mode. After device is waken up, if device is under ignition off state, FRI report will be sent regularly at the interval of "IGF Report Interval", and tow function will be disabled at this time.

The acknowledgment message of **AT+GTFRI** command:

➤ **+ACK:GTFRI,**

Example:			
<b>+ACK:GTFRI, ED0101,862170019025640,,0009,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' –	

		'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.3.2. Frequency Change of Fixed Report Information

The command **AT+GTFFC** is used to change the parameters of fixed report when certain event occurs. When the event disappears, the device will restore to its previous settings.

The device supports up to 5 sets of parameter for different events. Priority is assigned among these events. Only the set of parameters with the highest priority event will be executed if more than one event occurs at the same time.

#### ➤ AT+GTFFC=

Example:				
AT+GTFFC=gv600m,0,1,0,30,500,500,300,,,,,0016\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Priority	1	0-4	0
3	Mode	1	0-3	0
4	FRI Mode	1	0-5	0
5	FRI IGN Report Interval	<=5	5-86400s	30
6	FRI Report Distance	<=5	50-65535m	500
7	FRI Report Mileage	<=5	50-65535m	500
8	FRI IGF Report Interval	<=5	0 5-86400s	300
9	Reserved			
10	Corner Report	<=3	0 – 180	0
11	Reserved			
12	Reserved			
	Serial Number	4	0000 – FFFF	

	Tail Character	1	\$	\$
--	----------------	---	----	----

- ✧ <Priority>: Priority of the event which triggers the parameter change for fixed report. 0 has the highest priority.
- ✧ <Mode>: Specify the trigger event to change the fixed report parameters.
  - 0: Disable the parameters in the specified priority.
  - 1: Change the fixed report parameter when the device enters into any of the defined Geo-Fence.
  - 2: Change the fixed report parameter when the device enters into known roaming state.
  - 3: Change the fixed report parameter when the device enters into unknown roaming state.
- ✧ <FRI Mode>: When the specified event occurs, the working mode of the fixed report will be changed according to this parameter.
  - 0: Do not change the working mode
  - 1: Change the working mode to 'Timing Report'.
  - 2: Change the working mode to 'Distance Report'.
  - 3: Change the working mode to 'Mileage Report'.
  - 4: Change the working mode to 'Optimum Report'.
  - 5: Change the working mode to 'Fixed Time or Mileage Report'.
- ✧ <FRI IGN Report Interval>: Period to send the position information when ignition is on. The value range is 5 – 86400 and the unit is second.
- ✧ <FRI Report Distance>: The specified distance to send the position information when it is changed to fixed distance report. Unit: meter.
- ✧ <FRI Report Mileage>: The specified path length to send the position information when it is changed to fixed mileage report or optimum report. Unit: meter.
- ✧ <FRI IGF Report Interval>: Period to fix and send the position information when ignition is off if <Power Saving Mode> in **AT+GTCFG** is set to 2 and <FRI Mode> in this command is set to 1 (Fixed Timing Report). The value range is 0|5 – 86400 and the unit is second.
- ✧ <Corner Report>: The threshold to determine whether the device is turning around a corner. 0 means "Disable the corner report". For other values, the device will compare the current azimuth with the last known one, if the difference is greater than or equal to this value, the device will send the corner report with **+RESP:GTFRI**.

The acknowledgment message of **AT+GTFFC** command:

➤ **+ACK:GTFFC,**

Example:			
<b>+ACK:GTFFC, ED0101,862170019025640,,0016,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	

Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' ' ' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4. Alarm Settings

#### 3.2.4.1. Circular Geo-Fence Information

The command **AT+GTGEO** is used to configure the parameters of Circular Geo-Fence. (Geo-Fence is a virtual perimeter on a geographic area. When the terminal enters or exits the area, a notification will be generated. The notification contains information about the location of the terminal and can be sent to the backend server.)

#### ➤ AT+GTGEO=

Example: AT+GTGEO=gv600m,0,3,121.412248,31.187891,1000,600,1,1,0,0,0,0,,,000A\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	GEO ID	<=2	0 – 19	
3	Mode	1	0 – 3	0
4	Longitude	<=11	(-)xxx.xxxxxx	
5	Latitude	<=10	(-)xx.xxxxxx	
6	Radius	<=7	50 – 6000000m	50
7	Check Interval	<=5	0 5 – 86400sec	0
8	Output ID	1	0 – 4	0
9	Output Status	1	0 1	
10	Duration	<=3	0 – 255(×100ms)	0
11	Toggle Times	<=3	0 – 255	0
12	Trigger Mode	<=2	0 21 22	0
13	Trigger Report	1	0 1	0
14	Reserved	0		
15	Reserved	0		

	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <GEO ID>: ID of the circular Geo-Fence. Total 20 zones, 0 to 19, are supported.
- ✧ <Mode>: The working mode of the circular Geo-Fence to send the message **+RESP:GTGIN** or **+RESP:GTGOT** to the backend server.
  - 0: Disable the zone's Geo-Fence function.
  - 1: Entering the zone. The report will be generated only when the terminal enters the Geo-Fence.
  - 2: Exiting the zone. The report will be generated only when the terminal exits from the Geo-Fence.
  - 3: Both entering and exiting.
- ✧ <Longitude>: The longitude of a point which is defined as the center of the Circular Geo-Fence region. The format is "(–) xxx.xxxxxx" and the value range is from "–180.000000" to "180.000000". The unit is degree. West longitude is defined as negative value starting with "–" and east longitude is defined as positive value without "+".
- ✧ <Latitude>: The latitude of a point which is defined as the centre of the circular Geo-Fence region. The format is "(–) xx.xxxxxx" and the value range is from "–90.000000" to "90.000000". The unit is degree. South Latitude is defined as negative value starting with "–" and north Latitude is defined as positive value without "+".
- ✧ <Radius>: The radius of the circular Geo-Fence region. The value range is 50 – 6000000 and the unit is meter.
- ✧ <Check Interval>: The interval of GPS checking for the circular Geo-Fence alarm.
- ✧ <Trigger Mode>:
  - 0: Disable auto trigger mode
  - 21: Automatically set circular Geo Fence after ignition off. In this mode, the device will automatically set a circular Geo-Fence with the current location as the center point of the Geo-Fence when ignition is off. This circular Geo-Fence will only report exiting alarm. The circular Geo-Fence will be cancelled after exiting
  - 22: Manually enable circular Geo-Fence after ignition off. In this mode, the device will automatically set a circular Geo-Fence with the current location as the center point of the Geo-Fence when ignition is off. This circular Geo-Fence will only report exiting alarm. When the device exits this circular Geo-Fence, it will cancel this circular Geo-Fence and disable the trigger mode at the same time. The driver has to manually set it again if he/she wants to use this trigger mode next time.
- ✧ <Trigger Report>: Whether to send **+RESP:GTGES** message when specified trigger mode is triggered and when the Geo-Fence is cancelled.
  - 0: Disable report **+RESP: GTGES**.
  - 1: Enable report **+RESP: GTGES**.

The acknowledgment message of **AT+GTGEO** command:

➤ **+ACK:GTGEO,**

**Example:**



+ACK:GTGEO,ED0101,862170019025640,,0,000A,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
GEO ID	<=2	0 – 19	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.2. Polygon Geo-Fence

The command **AT+GTPEO** is used to configure the parameters of Polygon Geo-Fence. (Geo-Fence is a virtual perimeter on a geographic area. When the terminal enters or exits the area, a notification will be generated. The notification contains information about the location of the terminal and can be sent to the backend server.)

#### ➤ AT+GTPEO=

Example: AT+GTPEO=gv600m,0,0,1,3,121.412240,31.187801, 121.412248,31.187891,121.412258,31.187991,600,1,1,0,0,,,,,0039\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	GEO ID	<=2	0 – 19	0
3	Mode	1	0 – 3	0
4	Start Point	1	1-18	1
5	End Point	<=2	3-10	3
5+2N-1	Longitude	<=11	(-)xxx.xxxxxx	
5+2N	Latitude	<=10	(-)xx.xxxxxx	
6+2N	Check Interval	<=5	0 5 – 86400sec	0
7+2N	Output ID	1	0 – 4	0
8+2N	Output Status	1	0 1	

9+2N	Duration	<=3	0 – 255(×100ms)	0
10+2N	Toggle Times	<=3	0 – 255	0
11+2N	Reserved	0		
12+2N	Reserved	0		
13+2N	Reserved	0		
14+2N	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <GEO ID>: ID of the polygon Geo-Fence. Total twenty zones, 0 to 19, are supported.
  - ✧ <Mode>: The working mode of the Polygon Geo-Fence to send the message **+RESP:GTGIN** or **+RESP:GTGOT** to the backend server.
    - 0: Disable the Geo-Fence function.
    - 1: Entering the zone. The report will be generated only when the terminal enters the Geo-Fence.
    - 2: Exiting the zone. The report will be generated only when the terminal exits the Geo-Fence.
    - 3: Both entering and exiting.
  - ✧ <Start Point>: The start point of the polygon GEO-Fence.
  - ✧ <End Point>: The end point of the polygon GEO-Fence.
  - ✧ <Longitude>: The longitude of a point which is defined as the endpoint of the polygon Geo-Fence region. The format is “(-)xxx.xxxxxx” and the value range is from “-180.000000” to “180.000000”. The unit is degree. West longitude is defined as negative value starting with “-” and east longitude is defined as positive value without “+”.
  - ✧ <Latitude>: The latitude of a point which is defined as the endpoint of the polygon Geo-Fence region. The format is “(-)xx.xxxxxx” and the value range is from “-90.000000” to “90.000000”. The unit is degree. South Latitude is defined as negative value starting with “-” and north Latitude is defined as positive value without “+”.
- Note: For more groups of <Longitude> and <Latitude>, please use <Start Point> and <End point> to adjust, marked <Longitude> and <Latitude> means repeat.
- ✧ <Check Interval>: The checking interval for the Geo-Fence alarm.

The acknowledgment message of **AT+GTPEO** command:

➤ **+ACK:GTPEO,**

Example:			
<b>+ACK:GTPEO, ED0101, 862170019025640,,0,000B,20140221113250,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {‘A’ – ‘Z’, ‘0’ – ‘9’}	

Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
GEO ID	1	0 – 19	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.3. Tow Alarm Configuration

The **AT+GTTOW** command is used to configure the motion sensor and the parameters for tow alarm.

#### ➤ AT+GTTOW=

Example: AT+GTTOW= gv600m,0,120,120,,0,0,0,,,,,,,,,000D\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Tow Enable	1	0 1	0
3	Engine Off to Tow	<=2	5 – 15 min	10
4	Fake Tow Delay	<=2	0 – 10 min	1
5	Tow Interval	<=5	30 – 86400 sec	300
6	Tow Output ID	1	0 – 4	
7	Tow Output Status	1	0 1	
8	Tow Output Duration	<=3	0 – 255 (×100ms)	0
9	Tow Output Toggle Times	<=3	0 – 255	0
10	Rest Duration	<=3	1 – 255 (×15sec)	2
11	Motion Duration	<=2	1 – 10 (×100ms)	3
12	Motion Threshold	1	2 – 9	4
13	Tow Mileage Enable	1	0 1	0
14	Reserved	0		
15	Reserved	0		

16	Reserved	0		
17	Reserved	0		
18	Reserved	0		
19	Reserved	0		
20	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ **<Tow Enable>**: Enable or disable tow alarm (**+RESP:GTTOW**).
  - 0: Disable the tow alarm
  - 1: Enable the tow alarm
- ✧ **<Engine Off to Tow>**: A time parameter to judge whether the device is considered to be towed after the engine off. If the motion sensor doesn't detect stillness within the specified time after engine off, the device is being towed.
- ✧ **<Fake Tow Delay>**: After engine off and stillness detected, if the motion sensor detects moving again, the device goes into a state called fake tow. If the device keeps in fake tow beyond the period of time defined by the parameter **<Fake Tow Delay>**, it is considered to be towed.
- ✧ **<Tow Interval>**: The period to send tow alarm message.
- ✧ **<Tow Output ID>**: The ID of the output port to send the specified waveform when tow event is detected.
- ✧ **<Tow Output Status>**: Please refer to the parameter **<Output1–4 Status>** in chapter 3.2.5.1.
- ✧ **<Tow Output Duration>**: Please refer to the parameter **<Duration>** in chapter 3.2.5.1.
- ✧ **<Tow Output Toggle Times>**: Please refer to the parameter **<Toggle Times>** in chapter 3.2.5.1.
- ✧ **<Tow Mileage Enable>**: Enable or disable current tow mileage (**+RESP:GTTOW**).
  - 0: Disable the tow mileage, current total mileage.
  - 1: Enable current tow mileage.

The acknowledgment message of **AT+GTTOW** command:

➤ **+ACK:GTTOW,**

Example:			
<b>+ACK:GTTOW, ED0101,862170019025640,,000B,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	

Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

#### 3.2.4.4. Speed Alarm

This command is used to set speed-alarm range for the terminal. According to the working mode, the terminal will send message **+RESP:GTSPD** to the backend server when its moving speed is outside or inside the range.

##### ➤ AT+GTSPD=

Example: AT+GTSPD=gv600m,1,80,120,60,300,1,1,0,0,,,,,,,,,000C\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2 3 4	0
3	Min Speed	<=3	0 – 400km/h	0
4	Max Speed	<=3	0 – 400km/h	0
5	Validity	<=4	0 – 3600sec	60
6	Send Interval	<=4	30 – 3600sec	300
7	Output ID	1	0 – 4	0
8	Output Status	1	0 1	
9	Duration	<=3	0 – 255(×100ms)	0
10	Toggle Times	<=3	0 – 255	0
11	Reserved	0		
12	Reserved	0		
13	Reserved	0		
14	Reserved	0		
15	Reserved	0		
16	Reserved	0		
17	Reserved	0		
18	Reserved	0		

19	Reserved	0		
20	Reserved	0		
21	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ **<Mode>**: The working mode of the speed alarm.

- 0: Disable speed alarm.
- 1: Report speed alarm if the current speed is within the speed range defined by **<Min Speed>** and **<Max Speed>**.
- 2: Report speed alarm if the current speed is outside the speed range defined by **<Min Speed>** and **<Max Speed>**.
- 3: Report speed alarm only once if the current speed is within or outside the speed range defined by **<Min Speed>** and **<Max Speed>**. In this mode, **<Send Interval>** will be ignored.
- 4: Report speed alarm when the speed changes from inside to outside or vice versa. But the backend server cannot receive **+RESP:GTSPD** for speed changes from inside to outside unless **+RESP:GTSPD** for speed changes from outside to inside is received first. In this mode, **<Send Interval>** will be ignored.

✧ **<Min Speed>**: The lower limit speed.

✧ **<Max Speed>**: The upper limit speed.

✧ **<Validity>**: If the speed meets the alarm condition and maintains the period of time defined by **<Validity>**, the speed alarm will be triggered.

✧ **<Send Interval>**: The time interval of sending speed alarm message.

The acknowledgment message of **AT+GTSPD** command:

➤ **+ACK:GTSPD,**

Example: <b>+ACK:GTSPD, ED0101,862170019025640,,000C,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	≤20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.5. SOS Function

This command is used to configure the specified input port for emergency. When an emergency occurs, the end user can use this input port to trigger reporting message **+RESP:GTSOS** to the backend server or to the SOS number by SMS. A specified waveform can be configured to be sent on specified output port.

#### ➤ **AT+GTSOS=**

Example: <b>AT+GTSOS=gv600m,1,1,+8613812341234,1,1,0,0,,,,,000D\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 – 2	0
3	Digital Input ID	1	0 1 – 4	0
4	Reserved	0		
5	Output ID	1	0 – 4	
6	Output Status	1	0 1	
7	Duration	<=3	0 – 255(×100ms)	0
8	Toggle Times	<=3	0 – 255	0
9	Reserved	0		
10	Reserved	0		
11	Reserved	0		
12	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ **<Mode>**: The working mode of SOS function.
  - 0: Disable SOS function.
  - 1: Send the current position **+RESP:GTSOS** to the backend server.
  - 2: Send the current position to the SMS gateway and Direct Number List (if enabled) via SMS and **+RESP:GTSOS** to backend server
- ✧ **<Digital Input ID>**: ID of the digital input port which triggers the SOS function. 0 means the SOS function is disabled. The corresponding digital input port should be configured by the command **AT+GTDIS** first. If the SOS function is configured, there is no **+RESP:GTDIS** message for the specified digital input port.

The acknowledgment message of **AT+GTSOS** command:

➤ **+ACK:GTSOS,**

Example: <b>+ACK:GTSOS, ED0101,862170019025640,,000D,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.6. Roaming Detection Configuration

The command **AT+GTRMD** is used to configure the parameters for GSM roaming detection.

➤ **AT+GTRMD=**

Example: <b>AT+GTRMD=gv600m,0,,,,,1,2,4600F,4602F,,,1,1,,,,,2,2,,,,,1f,,,1f,,,,,0,0,0,0,,,0001\$</b> <b>AT+GTRMD=gv600m,1,,,,,1,3,46000,46002,46003,,,2,2,46007,,,1,1,46001,,,3fff,,,2ff,,,,,0,0,0,0,,,0002\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1	0
3	Reserved	0		
4	Reserved	0		
5	Reserved	0		
6	Reserved	0		
7	Home Operator Start	<=2	1-10	
8	Home Operator End	<=2	1-10	
9	Home Operator List	<=6*10		
10	Reserved	0		
11	Reserved	0		



12	Roaming Operator Start	<=3	1-100	
13	Roaming Operator End	<=3	1-100	
14	Roaming Operator List	<=6*100		
15	Reserved	0		
16	Reserved	0		
17	Black Operator Start	<=2	1-20	
18	Black Operator End	<=2	1-20	
19	Black Operator List	<=6*20		
20	Reserved	0		
21	Reserved	0		
22	Known Roaming Event Mask	<=4	0000 – 3FFF	3FFF
23	Reserved	0		
24	Reserved	0		
25	Unknown Roaming Event Mask	<=4	0000 – 3FFF	3FFF
26	Reserved	0		
27	Reserved	0		
28	Reserved	0		
29	Reserved	0		
30	Output ID	1	0 – 4	0
31	Output Status	1	0 1	
32	Duration	<=3	0~255(×100ms)	0
33	Toggle Times	<=3	0 – 255	0
34	Reserved	0		
35	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: Working mode of the roaming detection function.

- 0: Disable this function.
- 1: Enable this function.

✧ <Operator Start>: A numeral which indicates the first index of the white operator numbers to be input. For example, if the value is 1, it will update the white operator list from the 1st one. If the parameter is empty, there should be no white number list following the empty value.

- ✧ *<Operator End>*: A numeral which indicates the last index of the white operator numbers to be input. For example, if the value is 2, it will update the white operator list until the 2nd one. If the parameter is empty, there should be no white number list following the empty value.
- ✧ *<Home Operator List>*: A white number list of PLMN operators. The numbers are comprised of MCC and MNC, both of which consist of 3 digits. The operators in this list will be considered as in “Home” state. And two adjacent operator numbers are separated with ‘,’. The number of the operators in the list depends on the parameters *<Operator Start>* and *<Operator End>*. For example, if *<Operator Start>* is 1 and *<Operator End>* is 2, the operator list should include 2 operator numbers (empty value acceptable) and the two numbers are separated by with ‘,’. ‘MCCFF’ type code is used to identify operators across a whole country. For example, ‘460FF’ covers the mobile network operators all across China.
- ✧ *<Roaming Operator List>*: It is like the *<Home Operator List>* with difference that the operators in this list will be considered as in “Known Roaming” state.
- ✧ *<Black Operator List>*: It is like the *<Home Operator List>* with the difference that the operators in this list will be considered as in “Blocking Report” state. In this state, all reports will be buffered instead of being sent.  
Operators that are not in *<Home Operator List>*, *<Roaming Operator List>* and *<Black Operator List>* will be considered as in “Unknown Roaming” state.
- ✧ *<Known Roaming Event Mask>*: Bitwise mask to configure which event report should be sent to the backend server when GSM roaming state is detected. If the roaming state is “Known Roaming”, the *<Known Roaming Event Mask>* will be valid; otherwise the *<Unknown Roaming Event Mask>* will be valid.
  - Bit 0 for **+RESP:GTPNA**
  - Bit 1 for **+RESP:GTPFA**
  - Bit 2 for **+RESP:GTMPN**
  - Bit 3 for **+RESP:GTMPF**
  - Bit 4 is reserved
  - Bit 5 for **+RESP:GTBPL**
  - Bit 6 for **+RESP:GTBTC**
  - Bit 7 for **+RESP:GTSTC**
  - Bit 8 for **+RESP:GTSTT**
  - Bit 9 is reserved
  - Bit 10 for **+RESP:GTPDP**
  - Bit 11 for **+RESP:GTPNL**
  - Bit 12 for the ignition report **+RESP:GTIGN/GTVGN** and **+RESP:GTIGF/GTVGF**
  - Bit 13 for the ignition on location report **+RESP:GTIGL**
  - Bit 14 for **+RESP:GTEXP**
  - Reserved
  - Others are Reserved

For each bit, set it to 1 to enable corresponding event report, and 0 to disable.
- ✧ *<Unknown Roaming Event Mask>*: It works as the *<Known Roaming Event Mask>*.
- ✧ *<Output ID>*, *<Output Status>*, *<Duration>* and *<Toggle Times>*: When this function is enabled and roaming state is detected, the specified wave will be sent to the specified

output.

The acknowledgment message of the **AT+GTRMD** command:

➤ **+ACK:GTRMD,**

Example: <b>+ACK:GTRMD, ED0101,135790246811220,,0000,20090214093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X∈{'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

**Note:**

The length of AT Command cannot exceed 180 bytes when it is sent via Manage Tool. Make sure the command length is not more than 180 bytes through proper <Start Index> and <End Index> settings. A yellow prompt will appear on the Command Text Box if the length is over 180 bytes.

### 3.2.4.7. Buzzer Alarm Configuration

This command is used to set the buzzer alarm. There are four kinds of alarms. Each kind outputs a different sound. Before using those alarms, configure the output ID connected to the buzzer and enable it. The following event, over speed, can trigger the buzzer alarm defined by this command. Please refer to command **AT+GTSPA** for details.

➤ **AT+GTBZA=**

Example: <b>AT+GTBZA= gv600m,2,,,,,1,2,10,,,0,6,10,,,0,10,10,,,0,20,10,,,,,,,,,0000\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Output ID	1	0-4	0
3	Reserved	0		
4	Reserved	0		
5	Reserved	0		

6	Alarm 1 Output Status	1	0 1	
7	Duration	<=3	0 – 255 (×100ms)	0
8	Toggle Times	<=3	0 – 255	0
9	Reserved	0		
10	Reserved	0		
11	Alarm 2 Output Status	1	0 1	
12	Duration	<=3	0 – 255 (×100ms)	0
13	Toggle Times	<=3	0 – 255	0
14	Reserved	0		
15	Reserved	0		
16	Alarm 3 Output Status	1	0 1	
17	Duration	<=3	0 – 255 (×100ms)	0
18	Toggle Times	<=3	0 – 255	0
19	Reserved	0		
20	Reserved	0		
21	Alarm 4 Output Status	1	0 1	
22	Duration	<=3	0 – 255 (×100ms)	0
23	Toggle Times	<=3	0 – 255	0
24	Reserved	0		
25	Reserved	0		
26	Reserved	0		
27	Reserved	0		
28	Reserved	0		
29	Reserved	0		
30	Reserved	0		
31	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Output ID>: The output port which connects to the buzzer.

The acknowledgment message of the **AT+GTBZA** command:

➤ **+ACK:GTBZA,**

Example: +ACK:GTBZA, ED0101,862170019025640,,000D,20090214093254,FFFF\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.8. Overspeed Alarm

This command is used to set the speed thresholds and bind one alarm type with each speed threshold for the buzzer alarm. If the current speed meets one of the thresholds, the buzzer will make a sound corresponding to the alarm type.

#### ➤ AT+GTSPA

Example: AT+GTSPA= gv600m,2,,,,1,2,10,,,0,6,10,,,0,10,10,,,0,20,10,,,,,,0000\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2	0
3	Speed Threshold 1	<=3	0 – 400km/h	50
4	Reserved	0		
5	Validity	<=4	0 – 3600sec	60
6	Alarm Type	1	0 1 – 4	0
7	Reserved	0		
8	Reserved	0		
9	Speed Threshold 2	<=3	0 – 400km/h	70
10	Reserved	0		
11	Validity	<=4	0 – 3600sec	60
12	Alarm Type	1	0 1 – 4	0

13	Reserved	0		
14	Reserved	0		
15	Speed Threshold 3	<=3	0 – 400km/h	90
16	Reserved	0		
17	Validity	<=4	0 – 3600sec	60
18	Alarm Type	1	0 1 – 4	0
19	Reserved	0		
20	Reserved	0		
21	Speed Threshold 4	<=3	0 – 400km/h	110
22	Reserved	0		
23	Validity	<=4	0 – 3600sec	60
24	Alarm Type	1	0 1 – 4	0
25	Reserved	0		
26	Reserved	0		
27	Reserved	0		
28	Reserved	0		
29	Reserved	0		
30	Reserved	0		
31	Reserved	0		
32	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: The working mode of overspeed alarm.

- 0: Disable this function.
- 1: Strict Standard Mode. This mode will check the speed and trigger the buzzer alarm during speedup or slowdown.
- 2: Warning Mode. This mode will only check the speed and trigger the buzzer alarm during speedup.

✧ <Speed Threshold>: The minimum speed to trigger the buzzer alarm.

✧ <Validity>: If the speed meets the alarm condition and is maintained for the period of time longer than <Validity>, the buzzer alarm will be triggered.

✧ <Alarm Type>: The alarm type for each speed threshold. 0 means “No buzzer alarm”.

The acknowledgment message of the **AT+GTSPA** command:

➤ **+ACK:GTSPA,**

Example: +ACK:GTSPA, ED0101,862170019025640,,000D,20090214093254,FFFF\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.9. Excessive Idling Detection

The command **AT+GTIDL** is used to detect excessive engine idling (stationary while ignition on). The ignition signal must be connected to the device to use this function. When the device detects that the vehicle is entering into idle status, it will send event message **+RESP:GTIDN** to the backend server. When the vehicle exits the idle status, the device will send event message **+RESP:GTIDF** to the backend server.

#### ➤ AT+GTIDL=

Example: AT+GTIDL=gv600m,1,2,1,,,,,1,1,0,0,,,,,000E\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1	0
3	Time to Stationary	2	1 – 30 min	2
4	Time to Movement	1	1 – 5 min	1
5	Reserved	0		
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
9	Output ID	1	0 – 4	0
10	Output Status	1	0 1	0
11	Duration	<=3	0 – 255(×100ms)	0

12	Toggle Times	<=3	0 – 255	0
13	IDF after IGF	1	0-1	0
14	Reserved	0		
15	Reserved	0		
16	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Mode>: Working mode.
  - 0: Disable this function
  - 1: Enable this function.
- ✧ <Time to Stationary>: If the vehicle is detected to be stationary with ignition on for this time long, it is considered to be in idling status.
- ✧ <Time to Movement>: After the vehicle enters into idling status, if it moves again or turns ignition off and keeps in that status for this time long, the vehicle is considered to exit idling status.
- ✧ <Output ID>: Specify the ID of the output port (1 to 4) to output specified waveform when the vehicle enters into idling status. If it is set to 0, there is no output waveform.
- ✧ <IDF after IGF>: Specify required debouncing time to exit idle state after ignition off. 0 means needing no debouncing. 1 means needing to debounce <Time to Movement>.

The acknowledgment message of **AT+GTIDL** command:

➤ **+ACK:GTIDL,**

Example: <b>+ACK:GTIDL, ED0101,862170019025640,,000E,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z','0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$



### 3.2.4.10. Start/Stop Report

The command **AT+GTSSR** is used to detect the status of vehicle (Start or Stop status). When the device detects that the vehicle is entering into start status, it will send event message **+RESP:GTSTR** to the backend server. When the vehicle leaves the start status and enters into stop status, it will send event message **+RESP:GTSTP** to the backend server.

#### ➤ AT+GTSSR=

Example: AT+GTSSR=gv600m,1,2,1,5,2,,,,,0017\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1	0
3	Time to Stop	<=4	1 – 30 min/5-1800 sec	2
4	Time to Start	<=3	1 – 5 min/5-300 sec	1
5	Start Speed	<=2	1 – 10 Km/h	5
6	Long Stop	<=5	0 – 43200 min	0
7	Time Unit	1	0 1	0
8	Reserved	0		
9	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Mode>: Working mode.
  - 0: Disable this function
  - 1: Enable this function
- ✧ <Time to Stop>: After the vehicle enters into start status, if it rests again and keeps in that status for this time long, the vehicle is considered to exit start status.
- ✧ <Time to Start>: If the vehicle is detected to be moving with ignition on for this time long, it is considered to be in start status.
- ✧ <Start Speed>: The start speed threshold to determine whether the vehicle is start or not. When the device is detected to be moving with ignition on by the built-in motion sensor, it will start to check the speed from GPS. If the device speed stays greater than <Start Speed> longer than <Time to Start>, the vehicle is regarded to be in start status. The event report **+RESP:GTSTR** will be sent. Otherwise, if the device speed stays less than or equal to <Start Speed> longer than <Time to Stop>, the vehicle is regarded to exit start status. The event report **+RESP:GTSTP** will be sent. If GPS fix abnormality lasts more than 1 minute, only the built-in motion sensor will be used to detect the start/stop status and the speed will not be checked.

- ✧ **<Long Stop>**: If the duration of static state is more than **<Long Stop>**, the **+RESP:GTLSP** will be sent to backend server, and 0 means to disable.
- ✧ **<Time Unit>**: It controls the time unit of **<Time to Stop>** and **<Time to Start>** parameters.
  - 0: The time unit is minute.
  - 1: The time unit is second.

The acknowledgment message of **AT+GTSSR** command:

➤ **+ACK:GTSSR,**

Example: <b>+ACK:GTSSR, ED0101,862170019025640,,0017,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.11. I-button Setting

The command **AT+GTACD** is used to configure the parameters of I-button. When the iButton is access, a specified wave shape can be configured to the specified output port. IButton information report in message **+RESP:GTIDA**.

➤ **AT+GTACD**

Example: <b>AT+GTACD=gv600m,2,0,0,0,0,,,,,0005\$</b>			
Parameter	Length(byte)	Range/Format	Default
Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
iButton Timer	<=2	0 1 – 10(s)	0
Output ID	1	0-4	0
Output status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle	<=3	0 – 255	0

Reserved			
Reserved			
Reserved			
Reserved			
Reserved			
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ *<iButton Timer>*: Interval of search the iButton ID.

**Note:** The number of iButton ID is opposite order with number that print in iButton. We use the ID structure is < 1 byte family id> + < 6 byte serial number> + <1 byte CRC>. So the first byte of ID number is iButton's family id.

The acknowledgment message of **AT+GTACD** command:

➤ **+ACK:GTACD,**

Example: <b>+ACK:GTACD, FC0101,135790246811220,,0005,20090214093254,11F0\$</b>			
Parameter	Length(byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=10	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.12. Temperature Alarm

This command is used to set temperature-alarm range for the terminal. According to the working mode, the terminal will send event message **+RESP:GTTMP** to the backend server when the device detects the temperature is outside or inside the range.

➤ **AT+GTTMP=**

Example: <b>AT+GTTMP=gv600m,0,1, 862170019025640,,,-20,50,,,2,10,,,1,1,0,0,,,,,000C\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default

1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Alarm ID	1	0-7	
3	Mode	1	0-3	0
4	Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
5	Reserved	0		
6	Reserved	0		
7	Low Temperature	<=3	-55 – 125℃	0
8	High Temperature	<=3	-55 – 125℃	0
9	Reserved	0		
10	Reserved	0		
11	Validity	<=2	1 – 10	2
12	Send Interval	<=2	0 – 60	10
13	Reserved	0		
14	Reserved	0		
15	Output ID	1	0 – 4	0
16	Output Status	1	0 1	0
17	Duration	<=3	0 – 255(×100ms)	0
18	Toggle Times	<=3	0 – 255	0
19	Reserved	0		
20	Reserved	0		
21	Reserved	0		
22	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Alarm ID>: ID of the temperature alarm. Eight groups (0-7) are supported.

✧ <Mode>: The working mode of the temperature alarm.

- 0: Disable temperature alarm.
- 1: Report temperature alarm if the current temperature is within the temperature range defined by <Low Temperature> and <High Temperature>.
- 2: Report temperature alarm if the current temperature is outside the temperature range defined by <Low Temperature> and <High Temperature>.
- 3: Report temperature alarm only once if the current temperature is within or

outside the temperature range defined by *<Low Temperature>* and *<High Temperature>*. In this mode, *<Send Interval>* will be ignored.

- ✧ *<Sensor ID>*: ID of the temperature sensor. Total 8 sensors are supported.
- ✧ *<Low Temperature>*: The lower limit temperature.
- ✧ *<High Temperature>*: The upper limit temperature.
- ✧ *<Validity>*: When the temperature sensor detects the environment temperature meets the alarm condition and the duration is more than the value of *<validity>*, the temperature alarm will be triggered.
- ✧ *<Send Interval>*: The sending interval of temperature report **+RESP:GTTMP**. If *<Send Interval>* is set to 0, it will only report once.

The acknowledgment message of **AT+GTTMP** command:

➤ **+ACK:GTTMP**,

Example:			
<b>+ACK:GTTMP, ED0101,862170019025640,,0,000C,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	≤20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_' '?'	
Alarm ID	1	0-7	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.4.13. GPS Jamming Status Report

The command **AT+GTGPJ** is used to configure the parameters for GPS jamming status detection. When GPS jamming has been detected or suspected by the receiver, the device will send **+RESP:GTGPJ** event message to the backend server.

➤ **AT+ GTGPJ=**

Example:				
<b>AT+GTGPJ=gv600m,1,15,3,,,,,1,1,15,5,,0019\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4–6	'0'–'9' 'a'–'z' 'A'–'Z'	gv600m
2	Mode	1	0 1	0

3	CW Threshold	<=2	0 - 31	15
4	BB Threshold	<=2	0 - 15	3
5	Reserved	0		
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
9	Output ID	1	0 - 4	0
10	Output Status	1	0 1	0
11	Duration	<=3	0 - 255(×100ms)	0
12	Toggle Times	<=3	0 - 255	0
13	Reserved	0		
	Serial Number	4	0000-FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: Working mode.

- 0: Disable this function.
- 1: Enable this function.

✧ <BB Threshold>: Broadband jamming detection threshold (unit: dB)

✧ <CW Threshold>: Continuous wave (narrowband) jamming detection threshold (unit: dB)

The acknowledgement message of **AT+GTGPJ** command:

➤ **+ACK:GTGPJ**

Example:			
<b>+ACK:GTGPJ, 2B0204,135790246811220,,0005,20100310172830,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 - XXXFFF, X ∈ {'A' - 'Z', '0' - '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' - '9' 'a' - 'z' 'A' - 'Z'	
Serial Number	4	0000 - FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 - FFFF	
Tail Character	1	\$	\$

### 3.2.4.14. Bluetooth Event

The **AT+GTBTE** command is used to configure parameters of the Bluetooth device.

➤ **AT+GTBTE=**

Example:				
AT+GTBTE=gv600m,1,60,0,10,2400,1,1,ADD99AF06C21,1,0,0,0,,,,,0019\$				
SN	Parameter	Length(byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1	0
3	Send Interval	<=3	30-43200s	300
4	Low Temperature Threshold	<=3	-40 – 80℃	0
5	High Temperature Threshold	<=3	-40 – 80℃	10
6	Low Voltage Threshold	<=4	0-5000mv	2400
7	Start Point	<=2	1-10	1
8	End Point	<=2	1-10	1
9+N	MAC Addr	12	'0' – '9' 'a' – 'f' 'A' – 'F'	
10+N	Output ID	1	0 – 4	0
11+N	Output State	1	0 1	0
12+N	Duration	<=3	0 – 255(×100ms)	0
13+N	Toggle Times	<=3	0 – 255	0
14+N	Reserved	0		
15+N	Reserved	0		
16+N	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: Enable or disable the FOB MAC address match function.

● 0: Disable BLE sensor function.

● 1: Enable periodic report of **+RESP:GTBST**. The device will report **+RESP:GTBST** to server periodically. If the Bluetooth module's temperature or voltage is out of the defined range, **+RESP: GTBTA** will be reported following **+RESP:GTBST** report.

✧ <Send Interval>: If the <Mode> is set to 1, the device will report **+RESP:GTBST** to server every <Send Interval>. Unit: second.

✧ <Low Temperature Threshold>: Specify the lower limit temperature. When the temperature of Bluetooth module is below this value, **+RESP: GTBTA** will be reported.

- ✧ <High Temperature Threshold>: Specify the upper limit temperature. When the temperature of Bluetooth module is above this value, **+RESP: GTBTA** will be reported.
- ✧ <Low Voltage Threshold>: Specify the lower limit voltage. When the voltage of Bluetooth module is below this value, **+RESP: GTBTA** will be reported.
- ✧ <Start Point>: Specify the valid <MAC Addr> start point in the <MAC Addr> list.
- ✧ <End Point>: Specify the valid <MAC Addr> end point in the <MAC Addr> list.
- ✧ <MAC Addr>: MAC address for matching, for example: 112233445566. Up to 10 MAC address can be set up. The device only monitor the Bluetooth module with <MAC Addr> which is in the range from <Start Point> to <End Point> in the <MAC Addr> list.
- ✧ <Output ID>: Specify the ID (1 to 4) of the output port to output specified waveform when the **+RESP:GTBTA** event is triggered. If it is set to 0, there is no output waveform.
- ✧ <Output Status>, <Duration> and <Toggle Times>: Please refer to the Chapter '3.2.5 IO Application'.

The acknowledgment message of **AT+GTBTE** command:

➤ **+ACK:GTBTE,**

Example: <b>+ACK:GTBTE,F70101,135790246811220,,010A,20140116102313,02A5\$</b>			
Parameter	Length(byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z','0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.5. IO Application

#### 3.2.5.1. Digital Output

The **AT+GTOUT** command is used to set specified waveform from the digital output ports. Total four waveforms are supported as below. If it is set to waveform 1, the device will maintain this waveform at the specified output port after power reset.

The digital output 1 is a latched output. The final status of the output will be latched during power off. It supports only waveform 1.

The output port will output square wave if it is set to waveform 4. The waveform will be output only when the main power supply is connected. The waveform will still be output even if the device is rebooted.



**Waveform 1:**

✓ &lt;Duration&gt; = 0ms, &lt;Toggle Times&gt; = 0




Figure: Waveform 1

**Waveform 2:**

✓ &lt;Duration&gt; = 500ms, &lt;Toggle Times&gt; = 1




Figure 2: Waveform 2

**Waveform 3:**

✓ &lt;Duration&gt; = 800ms, &lt;Toggle Times&gt; = 3




Figure 3: Waveform 3

**Waveform 4:**

✓ &lt;Duration&gt; = 800ms, &lt;Toggle Times&gt; = 0




Figure 5: Waveform 4

➤ **AT+GTOUT=****Example:**

AT+GTOUT=gv600m,1,0,0,0,0,0,0,0,0,0,0,1,1,1,1,0004\$

SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Output1 Status	1	0 1	0
3	Duration	<=3	0-255(*100ms)	0
4	Toggle Times	<=3	0-255	0
5	Output2 Status	1	0 1	0
6	Duration	<=3	0 – 255(×100ms)	0
7	Toggle Times	<=3	0 – 255	0
8	Output3 Status	1	0 1	0
9	Duration	<=3	0 – 255(×100ms)	0
10	Toggle Times	<=3	0 – 255	0
11	Output4 Status	1	0 1	0
12	Duration	<=3	0 – 255(×100ms)	0
13	Toggle Times	<=3	0 – 255	0
14	DOS Report	1	0-F	0
15	Long Operation1	<=3	0 – 120min	0
16	Long Operation2	<=3	0 – 120min	0
17	Long Operation3	<=3	0 – 120min	0
18	Long Operation4	<=3	0 – 120min	0
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Output1–4 Status>: Used only for the waveform 1 as shown in Figure to set the final status of the output port.

- 0: Disable status.
- 1: Enable status.

✧ <Duration>: Please refer to Figure, Figure 2 and Figure 3. Unit is 100ms.

✧ <Toggle Times>: Please refer to Figure, Figure 2 and Figure 3.

When the <Duration> is set to 0, the <Toggle Times> must be set to 0. Otherwise the command may be invalid.

✧ <DOS Report>: Output status changes with waveform 1, whether to report **+RESP: GTDOS** or not.

- Bit 0: for output 1 report +RESP:GTDOS
- Bit 1: for output 2 report +RESP:GTDOS
- Bit 2: for output 3 report +RESP:GTDOS

- Bit 3: for output 4 report +RESP:GTDOS

For each bit, set it to 1 to enable and 0 to disable.

- ✧ <Long Operation1> and <Long Operation4>: The long operation time for output 1 and output 4. After the long time passed, the output waveform will be reset to the initial status at the specified output port. These two parameters would be effective only when the output waveform is 1 or 4.

The acknowledgment message of **AT+GTOUT** command:

➤ **+ACK:GTOUT,**

Example: +ACK:GTOUT, ED0101,862170019025640,,0004,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.5.2. External Power Supply Monitoring

The command **AT+GTEPS** is used to configure the parameters of external power supply monitoring. The device will measure and monitor the voltage of the external power supply. If the voltage of the external power supply matches the predefined alarm condition, the device will send an alarm message **+RESP:GTEPS** to the backend server to notify the status of the external power supply.

To make sure this function works in all situations, please switch on the internal backup battery in case that the voltages of the external power supply drops too low.

➤ **AT+GTEPS=**

Example: AT+GTEPS=gv600m,2,250,12000,3,2,1,1,0,0,1,,0007\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1 2	0
3	Min Threshold	<=5	250 – 32000 mV	

4	Max Threshold	<=5	250 – 32000 mV	
5	Sample Period	<=2	0 1 – 12(×2s)	0
6	Debounce Time	1	0 – 5 (×1s)	0
7	Output ID	1	0 – 4	
8	Output Status	1	0 1	
9	Duration	<=3	0 – 255(×100ms)	0
10	Toggle Times	<=3	0 – 255	0
11	Sync with FRI	2	00 01 10 11	00
12	Reserved			
13	Reserved			
14	MPN/MPF Validity Time	<=3	0 – 255 (×1s)	0
15	Mode for external power supply 2	1	0 1 2	
16	Min Threshold 2	<=5	250 – 32000 mV	
17	Max Threshold 2	<=5	250 – 32000 mV	
18	Sample Period	<=2	0 1 – 12(×2s)	0
19	Debounce Time	1	0 – 5 (×1s)	0
20	Output ID 2	1	0 – 4	
21	Output Status 2	1	0 1	
22	Duration 2	<=3	0 – 255(×100ms)	
23	Toggle Times 2	<=3	0 – 255	
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Mode>: Working mode of the external power supply monitoring.

- 0: Disable the external power supply monitoring.
- 1: Enable the external power supply monitoring. If the current voltage is within the range of (<Min Threshold>, <Max Threshold>), the **+RESP:GTEPS** alarm will be triggered.
- 2: Enable the external power supply monitoring. If the current voltage is outside the range of (<Min Threshold>, <Max Threshold>), the **+RESP:GTEPS** alarm will be triggered.

✧ <Min Threshold>: The lower limit of the voltage of the external power supply to trigger the

alarm.

- ✧ **<Max Threshold>**: The upper limit of the voltage of the external power supply to trigger the alarm.
- ✧ **<Sample Period>**: The sampling period to measure the external power supply.
- ✧ **<Debounce Time>**: The time for debouncing to avoid abnormal voltage drop of the external power supply.
- ✧ **<Output ID>**: Specify the ID of the output port (1 to 4) to output specified waveform when the **+RESP:GTEPS** alarm is triggered. If it is set to 0, there is no output waveform.
- ✧ **<Sync with FRI>**: Besides the **+RESP:GTEPS** alarm report, the device can also send the voltage of external power supply periodically along with the fixed report.
  - 00: Do not report external power supply voltage with fixed report.
  - 01: Report external power supply voltage with fixed report.
  - 10: Report second external power supply voltage with fixed report.
  - 11: Report two external power supply voltages with fixed report.
- ✧ **<MPN/MPF Validity Time>**: The validity time for detecting the device connecting or disconnecting to the main power supply. 0 means "Do not check the validity time". If **<MPN/MPF Validity Time>** is not 0, and the device remains connected or disconnected to the main power supply for the period of time specified by this parameter, the device will report **+RESP:GTMPN** or **+RESP:GTMPF** to the backend server. If it is detected that the device connects or disconnects to the main power supply when **<MPN/MPF Validity Time>** is 0, the device will report **+RESP:GTMPN** or **+RESP:GTMPF** to the backend server.

The acknowledgment message of **AT+GTEPS** command:

➤ **+ACK:GTEPS,**

Example: <b>+ACK:GTEPS,ED0101,862170019025640,,0007,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	≤20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.5.3. Digital Input Port Setting

The command **AT+GTDIS** is used to configure the parameters of 4 digital input ports. Input **<Ignition Detection>** is dedicated for ignition detection. The rest four inputs are customizable. If

the logical status of any one of the four digital inputs ports is changed, the device will send message **+RESP:GTDIS** to the backend server.

Before using digital input 1-4, *<IO Mode>* in **AT+GTCFG** command must be set to 0 on corresponding bit.

➤ **AT+GTDIS=**

Example: AT+GTDIS=gv600m,0,1,,0,1,1,4,,2,1,2,,3,3,,,,,,,,,0005\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Ignition Detection	1	0	0
3	Reserved	1	1	1
4	Debounce Time	<=2	0 – 20(×10ms)	5
5	No ignition	1	0 1	0
6	Input ID 1	1	1	1
7	Enable	1	0 1	0
8	Debounce Time	<=2	0 – 20(×10ms)	0
9	Validity Time	<=2	0 1 – 12(×2s)	0
10	Input ID 2	1	2	2
11	Enable	1	0 1	0
12	Debounce Time	<=2	0 – 20(×10ms)	0
13	Validity Time	<=2	0 1 – 12(×2s)	0
14	Input ID 3	1	3	3
15	Enable	<=2	0 1	0
16	Debounce Time	0	0 – 20(×10ms)	0
17	Validity Time	<=2	0 1 – 12(×2s)	0
18	Input ID 4	1	4	4
19	Enable	1	0 1	0
20	Debounce Time	<=2	0 – 20(×10ms)	0
21	Validity Time	<=2	0 1 – 12(×2s)	0
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ *<Ignition Detection>*: The ignition detection port.

- ✧ <Input ID 1-4>: The digital input port IDs.
- ✧ <Debounce Time>: The sampling period of the non-interruptible input port.
- ✧ <Enable>: Enable or disable the interrupt input.
  - 0: Disable
  - 1: Enable
- ✧ <Debounce Time>: The debouncing time for interruptible input port.
- ✧ <No ignition>: No Ignition wire connection.
  - 0: Ignition signal connected
  - 1: No ignition signal for virtual ignition, generates +RESP:GTVGN and +RESP:GTVGF report.
- ✧ <Validity Time>: The validity time of the input port. 0 means not to check the validity time.

The acknowledgment message of **AT+GTDIS** command:

➤ **+ACK:GTDIS,**

Example: +ACK:GTDIS,ED0101,862170019025640,,0005,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.5.4. Input/output Port Binding

This command is used to configure the user-defined output port action triggered by input ports. After the IO combination is set and corresponding condition occurs, the device will output specified waveform at the specified output port. The device will send message **+RESP:GTIOB** to the backend server when the logical status of bound input ports changes.

➤ **AT+GTIOB=**

Example: AT+GTIOB=gv600m,1,F,A,3,1,0,8,3,,,,,0006\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m

2	IOB ID	1	0 – 3	
3	Input Mask	2	0 – 1F	0
4	Trigger Mask	2	0 – 1F	0
5	Input Sample Period	<=2	0 1 – 12(×2s)	0
6	Output ID	1	0 – 4	0
7	Output Status	1	0 1	0
8	Duration	<=3	0 – 255(×100ms)	0
9	Toggle Times	<=3	0 – 255	0
10	Reserved	0		
11	Reserved	0		
12	Reserved	0		
13	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <IOB ID>: ID of the user-defined IO binding.
- ✧ <Input Mask>: Bitwise mask for input port composition. Each bit, from bit 0 to bit 4, represents one digital input port. Set it to 1 to enable and 0 to disable corresponding input port.
  - bit0: ignition detection
  - bit1: digital input 1
  - bit2: digital input 2
  - bit3: digital input 3
  - bit4: digital input 4
- ✧ <Trigger Mask>: bitwise mask for trigger condition composition of the corresponding input ports. Each bit, from bit 0 to bit 4, represents the logical status of the corresponding input port to trigger the IOB event. Set it to 1 to use enabled status as the trigger condition and 0 to use disabled status. Only when the logical status of all the input ports in one IO binding meets the trigger condition is the IOB event triggered.
  - bit0: ignition detection
  - bit1: digital input 1
  - bit2: digital input 2
  - bit3: digital input 3
  - bit4: digital input 4
- ✧ <Input Sample Period>: The period to check the status of all the digital input ports in one IO binding. **AT+GTIOB** and **AT+GTDIS** use independent sample period to check the input port status even for the same input port.
- ✧ <Output ID>: ID of the output port to output specified waveform when the trigger condition



meets. 0 means no waveform will be output.

The acknowledgment message of **AT+GTIOB** command:

➤ **+ACK:GTIOB,**

Example: <b>+ACK:GTIOB,ED0101,862170019025640,,1,0006,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
IOB ID	1	0 – 3	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.5.5. Analog Input Port Setting

The command **AT+GTAIS** is used to configure the parameters of analog input ports.

Make sure there is analog signal connected to the corresponding analog input port before carrying out settings to that port.

➤ **AT+GTAIS=**

Example: <b>AT+GTAIS=gv600m,1,0,250,2700,2,,1,1,0,0,1,,,2,1,250,2700,2,,1,1,0,0,1,,,,,0008\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4~7	'0'~'9' 'a'~'z' 'A'~'Z'	gv600m
2	Analog Input ID1	1	1	1
3	Mode	1	0 1 2 3 4 5	0
4	Min Threshold	<=5	0~32000 mV	
5	Max Threshold	<=5	0~32000 mV	
6	Sample Rate	<=2	0 1~12(×2s)	0
7	Reserved	0,TBD		
8	Output ID	1	0~4	

9	Output Active	1	0 1	
10	Duration	<=3	0~255(×100ms)	0
11	Toggle Times	<=3	0~255	0
12	Sync with FRI	1	0 1	0
13	Reserved	0		
14	Reserved	0		
15	Reserved	0		
16	Reserved	0		
17	Reserved	0		
18	Reserved	0		
19	Reserved	0		
20	Reserved	0		
21	Reserved	0		
22	Reserved	0		
23	Reserved	0		
24	Reserved	0		
25	Reserved	0		
26	Reserved	0		
27	Fuel Data Debounce	<=3	0-150	10
28	Fuel Sensor Delay	<=3	0-600 sec	30
29	Fuel Lost Alarm	<=2	0-50	10
30	Fuel Sensor Sample Count	<=3	0-150	20
31	Change Threshold	<=2	0-50%	0
	Serial Number	4	0000~FFFF	
	Tail Character	1	\$	\$

✧ <Analog Input ID 1>: The analog input port ID.

✧ <Mode>: Working mode of the analog input alarm (+RESP: GTAIS).

- 0: Disable analog input alarm.
- 1: Enable analog input alarm. If the current input voltage is within the range of (<Min Threshold>, <Max Threshold>), the alarm will be triggered.
- 2: Enable analog input alarm. If the current input voltage is outside the range of

(<Min Threshold>, <Max Threshold>), the alarm will be triggered.

- 3: Connect with special fuel level sensor to support fuel level reporting and monitoring.

Note: when the selected mode is 3, please do not choose the waveform 1 as the specified output waveform.

- 4: No alarm mode. The range of the voltage will be ignored and no alarm will be triggered.
- 5: Voltage processed mode. The range of the voltage will be ignored and no alarm will be triggered. But the voltage will be processed before being reported.

- ✧ <Min Threshold>: If <Mode> is set to 1 or 2, this is the lower limit of the voltage of the analog input port to trigger the alarm.
- ✧ <Max Threshold>: If <Mode> is set to 1 or 2, this is the upper limit of the voltage of the analog input port to trigger the alarm.
- ✧ <Sample Rate>: The sampling period of the analog input port.
- ✧ <Output ID>: Specify the ID of the output port (1 to 4) to output specified waveform when the analog input alarm is triggered. If it is set to 0, there is no output waveform.
- ✧ <Output Active>: set the final status of the output port.
  - 0: Disable status.
  - 1: Enable status.
- ✧ <Toggle Times>: The times of the square-wave.
- ✧ <Sync with FRI>: The device can send the analog input voltage periodically along with fixed message. Set this field to 1 to enable it and 0 to disable. If the analog input port is used to work with a fuel sensor and the <Sync with FRI> is enabled, the device will send the fuel level together with the fixed message.
- ✧ <Fuel Data Debounce>: Number of the data discarded when calculating the fuel level.
- ✧ <Fuel Sensor Delay>: After power on or enabling the fuel level reporting and monitoring function, the fuel sensor reports correct fuel level after <Fuel Sensor Delay>..
- ✧ <Fuel Loss Alarm>: If the difference between the current fuel level after ignition on and the last measured fuel level before previous ignition off is greater than this value, an unusual fuel consumption alarm is sent with the event message +RESP:GTFLA.
- ✧ <Fuel Sensor Sample Count>: This parameter defines the total number of sample readings from the fuel sensor for calculating the current fuel level. And it must be larger than <Fuel Data Debounce>.
- ✧ <Change Threshold>: This parameter defines the threshold of the value change. The value change must be greater than this defined threshold to trigger it. This value should not be greater than <Fuel Loss Alarm>, otherwise the +RESP:GTFLA may be reported incorrectly.

The acknowledgment message of **AT+GTAIS** command:

➤ **+ACK:GTAIS,**

Example:			
+ACK:GTAIS,ED0101,862170019025640,,0008,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' –	

		'Z','0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.6. Main Serial Port Application

#### 3.2.6.1. Serial Port Setting

The serial port of the device is used to connect to external devices to extend the application of the device. The command **AT+GTMUT** is used to configure the working mode of the serial port for different external devices and the parameters for the serial port communication.

#### ➤ AT+GTMUT=

Example: AT+GTMUT=gv600m,1,12,8,1,0,0,0,,,FFFF\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4~7	'0'~'9' 'a'~'z' 'A'~'Z'	gv600m
2	Working Mode	<=2	0   1   4	0
3	Baudrate Index	<=2	1 – 12	5
4	Data Bits	1	8	8
5	Stop Bits	1	1 – 3	1
6	Parity Bits	1	0 – 4	0
7	Sleep Enable	1	0   1	0
8	Input ID of Wakeup	0	0   1-4	0
9	Reserved (Optional)	0	0	0
10	Reserved (Optional)	0	0	
	Serial Number	4	0000~FFFF	
	Tail Character	1	\$	\$

✧ <Working Mode>: It configures the working mode of UART.

- 0: Disable UART.
- 1: Use UART to transfer data via **AT+GTDAT** and other protocol commands. When

executing **AT+GTDAT** command, the device will send execution result to the second serial port. "OK" is returned when the command is executed successfully, and "Error" is returned when the command fails to execute.

9	Hex convert mode	1	0 1	0
10	Reserved	0	0	

<Hex convert mode>: if this mode is enabled, it means the UART uses hex data.

- 4: Used for digital fuel sensor. Two reserved parameters are used as follows.

9	Digital Fuel Sensor Type	1	2 4	2
10	Reserved	0	0	

**Note:** DUT Fuel Sensor Type is 2 by default and UFSXXX type is 4 by default. Make sure the baud rate is suitable for the sensor and the default baud rate is 19200.

- ✧ <Baudrate Index>: The index of the supported baud rate of the serial port. All supported baud rates are listed as below:

Baudrate Index	Baud Rate
1	1200
2	2400
3	4800
4	7200
5	9600
6	14400
7	19200
8	28800
9	33900
10	38400
11	57600
12	115200

- ✧ <Data Bits>: Data bits of the UART. Their values can be 8.
- ✧ <Stop Bits>: Stop bits of the UART. Their values can be 1, 2 or 3.
  - 1: 1 Stop Bits.
  - 2: 2 Stop Bits.
  - 3: 1.5 Stop Bits.
- ✧ <Parity Bits>: Parity Bits of the UART. Their values can be 0, 1, 2, 3, or 4.
  - 0: None Parity.
  - 1: Odd Parity.
  - 2: Even Parity.
  - 3: Space Parity.
  - 4: Mark Parity.
- ✧ <Enable Sleep>: The device supports sleep mode which helps reduce power consumption. When the device enters into the sleep mode, the response to the serial port will be very slow unless the device is waked up. This parameter is used to enable or disable the sleep mode of the device.
  - 0: Disable the device sleep mode.

- 1: Enable the device sleep mode.
- ✧ <Input ID for Wakeup>: The ID of the digital input of GV600M used to wake up the device from the low power mode.
  - 0: Do not use digital input to wake up the device.
  - 1-4: The external device uses digital input to wake up the device.
- ✧ <Digital Fuel Sensor Type>: The type of digital fuel sensor connected to serial port.
  - 0: Reserved.
  - 1: Reserved.
  - 2: DUT-E.
  - 3: Reserved.
  - 4: UFSxxx.
  - 5: Reserved.
  - 6: Reserved.

Note: The device can receive all the AT commands only when it works under mode 0 and the GTMUT command is always supported regardless the setting of the mode.

The acknowledgment message of the **AT+GTMUT** command:

➤ **+ACK:GTMUT,**

Example: <b>+ACK:GTMUT, ED0101,862170019025640,,0018,20090214093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	≤20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.6.2. ID Authentication

The command **AT+GTIDA** is used to protect against unauthorized use. This function needs an ibutton and an external relay. To use this command, make sure both the ibutton and the external relay are connected to the device. When the device reads an ID, it will report event report **+RESP:GTIDA** to the server. If the ID is in the white list, it will be authorized until next time ignition off. After the ignition off again, the authentication valid time will last for a short period of time (settable). Within this period, the driver can turn on the engine again without reidentification.

➤ **AT+GTIDA=**

Example:

AT+GTIDA=gv600w,1,1,2,D2C4FBC5,87654321,45,3,,,,,1,1,0,0,,,,,FFFF\$			
Parameter	Length (Byte)	Range/Format	Default
Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600w
Mode	1	0/1/2	0
Start Index	<=2	1 – 250	
End Index	<=2	1 – 250	
ID Number List	<=8*20	'0' – '9','a' – 'f', 'A' – 'F'	
Timeout After Ignition Off	<=3	0/15 – 600sec	30
Report Mode	1	0 – 7	0
ID Valid Time	<=3	15 – 600sec	30
Reserved	0		
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0/1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Mode>: Working mode of the ID authentication function.
  - 0: Disable.
  - 1: Only authorized ID cards can unlock the vehicle.
  - 2: Any ID cards can unlock the vehicle.
- ✧ <Start Index>,<End Index>: The index range of the white list to which the ID numbers are to be updated. For example, if the <Start Index> is set to 1 and the <End Index> is set to 2, then the first two ID numbers in the white list will be updated by the numbers provided in the parameter <ID Number List>. The <Start Index> and <End Index> define the total amount of ID numbers that will be updated. If either one is empty, there should be no <ID Number List>parameter following the Index. A maximum of 8 numbers can be updated each time.
- ✧ <ID Number List>: A list of comma-separated ID number to be updated to the white list. The

amount of the ID numbers are determined by <Start Index> and <End Index>.

- ✧ <Timeout After Ignition Off>: When the ignition off, it will still be authorized for a short time. In this period, re-authentication is not needed. 0 means "Lock the vehicle when ignition off".
- ✧ <Report Mode>:
  - Bit 0: Report the ID which is authorized.
  - Bit 1: Report the ID which is unauthorized.
  - Bit 2: Report the ID which has logged out. (If authorized ID meets the trigger conditions <ID Valid Time> and <Timeout After Ignition Off>, then IDA report will be sent to indicate the log-out event).

For each bit, set it to 1 enable the report, and 0 disable the report. If <Report Mode> is 0, no report related to **+RESP:GTIDA** will be reported.

- ✧ <ID Valid Time>: It will remain authorized for this period of time when the ID is valid.
- ✧ <Output ID>: It Specified the ID of the output port to output specified waveform when it is authorized. Only the waveform 1 is supported.

The acknowledgment report of the **AT+GTIDA** command:

➤ **+ACK:GTIDA,**

Example: <b>+ACK: GTIDA, ED0101,862170013895931,,FFFF,20110101000009,0088\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=10	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

**Note:**

Make sure the total size of the command is not more than 160 bytes if it is sent via SMS.

### 3.2.6.3. External Digital Fuel Sensor

The command **AT+GTEFS** is used to configure the parameters of the external digital fuel sensor. Only when <Working Mode> in **AT+GTMUT** is set to 4, the parameters of this command will be effective.

➤ **AT+GTEFS=**

**Example:**

**AT+GTEFS=gv600m,,,,,15,10,,0,5,,,,,, FFFF\$**



Parameter	Length (Byte)	Range/Format	Default
Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
Reserved	0		
Reserved	0		
Ex Full Value	<= 5	0 – 65535	9999
Ex Fuel Sensor Delay	<=3	0   30- 600 sec	30
Ex Fuel Loss Alarm	<=2	0 – 50%	10
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Report Sensor Data	1	0/1	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Ex Full Value>: The value read from the sensor when the fuel tank is full.  
Note: This value needs to be set only for UFSxxx, and it is not required by the other sensors. The unit for DUT-E is 1mm. DUT-E can use <Ex Full Value> to calculate the percentage of fuel level.
- ✧ <Ex Fuel Sensor Delay>: After ignition on, before reporting the fuel level, the fuel sensor will be delayed for the period of time defined by <Ex Fuel Sensor Delay>.
- ✧ <Ex Fuel Loss Alarm>: If the difference between the current fuel level after ignition off and the last measured fuel level is greater than this value, an abnormal fuel consumption alarm will be sent to the backend server with event report **+RESP:GTFLA**. 0 means “Disable”.
- ✧ <Report Sensor Data>: A numeric to indicate whether to report raw data from fuel sensor to the server with **+RESP:GTFSD**. Currently, only the UFSxxx supports the raw data report.
  - 0: Do not report raw data from fuel sensor.
  - 1: Report raw data from fuel sensor.

The acknowledgment report of the **AT+GTEFS** command:

➤ **+ACK:GTEFS,**

**Example:**

+ACK:GTEFS, ED0101,135790246811220,,0008,20090214093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=10	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.6.4. Fuel Sensor Calibration Table

This command is used to set the calibration table for fuel sensor.

#### ➤ AT+GTFSC=

Example: AT+GTFSC=gv600m,,0,21,1,,,3,16000,0,10000,50,250,100,,,,,,,,,FFFF\$			
Parameter	Length (Byte)	Range/Format	Default
Password	4~20	'0'~'9' 'a'~'z' 'A'~'Z'	gv600m
Reserved			
Table ID	1	0 – 4	1
Sensor Type	1	0-2	2
Enable	1	0/1	0
Max. Tank Volume	<= 5	0 – 10000	100
Reserved			
Num of Node	<= 2	0/2 – 11	0
Node 1 Value	<= 5	0~99999	
Node 1 Percentage	<= 2	0 – 100	
⋮			
Node N Value	<= 5	0~99999	
Node N Percentage	<= 2	0 – 100	
Reserved			
Reserved			

Reserved			
Reserved			
Reserved			
Reserved			
Reserved			
Reserved			
Serial Number	4	0000~FFFF	
Tail Character	1	\$	\$

- ✧ <Table ID>: The ID of the calibration table that is currently being set.
- ✧ <Sensor Type>: The sensor type for this table.
  - 0: Reserved
  - 1: Reserved
  - 2: DUT-E
  - 3: Reserved
  - 4: UFSXXX
  - 5: Reserved.
  - 6: Reserved
- ✧ <Enable>: Enable or disable this table. If this table is enabled, the calculation of fuel level will be linearized.
- ✧ <Max. Tank Volume>: The maximum volume of tank. The unit is L.
- ✧ <Num of Node>: Number of the nodes in the table below.
- ✧ <Node N Value>: Value of this node.
- ✧ <Node N Percentage>: The corresponding percentage value of this node. This parameter must be in ascending order beginning with 0% and ending with 100%.

### 3.2.6.5. Fuel Sensor Upgrade

The command **AT+GTUFS** is used to upgrade the firmware of UFSxxx fuel sensor over the air.

#### ➤ AT+GTUFS=

**Example:**

```
AT+GTUFS=gv600w,3,30,0,,,http://220.178.67.210:8208/gv600w/deltabin/csb_des_07_build1116.bin,,,,,0001$
```

Parameter	Length (Byte)	Range/Format	Default
Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
Max Retries	1	0 – 3	0
Download Timeout	2	10-30min	10
Protocol Type	1	0	0
Server User Name	<=20	'0-9', ' _', 'a-z', 'A-Z'	

Server Password	<=20	'0-9', ' ', 'a-z', 'A-Z'	
Server URL	100	Legal URL	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Max Retries>: It specifies the maximum number of retries after the first downloading fails.
- ✧ <Download Timeout>: If downloading is not finished within this time, it will be regarded that the downloading failed.
- ✧ <Protocol Type>: The protocol used to download the package.
  - 0: HTTP. Only HTTP is supported now.
- ✧ <Server User Name>: If the file server uses authentication, the user name is specified here.
- ✧ <Server Password>: If the file server uses authentication, the password is specified here.
- ✧ <Server URL>: It specifies the URL to download the package.

The acknowledgment report of the **AT+GTUFS** command:

➤ **+ACK: GTUFS,**

Example: <b>+ACK:GTUFS,ED2001,135790246811220,,0018,20090214093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7. Other Settings

#### 3.2.7.1. Real Time Operation

The command **AT+GTRTO** is used to retrieve information from the terminal or control the

terminal to execute certain actions.

➤ **AT+GTRTO=**

Example: AT+GTRTO=gv600m,A,,,,,,0012\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Sub Command	2	0 – F 10-16	
3	AT Command   Configuration Mask	3 16	"SRI"  0000000000000000 – FFFFFFFFFFFFFFFF	
4	Output direction	1	0-3	
5	Reserved	0		
6	Reserved	0		
7	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

✧ <Sub Command>:

- 0: **GPS**. Get the GPS related information via message **+RESP: GTGPS**.
- 1: **RTL**. Request the terminal to report its current position immediately via message **+RESP: GTRTL**.
- 2: **READ**. Get the current configuration of the terminal via message **+RESP: GTALM** or **+RESP: GTALS** or **+RESP: GTALC**.
- 3: **REBOOT**. Reboot the terminal.
- 4: **RESET**. Reset all parameters to factory setting. Parameters configured by **AT+GTBSI**, **AT+GTSRI**, **AT+GTCFG**, **AT+GTTMA** and **AT+GTPIN** will not be reset.
- 5: **PWROFF**. Power off the device.
- 6: **CID**. Get the ICCID of the SIM card which is being used by the terminal via message **+RESP:GTCID**.
- 7: **CSQ**. Get the current received signal strength of the terminal via message **+RESP: GTCSQ**.
- 8: **VER**. Get the version information of the device via message **+RESP: GTVER**.
- 9: **BAT**. Get the battery level and adapter status of the terminal via message **+RESP: GTBAT**.
- A: **IOS**. Get status of all the IO ports via message **+RESP: GTIOS**.
- B: **TMZ**. Get the time zone settings via message **+RESP:GTTMZ**.
- C: **GIR**. Get cell information via message **+RESP:GTGSM**.
- D: **AIF**. Get APN, ICCID, base station ID, RSSI, cell ID, and IP via **+RESP:GTAIF**.

- E: **GSV**: Request the device to report the GPS fix level.
- F: **INF**: Read the device information report function. The corresponding information will be sent via the message **+RESP:GTINF**.
- 10-13: Reserved
- 14: **DELBUF**. Delete all the buffered reports.

✧ *<AT Command/Configuration Mask>*:

- *<AT Command>*: To get a single AT command's configuration when *<Sub Command>* is set to 2, follow the format in the following example. For example, to get the configuration of AT+GTFRI, please set AT+GTRTO=gv600m,2,FRI,,,,,0015\$, and get it via **+RESP:GTALS**.
- *<Configuration Mask>*: If *<Sub Command>* is set to 2, the configuration information of the specified *<Configuration Mask>* can be obtained via the message +RESP:GTALC. The Configuration Mask must be 16 bytes. If it's less than 16 bytes, '0' will be added in the high bytes of the Configuration Mask.

**Configuration Mask Table:**

Bit	Item to Mask
Bit 63	BTE
Bit 62	GPJ
Bit 61	Reserved
Bit 59	GAM
Bit 58	GLM
Bit 57	Reserved
Bit 56	Reserved
Bit 55	Reserved
Bit 54	Reserved
Bit 47	Reserved
Bit 46	Reserved
Bit 45	Reserved
Bit 44	PEO
Bit 43	RMD
Bit 42	FSC
Bit 41	TMP
Bit 40	Reserved
Bit 39	MUT

<b>Bit 38</b>	Reserved
<b>Bit 37</b>	SPA
<b>Bit 36</b>	BZA
<b>Bit 35</b>	Reserved
<b>Bit 34</b>	Reserved
<b>Bit 33</b>	PDS
<b>Bit 32</b>	ACD
<b>Bit 31</b>	IDA
<b>Bit 30</b>	EFS
<b>Bit 29</b>	SSR
<b>Bit 28</b>	Reserved
<b>Bit 27</b>	FFC
<b>Bit 26</b>	Reserved
<b>Bit 25</b>	HRM
<b>Bit 24</b>	WLT
<b>Bit 23</b>	Reserved
<b>Bit 22</b>	Reserved
<b>Bit 21</b>	Reserved
<b>Bit 20</b>	HMC
<b>Bit 19</b>	IDL
<b>Bit 18</b>	AIS
<b>Bit 17</b>	DOG
<b>Bit 16</b>	OWH
<b>Bit 15</b>	PIN
<b>Bit 14</b>	Reserved
<b>Bit 13</b>	SOS
<b>Bit 12</b>	SPD
<b>Bit 11</b>	GEO
<b>Bit 10</b>	FRI
<b>Bit 9</b>	TMA

<b>Bit 8</b>	IOB
<b>Bit 7</b>	OUT
<b>Bit 6</b>	DIS
<b>Bit 5</b>	EPS
<b>Bit 4</b>	TOW
<b>Bit 3</b>	CFG
<b>Bit 2</b>	Reserved
<b>Bit 1</b>	SRI
<b>Bit 0</b>	BSI

- ✧ **<Output Direction>**: This parameter determines the destination the response message of the RTO command will be reported to. This field is invalid for **<Sub Command>** 2(READ except +RESP:GTALS), 3(REBOOT), 4(RESET) and 5(PWROFF).
  - 0: The message will be sent to the backend server.
  - 1: The message will be sent to the main serial port.
  - 2: Reserved.
  - 3: If the command is received via SMS, the message will be output to the original SMS number, otherwise the message will be sent to the backend server.

The acknowledgment message of **AT+GTRTO** command:

➤ **+ACK:GTRTO,**

Example:			
+ACK:GTRTO,ED0101,862170019025640,,IOS,0012,20140511093254,11F1\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Sub Command	<=6	Sub Command String	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ *<Sub Command>*: A string to indicate the sub command of **AT+GTRTO**.



### 3.2.7.2. Transparent Data Transmission

The command **AT+GTDAT** is used to transfer data between the backend server and the equipment connected to the second serial port of the device. Data to the backend server is wrapped into message **+RESP:GTDAT** and sent to the backend server while data to the equipment is directly output to the second serial port without the @Tracker protocol stuffing. Transparent transfer is used to transmit the data to the device.

Before using this command, you should use **AT+GTMUT** command to set the correct parameters of the second serial port first.

#### ➤ AT+GTDAT=

<b>Example:</b> <b>AT+GTDAT=gv600m,0,,data to the backend server,,,,,0014\$</b> <b>AT+GTDAT=gv600m,1,,data to the serial port,,,,,0014\$</b> <b>AT+GTDAT=gv600m,2,,data to the backend server,,,,,0014\$</b> <b>AT+GTDAT=gv600m,3,,data to the serial port,,,,,0014\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Command Type	1	0 1 2 3	
3	Reserved	0		
4	Data	<=1280	ASCII Code	
5	Need Ack	1	0 1	
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Command Type>: To indicate in which way to send the data.
  - 0: Means to send message to the backend server with **+RESP:GTDAT (Short Format)**.
  - 1: Means to send the pure data directly to the serial port.
  - 2: Means to send message to the backend server with **+RESP:GTDAT (Long Format)**.
  - 3: Means to send the pure data directly to the serial port without CRLF.
- ✧ <Data>: Data to be transferred between the backend server and the equipment connected to the second serial port of the device. The max length for main serial port (MUT) is 1280.
- ✧ <Need Ack>: Need report **+ACK:GTDAT** or not.
  - 0: Do not need Ack report.
  - 1: Need report Ack.

The acknowledgment message of **AT+GTDAT** command:

➤ **+ACK:GTDAT,**

Example: <b>+ACK:GTDAT, ED0101,862170019025640,,0014,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7.3. White Number List Configuration

The **AT+GTWLT** command is used to set white number list.

➤ **AT+GTWLT=**

Example: <b>AT+GTWLT= gv600m,1,1,2,13813888888,13913999999,,,,,000C\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Number Filter	1	0 1 2	1
3	Mobile Start	1	1-10	1
4	Mobile End	1	1-10	1
5	White Number List	<=20*10		
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
9	Reserved	0		
	Serial Number	4	0000 – FFFF	

	Tail Character	1	\$	\$
--	----------------	---	----	----

- ✧ <Number Filter>: A numeric to indicate whether to filter the original number according to <White Number List> and <Direct Number List> before it sends Google link SMS to the original number.
  - 0: Do not return SMS to original number, ignore the received position request message no matter the original number is in the <White Number List> or <Direct Number List> or not.
  - 1: Do not filter the original number. It will return SMS to the original number as long as position request message is received via SMS.
  - 2: Filter the original number. If the original number isn't in <White Number List> or <Direct Number List>, it won't return a SMS to the incoming number even if the device receives position request message via SMS
- ✧ <Mobile Start>: A numeric to indicate the first index of the white number to be input. For example, if it is 1, it will update the white number list from the 1st one.
- ✧ <Mobile End>: A numeric to indicate the last index of the white number to be input. For example, if it is 2, it will update the white number list until the 2nd one.
- ✧ <White Number List>: A phone number list including multiple phone numbers. And two neighboring phone numbers are separated with ",". The number of the phone number in the list depends on the parameters <Mobile Start> and <Mobile End>. For example, if <Mobile Start> is 1 and <Mobile End> is 2, the <White Number List> should include 2 phone numbers and the two numbers are separated with ",".

The acknowledgment message of **AT+GTWLT** command:

➤ **+ACK:GTWLT,**

Example: <b>+ACK:GTWLT, ED0101,862170019025640,,0015,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

#### 3.2.7.4. Command String Storage

The **AT+GTCMD** command is used to store the commands used by the command **AT+GTUDF**.

➤ **AT+GTCMD=**

Example:			
AT+GTCMD=gv600m,1,1,AT+GTRTO=gv300,0,,,,,000B\$,,,,,0005\$			
Parameter	Length (Byte)	Range/Format	Default
Password	4 – 6	'0' – '9', 'a' – 'z', 'A' – 'Z'	gv600m
Mode	1	0-1	0
Stored cmd ID	<=2	0 – 31	
Command String	200	AT command	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Mode>: The working mode for storing command string.
  - 0: Delete the stored command.
  - 1: Add the stored command.
- ✧ <Stored cmd ID>: A numeral to identify the stored command.
- ✧ <Command String>: The content of the stored command.

The acknowledgement message of **AT+GTCMD** command:

➤ **+ACK:GTCMD**

Example:			
+ACK:GTCMD, ED0101,862170019025640,,0015,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

**3.2.7.5. User Defined Function**

The **AT+GTUDF** command is used to bind input events and the stored commands. The input events will trigger the corresponding stored commands.

➤ **AT+GTUDF=**

<b>Example:</b> <b>AT+GTUDF=gv600m,1,1,FFFFFFFF,30,0,0,FFFFFFFF,1,,,,,0005\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Password	4 – 6	'0' – '9', 'a' – 'z', 'A' – 'Z'	gv600m
Mode	1	0-2	0
Group ID	<=2	0 – 31	
Input ID Mask	<=16	0-FFFFFFFFFFFFFFFF	
Debounce Time	<=5	0-86400(s)	0
Inzizo Mask	<=5	00000-FFFFF	0
Outzizo Mask	<=5	00000-FFFFF	0
Stocmd ID Mask	<=8	0-FFFFFFFF	
Stocmd Ack	1	0 1	0
Inpeo Mask	<=5	00000-FFFFF	0
Outpeo Mask	<=5	00000-FFFFF	0
Reserved			
Reserved			
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ **<Mode>**: The working mode of the user defined function.
  - 0: Disable the group.
  - 1: Enable the group.
  - 2: Delete the group.
- ✧ **<Group ID>**: A numeral to identify the group of input events and stored commands to be executed.
- ✧ **<Input ID Mask>**: The bitwise mask to indicate the input events included in the group.
  - Bit 0 (00000001): Select ID1
  - Bit 1 (00000002): Select ID2
  - Bit 2 (00000004): Select ID3
  - Bit 3 (00000008): Select ID4

For example:

  - Bit (00000003): Select ID1, ID2
  - Bit (00000017): Select ID1, ID2, ID3, ID5

ID	Bit	Item to Mask
1	Bit 0	Power on finished
2	Bit 1	Ignition on
3	Bit 2	Ignition off
4	Bit 3	The GPRS network is attached
5	Bit 4	The GPRS network is not attached
6	Bit 5	The GSM network registered
7	Bit 6	The GSM network not registered
8	Bit 7	Network roaming
9	Bit 8	Network non roaming

10	Bit 9	SIM card is locked
11	Bit 10	GPS is turned on
12	Bit 11	GPS is turned off
13	Bit 12	The device is stationary
14	Bit 13	The device is moving
15	Bit 14	External charge inserted
16	Bit 15	No external charge
17	Bit 16	The device is charging
18	Bit 17	The device is not charging
19	Bit 18	Digital input 2 is low
20	Bit 19	Digital input 2 is high
21	Bit 20	Digital input 1 is low
22	Bit 21	Digital input 1 is high
23	Bit 22	SIM card is inserted
24	Bit 23	SIM card is not inserted
25	Bit 24	Reserved
26	Bit 25	Reserved
27	Bit 26	Inside the speed range
28	Bit 27	Outside the speed range
29	Bit 28	Messages need to be sent
30	Bit 29	No messages need to be sent
31	Bit 30	Digital input 3 is low
32	Bit 31	Digital input 3 is high
33	Bit 32	Backup battery inserted
34	Bit 33	No backup battery
35	Bit 34	Reserved
36	Bit 35	Reserved
37	Bit 36	Digital input 4 is low
38	Bit 37	Digital input 4 is high
39	Bit 38	Output1 Enable
40	Bit 39	Output1 Disable
41	Bit 40	Output2 Enable
42	Bit 41	Output2 Disable
43	Bit 42	Output3 Enable
44	Bit 43	Output3 Disable
45	Bit 44	Output4 Enable
46	Bit 45	Output4 Disable

✧ <Debounce Time>: The debounce time for input events before executing the specified stored commands.

✧ <Inzizo Mask>: The bitwise mask to indicate the input events within the circular Geo-Fence.

ID	Bit	Item to Mask
1	Bit 0	Inside the Geo 0

2	Bit 1	Inside the Geo 1
3	Bit 2	Inside the Geo 2
4	Bit 3	Inside the Geo 3
5	Bit 4	Inside the Geo 4
6	Bit 5	Inside the Geo 5
7	Bit 6	Inside the Geo 6
8	Bit 7	Inside the Geo 7
9	Bit 8	Inside the Geo 8
10	Bit 9	Inside the Geo 9
11	Bit 10	Inside the Geo 10
12	Bit 11	Inside the Geo 11
13	Bit 12	Inside the Geo 12
14	Bit 13	Inside the Geo 13
15	Bit 14	Inside the Geo 14
16	Bit 15	Inside the Geo 15
17	Bit 16	Inside the Geo 16
18	Bit 17	Inside the Geo 17
19	Bit 18	Inside the Geo 18
20	Bit 19	Inside the Geo 19

✧ <Outzizo Mask>: The bitwise mask to indicate the input events outside the circular Geo-Fence.

ID	Bit	Item to Mask
1	Bit 0	Outside the Geo 0
2	Bit 1	Outside the Geo 1
3	Bit 2	Outside the Geo 2
4	Bit 3	Outside the Geo 3
5	Bit 4	Outside the Geo 4
6	Bit 5	Outside the Geo 5
7	Bit 6	Outside the Geo 6
8	Bit 7	Outside the Geo 7
9	Bit 8	Outside the Geo 8
10	Bit 9	Outside the Geo 9
11	Bit 10	Outside the Geo 10
12	Bit 11	Outside the Geo 11
13	Bit 12	Outside the Geo 12
14	Bit 13	Outside the Geo 13
15	Bit 14	Outside the Geo 14
16	Bit 15	Outside the Geo 15
17	Bit 16	Outside the Geo 16
18	Bit 17	Outside the Geo 17
19	Bit 18	Outside the Geo 18
20	Bit 19	Outside the Geo 19

- ✧ **<Stocmd ID Mask>**: The bitwise masks of the stored commands which will be executed after the state of the group becomes TRUE (i.e. all the included input events occur.).
- ✧ **<Stocmd Ack>**: A numeral to indicate whether to send acknowledgement message after the stored commands are executed.
  - 0: Do not send acknowledgement message when the stored command is executed.
  - 1: Send acknowledgement message when the stored command is executed.
- ✧ **<Inpeo Mask>**: The bitwise mask to indicate the input events within the polygon Geo-Fence.

ID	Bit	Item to Mask
1	Bit 0	Inside the Peo 0
2	Bit 1	Inside the Peo 1
3	Bit 2	Inside the Peo 2
4	Bit 3	Inside the Peo 3
5	Bit 4	Inside the Peo 4
6	Bit 5	Inside the Peo 5
7	Bit 6	Inside the Peo 6
8	Bit 7	Inside the Peo 7
9	Bit 8	Inside the Peo 8
10	Bit 9	Inside the Peo 9
11	Bit 10	Inside the Peo 10
12	Bit 11	Inside the Peo 11
13	Bit 12	Inside the Peo 12
14	Bit 13	Inside the Peo 13
15	Bit 14	Inside the Peo 14
16	Bit 15	Inside the Peo 15
17	Bit 16	Inside the Peo 16
18	Bit 17	Inside the Peo 17
19	Bit 18	Inside the Peo 18
20	Bit 19	Inside the Peo 19

- ✧ **<Outpeo Mask>**: The bitwise mask to indicate the input events outside the polygon Geo-Fence.

ID	Bit	Item to Mask
1	Bit 0	Outside the Peo 0
2	Bit 1	Outside the Peo 1
3	Bit 2	Outside the Peo 2
4	Bit 3	Outside the Peo 3
5	Bit 4	Outside the Peo 4
6	Bit 5	Outside the Peo 5
7	Bit 6	Outside the Peo 6
8	Bit 7	Outside the Peo 7
9	Bit 8	Outside the Peo 8
10	Bit 9	Outside the Peo 9
11	Bit 10	Outside the Peo 10
12	Bit 11	Outside the Peo 11



13	Bit 12	Outside the Peo 12
14	Bit 13	Outside the Peo 13
15	Bit 14	Outside the Peo 14
16	Bit 15	Outside the Peo 15
17	Bit 16	Outside the Peo 16
18	Bit 17	Outside the Peo 17
19	Bit 18	Outside the Peo 18
20	Bit 19	Outside the Peo 19

**Note:**

Maximum 5 stored commands in a group will be executed.

The acknowledgement message of **AT+GTUDF** command:

➤ **+ACK:GTUDF**

Example: <b>+ACK:GTUDF, ED0101,862170019025640,,0015,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z','0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

**3.2.7.6. Google Link SMS Configuration**

The **AT+GTGLM** command is used to configure whether to send SMS with Google link for SOS and GEO event.

➤ **AT+GTGLM=**

Example: <b>AT+GTGLM=gv600m,1,1,2,13813888888,13913999999,,,,,000D\$</b>				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Google Mode	1	0 1	0
3	Mobile Start	1	1-3	

4	Mobile End	1	1-3	
5	Direct Number List	$\leq 20 \times 3$		
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
9	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

□

- ✧ <Google Mode>: A numeric to indicate whether to send a SMS with Google link to the number in <Direct Number List> for SOS and GEO events.
  - 0: Do not send a SMS with Google link to the number in the <Direct Number List> for SOS and GEO events.
  - 1: Send a SMS with Google link to the number in the <Direct Number List> for SOS and GEO events and include the terminal name in the Google hyperlink.
- ✧ <Mobile Start>: A numeric to indicate the first index of the white number to be input. For example, if it is 1, it will update the white number list from the 1st one. If it is empty, it should not include the number of <Direct Number List>.
- ✧ <Mobile End>: A numeric to indicate the last index of the white number to be input. For example, if it is 2, it will update the white Number list until the 2nd one. If it is empty, it should not include the number of <Direct Number List>.
- ✧ <Direct Number List>: A phone number list. It could include several phone numbers. And two neighboring phone numbers are separated with ",". The number of the phone number in the list is defined by the parameters <Mobile Start> and <Mobile End>. For example, if <Mobile Start> is 1 and <Mobile End> is 2, the <White Number List> should include 2 phone numbers and the two numbers are separated with ",".

The acknowledgment message of **AT+ GTGLM** command:

➤ **+ACK: GTGLM,**

Example: <b>+ACK:GTGLM, ED0101,862170019025640,,0015,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	$\leq 20$	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	

Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7.7. Hour Meter Counter

The command **AT+GTHMC** is used to measure accumulative ignition time. To use this command, the ignition signal must be connected to the device. *<Hour Meter Counter>* will be included in **+RESP:GTFRI**, **+RESP:GTIGN** or **+RESP:GTIGF** reports.

#### ➤ AT+GTHMC=

Example: AT+GTHMC=gv600m,1,12345:12:34,,,,,,,,,0015\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Hour Meter Enable	1	0 1	0
3	Initial Hour Meter Count	11	00000:00:00-99999:00:00	00000:00:00
4	Reserved	0		
5	Reserved	0		
6	Reserved	0		
7	Reserved	0		
8	Reserved	0		
9	Reserved	0		
10	Reserved	0		
11	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ *<Hour Meter Enable>*: Enable or disable hour meter counter function. If hour meter counter function is enabled, hour meter count will be increased when the device is in ignition.
  - 0: Disable hour meter counter function
  - 1: Enable hour meter counter function
- ✧ *<Initial Hour Meter Count>*: Initial value of hour meter. It is formatted with 5 hour digits and 2 minute digits and 2 second digits and ranges from 00000:00:00–99999:00:00. The *<Hour Meter Count>* in **+RESP:GTFRI**, **+RESP:GTIGN**/**+RESP:GTVGN** or **+RESP:GTIGF**/**+RESP:GTVGF** will be increased based on the value of first-time ignition on..

The acknowledgment message of **AT+GTHMC** command:

➤ **+ACK:GTHMC,**

Example:			
+ACK:GTHMC, ED0101,862170019025640,,0015,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7.8. GPS-Assisted Motion Measurement

The command **AT+GTGAM** is used for assisting in measuring motion with GPS if the sensor detects motionless state while the vehicle is ignition on.

➤ **AT+GTGAM=**

Example:				
AT+GTGAM=gv600m,1,1,25,10,60,,,,0001\$				
SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 20	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
2	Mode	1	0 1	1
3	Speed Mode	1	0 1	1
4	Motion Speed Threshold	<=2	5-50km/h	25
5	Motion Cumulative Time	<=3	10-100s	10
6	Motionless Cumulative Time	<=3	10-250s	60
7	Reserved	0		
8	Reserved	0		
9	Reserved	0		
10	Reserved	0		
11	Reserved	0		

	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ **<Mode>**: The working mode of the GPS-assisted motion measurement function.
  - 0: Disable this function.
  - 1: Enable this function.
- ✧ **<Speed Mode>**: It combines with GPS speed to measure the status of movement.
  - 0: Disable the function.
  - 1: Enable the function.
- ✧ **<Motion Speed Threshold>**: The speed threshold combined with GPS speed to measure the status of movement.
- ✧ **<Motion Cumulative Time>**: If the average speed in **<Motion Cumulative Time>** is higher than **<Motion Speed Threshold>**, the device is considered to be in motion status.
- ✧ **<Motionless Cumulative Time>**: If the average speed in **<Motionless Cumulative Time>** is lower than **<Motion Speed Threshold>**, the device is considered to be in motionless status.
- ✧ **<GPS Fix Failure Timeout>**: If the time for GPS fix is more than **<GPS Fix Failure Timeout>**, the device will update motion status by motion sensor again.

The acknowledgment message of the **AT+GTGAM** command:

➤ **+ACK:GTGAM,**

<b>Example:</b> <b>+ACK:GTGAM, ED0101,135790246811220,,1,0006,20090214093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X∈{'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7.9. Update Configuration Over the Air

The AT+GTUPC command is used to send control command.

➤ **AT+GTUPC=**

**Example:**

**AT+GTUPC=gv600m,0,10,0,0,168,http://www.queclink.com/configure.ini,,,,,0001\$**

SN	Parameter	Length (Byte)	Range/Format	Default
1	Password	4 – 20	'0'-'9','a'-'z','A'-'Z'	gv600m
2	Max Download Retry	1	0 – 3	0
3	Download Timeout	<=2	5 – 30 min	10
4	Download Protocol	1	0	0
5	Report Enable	1	0 1	0
6	Update Interval	<=4	0 – 8760 hour	0
7	Download URL	<=100	URL	
8	Mode	1	0 1	0
9	Reserved	0		
10	Reserved	0		
11	Reserved	0		
	Serial Number	4	0000 – FFFF	
	Tail Character	1	\$	\$

- ✧ <Password>: The valid characters of password include '0'-'9', 'a'-'z', 'A'-'Z'. The default value is "gv600m".
- ✧ <Max Download Retry>: Specifies the maximum times of retrying to download the configuration file upon downloading failure.
- ✧ <Download Timeout>: If downloading is not finished within this time, it will be regarded that the downloading failed.
- ✧ <Download Protocol>: The protocol used to download the file. Only HTTP is supported now. Set it to 0.
- ✧ <Report Enable>: A numeric to indicate whether to send the message **+RESP:GTUPC** to indicate the configuration was updated over the air.
  - 0: Do not send the message +RESP:GTUPC
  - 1: Send the message +RESP:GTUPC
- ✧ <Update Interval>: The time interval (hour) for updating the configuration over the air.
- ✧ <Download URL>: Specify the URL to download the configuration file. If the URL ends with "/", it means this is just a path without any file. <imei>.ini will be added as the file name at the end of URL.
- ✧ <Mode>: A numeric to indicate the working mode of downloading configuration over the air
  - 0: Disable this function.
  - 1: Enable this function

The acknowledgement message of **AT+GTUPC** command report is reported as Location report.

#### Notice:

If the <Download URL> ends with "/", it means the URL is a path without file name. <imei>.ini will

be added as the file name at the end of URL.. If it is larger than 100, an error will be reported.

The acknowledgment message of **AT+GTUPC** command:

➤ **+ACK:GTUPC,**

Example: <b>+ACK:GTUPC, ED0101,862170019025640,,001D,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.2.7.10. SMS Request Position

This command can only be sent via SMS. Device will send SMS message with Google maps hyperlink and the current position or send message **+RESP:GTLBC** immediately.

Command Format	<b>get position</b>
Example	get position

**Get position:** it's a command string to query current position.

## 3.3. Reports

This section defines the formats of the messages. Due to the max length of SMS message is 160 bytes, it is recommended to set the *<Report Composition Mask>* in **AT+GTCFG** properly to limit the length of the report, otherwise the report will be truncated to fit the length of SMS message.

### 3.3.1. Position Related Reports

➤ **+RESP:GTTOW,**

If the tow alarm is enabled by the command **AT+GTTOW**, the device will send the message **+RESP:GTTOW** to the backend server when the motion sensor detects towing.

➤ **+RESP:GTDIS,**

If the status of digital inputs is detected being changed, the device will send the message

**+RESP:GTDIS** to the backend server.

➤ **+RESP:GTIOB,**

If the IO combination is set and the corresponding condition appears, the device will send the message **+RESP:GTIOB** to the backend server.

➤ **+RESP:GTSPD,**

If the speed alarm is enabled, the device will send the message **+RESP:GTSPD** to the backend server when the speed of the device is within the alarm range.

➤ **+RESP:GTSOS,**

If the SOS function is enabled, the device will send the message **+RESP:GTSOS** to the backend server when the corresponding digital input port triggers SOS.

➤ **+RESP:GTRTL,**

After the device receives the command **AT+GTRTO**, the GPS starts to get the current position and then send the message **+RESP:GTRTL** to the backend server.

➤ **+RESP:GTPNL,**

Power on location

➤ **+RESP:GTDG,**

The watchdog rebooting message

➤ **+RESP:GTIGL,**

The location message for ignition on and ignition off

All of the above messages have the same format as shown below.

**Example:**

```
+RESP:GTTOW,ED0101,862170019025640,,,10,,1,4.3,92,70.0,121.354335,31.222073,20140511
093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0$
```

```
+RESP:GTDIS,ED0101,862170019025640,,,20,,1,4.3,92,70.0,121.354335,31.222073,201405110
93254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0$
```

```
+RESP:GTIOB,ED0101,862170019025640,,,10,,1,4.3,92,70.0,121.354335,31.222073,20140511
093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0$
```

```
+RESP:GTSPD,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,20140511
093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0$
```

```
+RESP:GTSOS,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,20140511
093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0$
```

```
+RESP:GTRTL,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,20140511
```



093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

+RESP:GTDOG,ED0101,862170019025640,,,01,,1,4.3,92,70.0,121.354335,31.222073,20140511  
093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

+RESP:GTIGL,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,201405110  
93254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Reserved			
Report ID/Report Type	2	X(0-4)X(0-6)	
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ **<Report ID/Report Type>**: The report ID and the type of the report type in hex format. 4 high bits mean report ID and 4 low bits mean report type.

Report ID has different meanings in different messages as below.

- The ID of digital input port which triggers the message **+RESP:GTDIS** and **+RESP:GTSOS**. The range is 1 – 4.
- The ID of the bound IO which triggers the message **+RESP:GTIOB**. The range is 0 – 3.
- The ID of the digital input port which triggers the reboot message **+RESP:GTDOG**. The valid value is 1 - 4.

For the rest of the messages, it will always be 0.

Meanings of different report type in different messages are as below:

- In the **+RESP:GTDIS** message generated by the digital input
  - 0: The current logical status of the input port is disabled status.
  - 1: The current logical status of the input is enabled status.
- In the **+RESP:GTIOB** message generated by bound IO
  - 0: The current logical status of the bound IO does not meet the alarm condition.
  - 1: The current logical status of the bound IO meets the alarm condition.
- In the message of speed alarm **+RESP:GTSPD**
  - 0: Outside the predefined speed range.
  - 1: Inside the predefined speed range.
- In the message of protocol watchdog reboot message **+RESP:GTDOG**
  - 1: Reboot message for time based working mode
  - 2: Reboot message for ignition on working mode
  - 3: Reboot message for input triggered reboot
  - 4: Reboot message for network watchdog.
  - 5: Reboot message for no activation watchdog.
  - 6: Reboot message for network data retrying to reboot watchdog.
- In the message of ignition on and ignition off message **+RESP:GTIGL**
  - 0: The engine is ignition on.
  - 1: The engine is ignition off.

For the rest of the messages, it will always be 0.

- ✧ **<Number>**: The number of the GPS positions included in the message. Generally, it equals to 1.
- ✧ **<GPS Accuracy>**: The HDOP defined in NMEA0183 (The National Marine Electronics Association (NMEA) is a non-profit association of manufacturers, distributors, dealers, educational institutions, and others interested in peripheral marine electronics occupations. The NMEA 0183 standard defines an electrical interface and data protocol for communications between marine instrumentation.). The range of the value is 0 – 50. Here 0 means no GPS fix.
- ✧ **<Speed>**: The current speed. Unit: km/h
- ✧ **<Azimuth>**: The azimuth of the GPS fixing.
- ✧ **<Altitude>**: The height above the sea level.
- ✧ **<Longitude>**: The longitude of the current position.
- ✧ **<Latitude>**: The latitude of the current position.

- ✧ <GPS UTC Time>: The UTC time from the GPS chip.
- ✧ <MCC>: Mobile Country Code. It is 3-digit in length and ranges from 000 to 999. If bit 3 is not set to 1 in field <Report Composition Mask> within **AT+GTCFG**, the length of this field is 0 in ASCII format message.
- ✧ <MNC>: Mobile Network Code. It is 3-digit in length and ranges from 000 to 999. If bit 3 is not set to 1 in field <Report Composition Mask> within **AT+GTCFG**, the length of this field is 0 in ASCII format message.
- ✧ <LAC>: Location Area Code in hex format.
- ✧ <Cell ID>: Cell ID in hex format.
- ✧ <Mileage>: The current total mileage or the current tow mileage.

➤ **+RESP:GTFRI,**

If fixed report is enabled, the device will send the message **+RESP:GTFRI** to the backend server according to the working mode.

<b>Example:</b> <b>+RESP:GTFRI,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,12345:12:34,,,80,210100,,,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
External Power VCC	<=5	0 – 32000 mV	
Report ID/Report Type	2	X(1-6)X(0-6)	
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	

LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Hour Meter Count	11	HHHHH:MM:SS	
Analog Input 1	<=5	0~32000 mV	
Reserved	0		
Backup Battery Percentage	<=3	0 – 100	
Device Status	6	000000 – FFFFFFFF	
External Power VCC2	<=5	0 – 32000 mV	
Reserved	0		
Reserved	0		
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <External Power VCC>: The voltage of the external power supply. Use command **AT+GTEPS** to decide whether to send the external power supply voltage periodically with fixed report or not. If not, this field will be empty.

✧ <Report ID/Report Type>: Indicate the working mode of the fixed report and the type of the message.

Report ID has six meanings as below.

- 1: Fixed timing report.
- 2: Fixed distance report.
- 3: Fixed mileage report.
- 4: Fixed timing and mileage report.
- 5: Fixed timing or mileage report.
- 6: GSM DEEP mode fixed timing report

Report type has six meanings as below.

- 0: The normal fixed report.
- 1: Corner report which indicates that the device just turns around a corner.
- 2: FRI report frequency change which indicates that the terminal enters into Geo-Fence status or known/unknown roaming status.
- 3: Corner report when FRI report frequency changed.
- 4: Mileage report when fixed report is mode 5.
- 5: Reserved.
- 6: Mileage report when fixed report is mode 5 and FFC works.

✧ <Number>: The number of the GPS positions included in the message. Generally, it equals to

1.

- ✧ **<Hour Meter Count>**: If hour meter counter function is enabled by the command **AT+GTHMC**, total hours counted when engine is on will be reported in this field. It is formatted with 5 hour digits and 2 minute digits and 2 second digits and ranges from 00000:00:00–99999:00:00. If the function is disabled, this field will be empty.
- ✧ **<Analog1 Input 1>**: The voltage of the analog input 1 or the fuel level measured from the fuel sensor connected to the corresponding analog input port. Use command **AT+GTAIS** to decide whether to send the external voltage of the analog input 1 or 2 or the fuel level with the format of “FXX” periodically with FRI report or not. If not, this field will be empty.
- ✧ **<Backup Battery Percentage>**: The current volume of the backup battery in percentage.
- ✧ **<Device Status>**: The state of the device. The left two bits indicate the current motion state of the device, the middle two bits indicate the input ports status and the right two bits indicate the output ports status.

The current motion state of the device:

- **16 (Tow)**: The device attached vehicle is ignition off and it is towed.
- **1A (Fake Tow)**: The device attached vehicle is ignition off and it might be towed.
- **11 (Ignition Off Rest)**: The device attached vehicle is ignition off and it is motionless.
- **12 (Ignition Off Motion)**: The device attached vehicle is ignition off and it has been moving before it is regarded as being towed.
- **21 (Ignition On Rest)**: The device attached vehicle is ignition on and it is motionless.
- **22 (Ignition On Motion)**: The device attached vehicle is ignition on and it is moving.
- **41 (Sensor Rest)**: The device attached vehicle is motionless without ignition signal detected.
- **42 (Sensor Motion)**: The device attached vehicle is moving without ignition signal detected.

The input ports status: A bitwise hex integer to represent the logical status of the digital input. From the lowest bit to the highest bit, each bit represents ignition detection and one of the digital inputs 1 – 4 respectively. For each bit, 0 means disable status, 1 means enable status.

The output ports status: A bitwise hex integer to represent the logical status of the digital output. From the lowest bit to the highest bit, each bit represents one of the digital outputs 1 – 4 respectively. For each bit, 0 means disable status, 1 means enable status.

- ✧ **<External Power VCC2>**: The voltage of the reserved external power supply. Use command **AT+GTEPS** to decide whether to send the external power supply voltage periodically with FRI report or not. If not, this field will be empty.

#### ➤ **+RESP:GTERI,**

If the **+RESP:GTERI** is enabled, the device will send the message **+RESP:GTERI** to the backend server instead of **+RESP:GTFRI**.

#### **Example:**

```
/*1wire bus connect no device*/
+RESP:GTERI,ED0101,862170019025640,,00000000,,10,,2,1.8,0,-2.5,117.198440,31.845219,20
120802061037,0460,0003,36100010,014B,00,0.0,,,,0,410000,20120802061040,0012$
```

/\*1wire bus connect only one device\*/

+RESP:GTERI,ED0101,862170019025640,,00000002,,10,,1,0,0,0,43.6,117.198435,31.845227,2  
0120728025538,0460,0003,36100010,014B,00,0.0,,,,,0,220100,2,1,FD0000034129ED28,2,01A2  
,20120728025540,0010\$

/\*1wire bus connect two devices\*/

+RESP:GTERI,ED0101,862170019025640,,00000002,,10,1,0,3.2,0,64.7,117.198613,31.845190,  
20120728025304,0460,0003,36100010,014B,00,0.0,,,,,0,210100,2,2,3C00000340FD1128,2,019  
E,FD0000034129ED28,2,01AC,20120728025310,000A\$

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
ERI Mask	8	00000000 – FFFFFFFF	
External Power Supply	<=5	0 – 32000 mV	
Report ID/Report Type	2	X(1-6)X(0-6)	
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Hour Meter Count	11	HHHHH:MM:SS	

Analog Input 1	<=5	0~32000 mV	
Reserved	0		
Backup Battery Percentage	<=3	0 – 100	
Device Status	6	000000 – FFFFFFFF	
External Power Supply2	<=5	0 – 32000 mV	
1-Wire Device Number (optional)	<=1	0-8	
1-Wire Devices ID (optional)	<=16		
1-Wire Devices TYPE (optional)	1	1	
1-Wire Devices DATA (optional)	2		
Fuel Sensor number (Optional)	<=1	0-1	
Sensor Type	1	2	
Percentage (Optional)	<=3	0 –100	
Volume (Optional)	<=5	0 –65535	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <1-Wire Device Number>: The number of 1-wire device connected to GV600M. If it is 0, the following fields <1-wire Device ID>, <1-wire Device Type>, <1-wire Device Data> will not display. If there are more than one 1-wire devices connected, the following fields <1-wire Device ID>, <1-wire Device Type>, <1-wire Device Data> will repeat to show the information of all connected 1-wire devices. If Bit 1 of <ERI Mask> in **AT+GTFRI** is enabled, the part <1-Wire Data> will display, otherwise, the part <1-Wire Data> will not display.
- ✧ <1-Wire Device ID>: Means the 1-Wire device ID read from the device. If the bit 1 is not set to 1 in field <ERI Mask> within **AT+GTFRI**, the length of this field is 0 in ASCII format message.
- ✧ <1-Wire Device TYPE>: Means the 1-Wire device type. If the bit 1 is not set to 1 in field <ERI Mask> within **AT+GTFRI**, the length of this field is 0 in ASCII format message.
  - 1: Temperature sensor.
- ✧ <1-Wire Device DATA>: Means the data read from the 1-Wire devices. If the value of <1-Wire Device Type> is the temperature sensor, this indicates the temperature value. To convert the value of the two bytes in hex to decimal, multiply it by 0.0625 to get the temperature value in Celsius degrees. If the first 5 bits of the high byte are 1, the temperature value is below zero Celsius degrees and the value is represented in two's complement format. To obtain the temperature in decimal, plus the hexadecimal data by 1 and then multiply it by 0.0625 to get the value in Celsius degrees.

**Note:** the key word (optional) means the item is controlled by the parameter *<ERI Mask>*.

➤ **+RESP:GTEPS,**

If the external power supply monitoring is enabled by the command **AT+GTEPS**, the device will send the message **+RESP:GTEPS** to the backend server when the voltage of the external power supply enters the alarm range.

➤ **+RESP:GTAIS,**

If the analog input alarm is enabled by the command **AT+GTAIS**, the device will send the message **+RESP:GTAIS** to the backend server when analog input voltage enters the alarm range.

All of the above messages have the same format as shown below.

<b>Example:</b> <b>+RESP:GTEPS,ED0101,862170019025640,,13500,00,,1,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$</b>  <b>+RESP:GTAIS,ED0101,862170019025640,,1980,11,,1,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
External Power/Analog Input VCC	<=5	0 – 32000 mV	
Report ID/Report Type	2	X(0-2)X(0-1)	
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	



LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
External Power/Reserved	<=5 0	0 – 32000 mV   0	
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <External Power/Analog Input VCC>: The value of the external power supply voltage or the analog input voltage. When the voltage of the analog input meets the alarm condition set by command **AT+GTEPS** or **AT+GTAIS**, the device will send the current analog input voltage along with **+RESP:GTEPS** or **+RESP:GTAIS** message to the backend server

✧ <Report ID/Report Type>: The report ID and the type of the report type in hex format. 4 high bits mean report ID and 4 low bits means report type.

Report ID has different meanings in these two messages.

- The ID of analog input port which triggers message **+RESP:GTEPS**. The value is 1-2.
- The ID of analog input port which triggers message **+RESP:GTAIS**. The range is 1.

Report type has two meanings as below:

- 0: Outside of the predefined range.
- 1: Inside of the predefined range.

✧ <Number>: The number of the GPS positions included in the message. Generally, it equals to 1.

➤ **+RESP:GTGIN**

➤ **+RESP:GTGOT**

If Geo-Fence is configured and enabled, the device will send the message **+RESP:GTGIN** to the backend server according to the settings when the device enters the Geo-Fence and will send **RESP:GTGOT** when the device exits the Geo-Fence.

**Example:**

```
+RESP:GTGIN,ED0101,862170019025640,,,,1,,,,,3,0.7,0,58.9,117.201251,31.833126,20140511
093254,0460,0003,36100010,014B,00,0.0,,,,,20140511093254,0013$
+RESP:GTGOT,ED0101,862170019025640,,,,1,,,,,3,0.0,0,58.9,117.201251,31.833126,20140511
093254,0460,0003,36100010,014B,00,0.0,,,,,20140511093254,0016$
```

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	

Reserved			
Reserved			
Area Type	1	0-1	
GEO ID Group	<=5	20 bit 1-FFFFFF (GEOID 0 – 19)	
Reserved			
Reserved			
Reserved			
Reserved			
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Reserved			
Reserved			
Reserved			
Reserved			
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Area Type>: 0-Polygon GEO; 1-Circle GEO.

- ✧ **<GEO ID Group>**: The bitwise mask for trigger condition composition of the corresponding GEO ID. Each bit, from bit 0 to bit 19, represents the logical status of the corresponding GEO ID to trigger the entering or exiting event. 1 means that the event of the GEO ID set has been triggered and 0 means has not.

➤ **+RESP:GTGES**

Report **+RESP:GTGES** according to Trigger Mode and Trigger Report in **AT+GTGEO** after ignition off.

**Example:**

**+RESP:GTGES,ED0101,862170019025640,gv600m,,0,0,0,100,30,,1,24.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Reserved			
Trigger GEO ID	<=2	0-19	
Trigger GEO Enable	1	0 1	
Trigger Mode	<=3	0 21 22	
Radius	<=7	50 – 6000000m	
Check Interval	<=5	0 5 – 86400sec	
Number	1	0 – 1	
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	

Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Trigger GEO ID>: The ID of Geo-Fence. The range is 0 – 19.
- ✧ <Trigger GEO Enable>: Current Parking-Fence is active or inactive.
  - 0 Current Parking-Fence is inactive.
  - 1 Current Parking-Fence is active.

➤ **+RESP:GTLBC,**

If the bit 4 or bit 5 of <location request mask> in command **AT+GTCFG** is set to 1, the device will get and send the current position to the backend server by the message **+RESP:GTLBC** when there is a location request.

**Example:**

**+RESP:GTLBC,ED0101,862170019025640,,+8613800000000,1,4.3,92,70.0,121.354335,31.222073,20151015013254, 0460,0003,36100010,014B,00,20151015093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Original Number	<=20	phone number	
Number	1	1	1
GPS Accuracy	<=2	0 1 – 50	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	

MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved			
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ *<Original Number>*: The phone number that triggers the message.

➤ **+RESP:GTIDA,**

According to the *<Mode>* of the command **AT+GTIDA**, the reporting mode of **+RESP:GTIDA** varies.

If *<Mode>* is set to 1 or 2, **+RESP:GTIDA** will be reported according to the configuration in *<Report Mode>*.

If *<Mode>* is set to 0, **+RESP:GTIDA** will always be reported without checking the state of ID authorization.

<b>Example:</b> <b>+RESP:GTIDA,ED0101,862170013895931,,D2C4FBC5,1,1,1,0.8,0,22.2,117.198630,31.845229,20120802121626,0460,0000,5663,2BB9,00,0.0,,,,,20120802121627,008E\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	≤20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Reserved			
ID	≤20	'0' – '9' 'A' – 'F'	
ID Report Type	1	0/1/2	
Number	1	0 – 1	
GPS Accuracy	≤2	0/1 – 50	
Speed	≤5	0.0 – 999.9 km/h	
Azimuth	≤3	0 – 359	
Altitude	≤8	(-)xxxxx.x m	
Longitude	≤11	(-)xxx.xxxxxx	
Latitude	≤10	(-)xx.xxxxxx	

GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Reserved			
Reserved			
Reserved			
Reserved			
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <ID>: The ID that is read currently.
- ✧ <ID Report Type>: A numeric to indicate the type of reported ID.
  - 0: The ID is unauthorized or IDA function is disabled.
  - 1: The ID is authorized.
  - 2: The ID has logged out.

### 3.3.2. Device Information Report

If the device information report function is enabled by the command **AT+GTCFG**, the device will send the device information by the message **+RESP:GTINF** to the backend server periodically.

#### ➤ +RESP:GTINF,

**Example:**

**+RESP:GTINF,ED0101,862170019025640,,16,,16,0,1,12000,,4.40,0,0,0,0,20140511093254,0,1300,2000,00,00,+0800,0,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
State	2	11 12 21 22 41 42 1A 16	
ICCID	20	'0' – '9' 'a' – 'z' 'A' – 'Z'	

CSQ RSSI	<=2	0 – 31	
CSQ FER	<=2	0 – 7	
External Power Supply	2	00 01 10 11	
External Power VCC	<=5	0 – 32000mV	
External Power VCC2	<=5	0 – 32000mV	
Backup Battery VCC	<=4	0.00 – 4.50 V	
Charging	1	0 1	
LED On	1	0 1	
Reserved	0		
Reserved			
Last Fix UTC Time	14	YYYYMMDDHHMMSS	
IO Mode	1	0-F	
Analog Input VCC1	<=5	0~32000mV	
Reserved			
Digital Input	2	00 – 1F	
Digital Output	2	00 – 0F	
Reserved	0		
Reserved	0		
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <State>: The current motion state of the device.

- 16 (**Tow**): The device attached vehicle is ignition off and it is towed.
- 1A (**Fake Tow**): The device attached vehicle is ignition off and it might be towed.
- 11 (**Ignition Off Rest**): The device attached vehicle is ignition off and it is motionless.
- 12 (**Ignition Off Motion**): The device attached vehicle is ignition off and it has been moving before it is regarded as being towed.
- 21 (**Ignition On Rest**): The device attached vehicle is ignition on and it is motionless.
- 22 (**Ignition On Motion**): The device attached vehicle is ignition on and it is moving.
- 41 (**Sensor Rest**): The device attached vehicle is motionless without ignition signal detected.
- 42 (**Sensor Motion**): The device attached vehicle is moving without ignition signal detected.

✧ <CSQ RSS/>: The signal strength level.

CSQ RSSI	Signal Strength (dBm)
0	<-133
1	-111
2 – 30	-109 – -53
31	>-51

- ✧ <CSQ FER>: The quality of the network signal. The range is 0-7.
- ✧ <External Power Supply>: Whether the external power supply is connected.
  - 00: No External Power Supply connected
  - 01: External Power Supply VCC connected, VCC2 not connected.
  - 10: External Power Supply VCC2 connected, VCC not connected
  - 11: Two external power supplies connected.
- ✧ <External Power Supply VCC>: The voltage of the external power supply.
- ✧ <External Power Supply VCC2>: The voltage of the external power supply.
- ✧ <Backup Battery VCC>: The voltage of the backup battery. The value of this field is only valid when the external power is not connected.
- ✧ <Charging>: Whether the backup battery is being charged when the main power supply is connected.
  - 0: Not charging
  - 1: Charging
- ✧ <Last Fix UTC Time>: The UTC time of the latest successful GPS fixing.
- ✧ <IO Mode>: The working mode of IO1-IO4 on the connector.
- ✧ <Analog Input VCC1>: The voltage of the analog input 1.
- ✧ <Digital Input>: A bitwise hex integer to represent the logical status of the digital input. From the lowest bit to the highest bit, each bit represents ignition detection and one of the digital inputs 1 – 4 respectively. For each bit, 0 means disabled status and 1 means enabled status.
- ✧ <Digital Output>: A bitwise hex integer to represents the logical status of the digital output. From the lowest bit to the highest bit, each bit represents one of the digital outputs 1 – 4 respectively. For each bit, 0 means disabled status and 1 means enabled status

### 3.3.3. Report of Real Time Querying

#### 3.3.3.1. +RESP:GTGPS

After the device receives the command **AT+GTRTO** to read the GPS information, it will send the GPS information to the backend server by the message **+RESP:GTGPS**.

➤ **+RESP:GTGPS,**

<b>Example:</b> <b>+RESP:GTGPS,ED0101,862170019025640,,,,,0000,,0,20140511093254,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	



Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Reserved	0		
Reserved	0		
Reserved	0		
Report Composition Mask	4	0000 – FFFF	
Reserved	0		
Reserved			
Last Fix UTC Time	14	YYYYMMDDHHMMSS	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Report Composition Mask>: Refer to <Report Composition Mask> of **AT+GTCFG** command.

### 3.3.3.2. +RESP:GTALM

After the device receives the command **AT+GTRTO** to read all the configurations, it will send all configurations to the backend server by the message **+RESP:GTALL**. This message is only sent via GPRS even if the report mode is Force on SMS. If the message's length is too long, then it will be sub packaged into several **+RESP:GTALM** messages. The **+RESP:GTALM** does not support HEX report.

#### ➤ +RESP:GTALM,

##### Example:

```
+RESP:GTALM,ED0101,862170019025640,,16,1,BSI,cmnet,,,,,,,,SRI,3,,1,116.228.146.250,8186,1
92.0.0.0,0,,0,0,0,0,,,CFG,gv600m,gv600m,0,0,0,0,,003F,1,,3FFF,0,0,0,300,0,1,0,0,001F,0,TOW,0,
10,1,300,0,0,0,0,2,3,2,,,,,,,,EPS,0,0,0,0,0,0,0,0,0,0,DIS,0,1,,0,1,0,0,0,2,0,0,0,3,0,,0,,,,OUT,0,,,
,,,IOB,0,0,0,0,0,0,0,0,,,,,1,0,0,0,0,0,0,0,,,,,2,0,0,0,0,0,0,0,,,,,3,0,0,0,0,0,0,0,,,,,TMA,+0000,0,,,,FR
I,0,1,,1,0000,0000,180,30,1000,1000,,0,600,00000000,,,,,20130508122835,0009$
```

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	

Total Packets	2	10	
Current Packet	<=2	1 – 10	
Configurations	< 1500		
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Total Packets>: The total number of **+RESP:GTALM**.
- ✧ <Current Packet>: The sequence number of current packet.
- ✧ <Configurations>: The current configuration of the device. The 1st message contains configuration for the commands from **BSI** to **FRI**, the 2nd is for the commands from **GEO** to **DOG**, the 3rd is for the commands from **AIS** to **SSR**, the 4th to 7th are for the command **IDA**, the 8th is for the commands from **ACD** to **TMP**, the 9th is for the command **RMD**, the 10th to 13th messages are for the command **PEO**, the 14th is for the commands from **GLM** to **BTE**.

**Note:** The length of every **+RESP:GTALM** message (including header and tail) should be no more than 1500 characters.

#### 3.3.3.3. +RESP:GTALC

After the device receives the command **AT+GTRTO** to read the configurations, it will send corresponding configuration information to the backend server by the message **+RESP:GTALC** according to the configuration mask. This message is only sent via GPRS even if the report mode is Force on SMS. The **+RESP:GTALC** does not support HEX report.

➤ **+RESP:GTALC,**

**Example:**

```
+RESP:GTALC,ED0105,352948070050376,gv600m,77FBFFB,1,1,BSI,3gnet,sss,123,,,,0,SRI,3,,1,21
8.17.46.11,880,,0,15889592611,0,0,0,0,,,CFG,gv600m,gv600m,1,666.0,,,007F,0,,7FFD,C,1,1,30,
10,,0,0,00FF,0,,,,,24,,15,1,0,,TOW,0,10,1,300,0,0,0,0,2,3,3,,,,,,,,,EPS,0,250,250,0,0,0,0,0,00,,0
,0,250,250,0,0,0,0,0,DIS,0,1,5,0,1,0,0,0,2,0,0,0,3,0,0,0,4,0,0,0,OUT,0,,,,,,IOB,0,0,0,0,0,0,0,0,,,,
,1,0,0,0,0,0,0,0,2,0,0,0,0,0,0,0,3,0,0,0,0,0,0,0,TMA,+0700,1,,,,,FRI,1,0,,1,0000,0000,,360
0,1000,1000,,0,3600,00000000,,,GEO,0,0,,50,0,0,0,0,0,0,0,1,0,,,50,0,0,0,0,0,0,0,2,0,,,50,0,0,
0,0,0,0,0,0,,3,0,,50,0,0,0,0,0,0,0,4,0,,,50,0,0,0,0,0,0,0,5,0,,,50,0,0,0,0,0,0,0,6,0,,,50,0,0,0,0,0,
0,0,,,7,0,,,50,0,0,0,0,0,0,0,8,0,,,50,0,0,0,0,0,0,0,9,0,,,50,0,0,0,0,0,0,0,10,0,,,50,0,0,0,0,0,0,0,
,11,0,,,50,0,0,0,0,0,0,0,12,0,,,50,0,0,0,0,0,0,0,13,0,,,50,0,0,0,0,0,0,0,14,0,,,50,0,0,0,0,0,0,0,
15,0,,,50,0,0,0,0,0,0,0,16,0,,,50,0,0,0,0,0,0,0,17,0,,,50,0,0,0,0,0,0,0,18,0,,,50,0,0,0,0,0,0,0,
19,0,,,50,0,0,0,0,0,0,0,SPD,1,0,1,0,3600,0,0,0,0,,,,,,,,,SOS,0,0,,0,0,0,0,,,,,PIN,0,,0,,,,,OWH,0,1
F,0900,1200,1300,1800,,,0,0,0,0,0,0,,,DOG,0,60,30,0200,,1,0,0,480,480,480,AIS,1,0,0,0,0,,0,0,0,
0,0,,,,,,,,,,,,,10,30,10,20,0,IDL,1,30,5,,,,,0,0,0,0,,,,,HMC,1,00000:00:00,,,,,,WLT,0,,,,,,,,,,,,,HR
M,,,7F,FEFFFF,FEFFFF,2F7F,FF,7F,7F,,,,,14E0$
```

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Configuration Mask	<=16	0000000000000000 – FFFFFFFFFFFFFFFF	
Next Packet	1	0-1	0
Current Packet	<=2	1-20	1
BSI	3	BSI	BSI
APN	<=40		
APN User Name	<=30		
APN Password.	<=30		
Backup APN	<=40		
Backup APN User Name	<=30		
Backup APN Password	<=30		
Network Mode	1		0
Manual netreg	1		
SRI	3	SRI	SRI
Report Mode	1	0 – 7	0
Reserved	0		
Buffer Mode	1	0 1 2	1
Main Server IP/ Domain Name	<=60		
Main Server Port	<=5	0 – 65535	
Backup Server IP/ Domain Name	<=60		
Backup Server Port	<=5	0 – 65535	
SMS Gateway	<=20		
Heartbeat Interval	<=3	0 5 – 360min	0
Enable SACK	1	0 1 2	0
Protocol Format	1	0 1	0

Enable SMS ACK	1	0 1	0
Reserved	0		
Reserved	0		
CFG	3	CFG	CFG
Password	4-20	'0' - '9' 'a' - 'z' 'A' - 'Z'	gv600m
Device Name	<=20	'0' - '9' 'a' - 'z' 'A' - 'Z' '-' '_'	gv600m
Enable ODO	1	0 1	0
ODO Initial Mileage	<=9	0.0 - 4294967.0Km	0.0
Reserved	0		
Reserved	0		
Report Component Mask	4	0000 - FFFF	003F
Power Saving Mode	1	0 - 3	1
Reserved	0		
Event Mask	4	0000 - FFFF	3FFFF
IO Mode	1	0 - F	0
LED On	1	0 1	0
Enable Info Report	1	0 1	0
Info Report Interval	<=5	30 - 86400sec	300
Location request mask	1	00 20	00
Reserved	0		
Backup Battery Charge Mode	1	0 1	0
AGPS Mode	1	0 1	0
GSM Report	4	0000 - FFFF	000F
GPS Lost Time	2	0 - 30min	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Wakeup Hour Interval	<=3	1-720	24

Sensor wakeup device debounce	<=2	0 10-60(s)	10
Work Time Per Wakeup	<=2	5-60	15
Power Output	1	0 1	0
Temperature Sample Interval	<=2	0 10-255(s)	0
Reserved	0		
TOW	3	TOW	TOW
Tow Enable	1	0 1	0
Engine Off to Tow	<=2	5 – 15min	10
Fake Tow Delay	<=2	0 – 10min	1
Tow Interval	<=5	30 – 86400sec	300
Tow Output ID	1	0 – 4	0
Tow Output Status	1	0 1	0
Tow Output Duration	<=3	0 – 255(×100ms)	0
Tow Output Toggle Times	<=3	0 – 255	0
Rest Duration	<=3	1 – 255(×15sec)	2
Motion Duration	<=2	1 – 10(×100ms)	3
Motion Threshold	1	2 – 9	3
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
EPS	3	EPS	EPS
Mode	1	0 1 2	0
Min. Threshold	<=5	250 – 32000 mV	250
Max. Threshold	<=5	250 – 32000 mV	250

Sample Period	$\leq 2$	0 1 – 12( $\times 2s$ )	0
Debounce Time	1	0 – 5( $\times 1s$ )	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255( $\times 100ms$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Sync with FRI	2	00 01 10 11	00
Reserved	0		
Reserved	0		
MPN/MPF Validity Time	1	0 – 255 ( $\times 1s$ )	0
Mode	1	0 1 2	0
Min. Threshold	$\leq 5$	250 – 32000 mV	250
Max. Threshold	$\leq 5$	250 – 32000 mV	250
Sample Period	$\leq 2$	0 1 – 12( $\times 2s$ )	0
Debounce Time	1	0 – 5( $\times 1s$ )	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255( $\times 100ms$ )	0
Toggle Times	$\leq 3$	0 – 255	0
DIS	3	DIS	DIS
Ignition Detection	1	0	0
Reserved	1	1	1
Debounce Time	$\leq 2$	0 – 20( $\times 10ms$ )	5
No ignition	1	0 1	0
Input ID 1	1	1	1
Enable	1	0 1	0
Debounce Time	$\leq 2$	0 – 20( $\times 10ms$ )	0
Validity Time	$\leq 2$	0 1 – 12( $\times 2s$ )	0
Input ID 2	1	2	2
Enable	1	0 1	0

Debounce Time	$\leq 2$	0 – 20( $\times 10\text{ms}$ )	0
Validity Time	$\leq 2$	0 1 – 12( $\times 2\text{s}$ )	0
Input ID 3	1	3	3
Enable	1	0 1	0
Debounce Time	$\leq 2$	0 – 20( $\times 10\text{ms}$ )	0
Validity Time	$\leq 2$	0 1 – 12( $\times 2\text{s}$ )	0
Input ID 4	1	3	4
Enable	1	0 1	0
Debounce Time	$\leq 2$	0 – 20( $\times 10\text{ms}$ )	0
Validity Time	$\leq 2$	0 1 – 12( $\times 2\text{s}$ )	0
OUT	3	OUT	OUT
DOS Report	1	0-7	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
IOB	3	IOB	IOB
IOB ID0	1	0	0
Input Mask	2	0 – 1F	0
Trigger Mask	2	0 – 1F	0
Input Sample Period	$\leq 2$	0 1 – 12( $\times 2\text{s}$   $\times 4\text{s}$ )	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		

Reserved	0		
IOB ID1	1	1	1
Input Mask	2	0 – 1F	0
Trigger Mask	2	0 – 1F	0
Input Sample Period	$\leq 2$	0   1 – 12( $\times 2s$   $\times 4s$ )	0
Output ID	1	0 – 4	0
Output Status	1	0   1	0
Duration	$\leq 3$	0 – 255( $\times 100ms$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
IOB ID2	1	2	2
Input Mask	2	0 – 1F	0
Trigger Mask	2	0 – 1F	0
Input Sample Period	$\leq 2$	0   1 – 12( $\times 2s$   $\times 4s$ )	0
Output ID	1	0 – 4	0
Output Status	1	0   1	0
Duration	$\leq 3$	0 – 255( $\times 100ms$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved			
IOB ID3	1	3	3
Input Mask	2	0 – 1F	0
Trigger Mask	2	0 – 1F	0
Input Sample Period	$\leq 2$	0   1 – 12( $\times 2s$   $\times 4s$ )	0
Output ID	1	0 – 4	0



Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved			
TMA	3	TMA	TMA
Time zone	1	- +HHMM	+
Daylight Saving	1	0 1	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
FRI	3	FRI	FRI
Mode	1	0 – 5	0
Discard No Fix	<=2	0 1	1
Reserved	0		
Enable Period	1	0 1	1
Begin Time	4	HHMM	0000
End Time	4	HHMM	0000
Check Interval	<=5	0 30 – 86400sec	180
Send Interval	<=5	0 5 – 86400sec	30
Distance	<=5	300 – 65535m	1000
Mileage	<=5	300 – 65535m	1000
Reserved	0		
Corner Report	<=3	0 – 180	0
IGF Report Interval	<=5	0 5-86400sec	600
ERI Mask	8	00000000-FFFFFFFF	00000000
Reserved	0		

Reserved	0		
Reserved	0		
GEO	3	GEO	GEO
GEO ID0	1	0	0
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID1	1	1	1
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		

Reserved	0		
GEO ID2	1	2	2
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID3	1	3	3
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID4	1	4	4

Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID5	1	5	5
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID6	1	6	6
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000

Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID7	1	7	7
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID8	1	8	8
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50

Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID9	1	9	9
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID10	2	10	10
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0

Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID11	2	11	11
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID12	2	12	12
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0

Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID13	2	13	13
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID14	2	14	14
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0



Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID15	2	15	15
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID16	2	16	16
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		

Reserved	0		
GEO ID17	2	17	17
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID18	2	18	18
Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
GEO ID19	2	19	19

Mode	1	0 – 3	0
Longitude	<=11	(-)xxx.xxxxxx	0.000000
Latitude	<=10	(-)xx.xxxxxx	0.000000
Radius	<=7	50 – 6000000m	50
Check Interval	<=5	0   5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Trigger Mode	<=2	0 21 22	0
Trigger Report	1	0 1	0
Reserved	0		
Reserved	0		
SPD	3	SPD	SPD
Mode	1	0 1 2 3 4	0
Min Speed	<=3	0 – 400km/h	0
Max Speed	<=3	0 – 400km/h	0
Validity	<=4	15 – 3600sec	60
Send Interval	<=4	30 – 3600sec	300
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Report ID	<=2	0 – 15	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		

Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
SOS	3	SOS	SOS
Mode	1	0 – 4	0
Digital Input ID	1	0 – 4	0
Reserved			
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
PIN	3	PIN	PIN
Enable Auto-unlock PIN	1	0 1	1
PIN	1	'0' – '9'	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
OWH	3	OWH	OWH
Mode	1	0 1 2 3	0
Day of Work	<=2	0 – 7F	1F
Working Hours Start1	4	HHMM	0900
Working Hours End1	4	HHMM	1200
Working Hours Start2	4	HHMM	1300

Working Hours End2	4	HHMM	1800
Reserved	0		
Reserved	0		
Digital Input ID	1	0 – 4	0
Digital Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
DOG	3	DOG	DOG
Mode	1	0 1 2	1
Ignition Frequency	<=3	10 – 120min	60
Interval	<=2	1 – 30	7
Time	4	HHMM	0200
Reserved	0		
Report Before Reboot	1	0 1	1
Input ID	1	0-4	0
Unit	1	0 1	0
No Network Interval	4	0   5-1440 min	480
No Activation Interval	4	0   5-1440 min	480
Send Failure timeout	4	0   5-1440 min	480
AIS	3	AIS	AIS
Analog Input ID1	1	1	1
Mode	1	0 1 2 3 4 5	0
Min. Threshold	<=5	0~2700 0~32000mV	0
Max. Threshold	<=5	0~2700 0~32000mV	0
Sample Period	<=2	0 1 – 12(×2s)	0

Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255(×100ms)	0
Toggle Times	$\leq 3$	0 – 255	0
Sync with FRI	1	0 1	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Fuel Data Debounce	$\leq 3$	0-150	10
Fuel Sensor Delay	$\leq 3$	0-600 sec	30
Fuel Lost Alarm	$\leq 2$	0-50	10
Fuel Sensor Sample Count	$\leq 3$	0-150	20
Change Threshold	$\leq 2$	0-50%	0
IDL		IDL	IDL
Mode	1	0 1	0
Time to Stationary	2	1 – 30 min	2
Time to Movement	1	1 – 5 min	1
Reserved	0		

Reserved	0		
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
IDF after IGF	1	0-1	0
Reserved	0		
Reserved	0		
Reserved	0		
HMC	3	HMC	HMC
Enable Hour Meter	1	0 1	0
Initial Hour Meter Count	11	00000:00:00-99999:00:00	00000:00:00
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
WLT	3	WLT	WLT
Call Filter	1	0 1 2 3	
Start Index	<=2	1 – 10	
End Index	<=2	1 – 10	
Phone Number List	<=20*10		
Reserved	0		
Reserved	0		
Reserved	0		

Reserved	0		
HRM	3	HRM	HRM
Reserved	0		
Reserved	0		
ACK Mask	1	'0' – '9' 'a' – 'f' 'A' – 'F'	7F
Response Mask	4	'0' – '9' 'a' – 'f' 'A' – 'F'	FFFFFFFF
Event Mask	4	'0' – '9' 'a' – 'f' 'A' – 'F'	FFFFFFFF
Information Mask	<=8	'0' – '9' 'a' – 'f' 'A' – 'F'	2F7F
HBD Mask	1	'0' – '9' 'a' – 'f' 'A' – 'F'	FF
DAT Mask	<=8	00000000 – FFFFFFFF	7F
Reserved	0		
Reserved	0		
Reserved	0		
FFC	3	FFC	FFC
Priority	1	0	0
Mode	1	0-3	0
FRI Mode	1	0-5	0
FRI IGN Report Interval	<=5	5-86400s	30
FRI Report Distance	<=5	50-65535m	500
FRI Report Mileage	<=5	50-65535m	500
FRI IGF Report Interval	<=5	0 5-86400s	300
Reserved			
Reserved			
Reserved			
Reserved			
Priority	1	1	1
Mode	1	0-3	0
FRI Mode	1	0-5	0
FRI IGN Report Interval	<=5	5-86400s	30
FRI Report Distance	<=5	50-65535m	500



FRI Report Mileage	<=5	50-65535m	500
FRI IGF Report Interval	<=5	0 5-86400s	300
Reserved			
Reserved			
Reserved			
Reserved			
Priority	1	2	2
Mode	1	0-3	0
FRI Mode	1	0-5	0
FRI IGN Report Interval	<=5	5-86400s	30
FRI Report Distance	<=5	50-65535m	500
FRI Report Mileage	<=5	50-65535m	500
FRI IGF Report Interval	<=5	0 5-86400s	300
Reserved			
Reserved			
Reserved			
Reserved			
Priority	1	3	3
Mode	1	0-3	0
FRI Mode	1	0-5	0
FRI IGN Report Interval	<=5	5-86400s	30
FRI Report Distance	<=5	50-65535m	500
FRI Report Mileage	<=5	50-65535m	500
FRI IGF Report Interval	<=5	0 5-86400s	300
Reserved			
Reserved			
Reserved			
Reserved			
Priority	1	4	4
Mode	1	0-3	0

FRI Mode	1	0-5	0
FRI IGN Report Interval	<=5	5-86400s	30
FRI Report Distance	<=5	50-65535m	500
FRI Report Mileage	<=5	50-65535m	500
FRI IGF Report Interval	<=5	0 5-86400s	300
Reserved			
Reserved			
Reserved			
Reserved			
SSR	3	SSR	SSR
Mode	1	0 1	0
Time to Stop	2	1 – 30 min/5-1800 sec	2
Time to Start	1	1 – 5 min/5-300 sec	1
Start Speed	2	1 – 10 Km/h	5
Long Stop	<=5	0 – 43200 min	0
Reserved	0		
Reserved	0		
Reserved	0		
IDA	3	IDA	IDA
Mode	1	0/1/2	0
Start Index	<=2	1 – 250	
End Index	<=2	1 – 250	
ID Number List	<=8*20	'0' – '9', 'a' – 'f', 'A' – 'F'	
Timeout After Ignition Off	<=3	0/15 – 600sec	30
Report Mode	1	0 – 7	0
ID Valid Time	<=3	15 – 600sec	30
Reserved	0		
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0

Output Status	1	0/1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
ACD	3	ACD	ACD
iButton Timer	<=2	0 1 – 10(s)	0
Output ID	1	0-4	0
Output status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle	<=3	0 – 255	0
Reserved			
Reserved			
Reserved			
Reserved			
Reserved			
PDS	3	PDS	PDS
Mode	1	0 1 2	0
Mask	4	0000-FFFF	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
BZA	3	BZA	BZA
Output ID	1	0 2 3	0
Reserved	0		

Reserved	0		
Reserved	0		
Alarm 1 Output Status	1	0 1	
Duration	$\leq 3$	0 – 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Alarm 2 Output Status	1	0 1	
Duration	$\leq 3$	0 – 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Alarm 3 Output Status	1	0 1	
Duration	$\leq 3$	0 – 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Alarm 4 Output Status	1	0 1	
Duration	$\leq 3$	0 – 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
SPA	3	SPA	SPA
Mode	1	0 12	0

Speed Threshold 1	<=3	0 – 400km/h	50
Reserved	0		
Validity	<=4	0 – 3600sec	60
Alarm Type	1	0 1 – 4	0
Reserved	0		
Reserved	0		
Speed Threshold 2	<=3	0 – 400km/h	70
Reserved	0		
Validity	<=4	0 – 3600sec	60
Alarm Type	1	0 1 – 4	0
Reserved	0		
Reserved	0		
Speed Threshold 3	<=3	0 – 400km/h	90
Reserved	0		
Validity	<=4	0 – 3600sec	60
Alarm Type	1	0 1 – 4	0
Reserved	0		
Reserved	0		
Speed Threshold 4	<=3	0 – 400km/h	110
Reserved	0		
Validity	<=4	0 – 3600sec	60
Alarm Type	1	0 1 – 4	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		

MUT	3	MUT	MUT
Working Mode	<=2	0   1   4	0
Baudrate Index	<=2	1 – 12	5
Data Bits	1	8	8
Stop Bits	1	1 – 3	1
Parity Bits	1	0 – 4	0
Sleep Enable	1	0 1	0
Input ID of Wakeup	0	0 1-4	0
Reserved (Optional)	0	0	0
Reserved (Optional)	0	0	
TMP	3	TMP	TMP
Alarm ID	1	0-7	0
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		

Reserved	0		
Reserved	0		
Alarm ID	1	0-7	1
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	2
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0

Reserved	0		
Reserved	0		
Validity	$\leq 2$	1 – 10	2
Send Interval	$\leq 2$	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255(×100ms)	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	3
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	$\leq 3$	-55 – 125°C	0
High Temperature	$\leq 3$	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	$\leq 2$	1 – 10	2
Send Interval	$\leq 2$	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	$\leq 3$	0 – 255(×100ms)	0



Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	4
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	5
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		

Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	6
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		

Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Alarm ID	1	0-7	7
Mode	1	0-3	0
Sensor ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Reserved	0		
Low Temperature	<=3	-55 – 125°C	0
High Temperature	<=3	-55 – 125°C	0
Reserved	0		
Reserved	0		
Validity	<=2	1 – 10	2
Send Interval	<=2	0 – 60	10
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
RMD	3	RMD	RMD

Mode	1	0 1	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Home Operator List	$\leq 6 \times 10$		
Reserved	0		
Reserved	0		
Roaming Operator List	$\leq 6 \times 100$		
Reserved	0		
Reserved	0		
Black Operator List	$\leq 6 \times 20$		
Reserved	0		
Reserved	0		
Known Roaming Event Mask	$\leq 4$	0000 – 3FFF	3FFF
Reserved	0		
Reserved	0		
Unknown Roaming Event Mask	$\leq 4$	0000 – 3FFF	3FFF
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Output ID	1	0 – 4	0
Output Status	1	0 1	
Duration	$\leq 3$	0 ~ 255( $\times 100\text{ms}$ )	0
Toggle Times	$\leq 3$	0 – 255	0
Reserved	0		
Reserved	0		
PEO	3	PEO	PEO

GEO ID	1	0 – 19	0
Mode	1	0 – 3	0
Start point	1	1-10	1
End point	<=2	1-10	3
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
...			
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
Check Interval	<=5	0 5 – 86400sec	0
Output ID	1	0 – 4	0
Output Status	1	0 1	
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
GLM	3	GLM	GLM
Google Mode	1	0 1 2	0
Mobile Start	1	1-3	
Mobile End	1	1-3	
Direct Number List	<=20*3		
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
GAM	3	GAM	GAM
Mode	1	0 1	1
Speed Mode	1	0 1	1

Motion Speed Threshold	<=2	5-50km/h	25
Motion Cumulative Time	<=3	10-100s	10
Motionless Cumulative Time	<=3	10-250s	60
GPS Fix Failure Timeout	<=4	5-1800s	60
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
GPJ	3	GPJ	GPJ
Mode	1	0 1	0
CW Threshold	<=2	0 - 31	15
BB Threshold	<=2	0 - 15	3
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Output ID	1	0 - 4	0
Output Status	1	0 1	0
Duration	<=3	0 - 255(×100ms)	0
Toggle Times	<=3	0 - 255	0
Reserved	0		
BTE	3	BTE	BTE
Mode	1	0 1	0
Send Interval	<=3	30-43200s	300
Low Temperature Threshold	<=3	-40 - 80℃	0
High Temperature Threshold	<=3	-40 - 80℃	10
Low Voltage Threshold	<=4	0-5000mv	2400
Start Point	<=2	1-10	1

End Point	<=2	1-10	1
MAC Addr	12	'0' – '9' 'a' – 'f' 'A' – 'F'	
Output ID	1	0 – 4	0
Output State	1	0 1	0
Duration	<=3	0 – 255(×100ms)	0
Toggle Times	<=3	0 – 255	0
Reserved	0		
Reserved	0		
Reserved	0		
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Next Packet>: Related information packet is complete or not.

- 0: There is a complete information packet.
- 1: There is not a complete information packet.

✧ <Current Packet>: This is the index of **+RESP:GTALC**.

### 3.3.3.4. +RESP:GTCID

After the device receives the command **AT+GTRTO** to read the ICCID of the SIM card, it will send the ICCID to the backend server by the message **+RESP:GTCID**.

➤ **+RESP:GTCID,**

Example: <b>+RESP:GTCID,ED0101,862170019025640,,898600810906F8048812,20090214093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
ICCID	20		
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.3.3.5. +RESP:GTCSQ

After the device receives the command **AT+GTRTO** to read the network signal level, it will send the network signal level to the backend server by the message **+RESP:GTCSQ**.

#### ➤ +RESP:GTCSQ,

Example: +RESP:GTCSQ,ED0101,862170019025640,,16,0,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
CSQ RSSI	<=2	0 – 31	
CSQ FER	<=2	0 – 7	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <CSQ RSSI>: The signal strength level.

CSQ RSSI	Signal Strength (dBm)
0	<-133
1	-111
2 – 30	-109 – -53
31	>-51

✧ <CSQ FER>: The quality of the network signal. The range is 0-7.

### 3.3.3.6. +RESP:GTVER

After the device receives the command **AT+GTRTO** to get the versions (including firmware version, hardware version and module version), it will send the version information to the backend server by the message **+RESP:GTVER**.

#### ➤ +RESP:GTVER,

Example: +RESP:GTVER,ED0101,862170019025640,,GV600,0101,0101,0101,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default



Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
Device Type	10	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Firmware Version	4	0000 – FFFF	
Hardware Version	4	0000 – FFFF	
Spi-flash Version	4	0000 – FFFF	
Modem Hardware Version	<=20		
Modem Software Version	<=50		
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Device Type>: The type of the device.
- ✧ <Firmware Version>: The firmware version. The first two characters represent the major version and the last two characters represent the minor version. For example: **010A** means the version GV600R00A01V10.
- ✧ <Hardware Version>: The hardware version. The first two characters represent the major version and the last two characters represent the minor version. For example: **010A** means the version **1.10**.
- ✧ <Spi-Flash Version>: Reserved
- ✧ <Modem Hardware Version>: The module model HL8518
- ✧ <Modem Software Version> : The software version of the modem, for example "RHL85xx.5.14.0.5.0. 20160401.x6255"

### 3.3.3.7. +RESP:GTBAT

After the device receives the command **AT+GTRTO** to read the power supply information, it will send the power supply information to the backend server by the message **+RESP:GTBAT**.

#### ➤ +RESP:GTBAT,

<b>Example:</b> <b>+RESP:GTBAT,ED0101,862170019025640,,10,12000,,4.40,0,0,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	

Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
External Power Supply	2	00 01 10 11	
External Power VCC	<=5	0 – 32000mV	
External Power VCC2	<=5	0 – 32000mV	
Backup Battery VCC	<=4	0.00 – 4.50 V	
Charging	1	0 1	
LED On	1	0 1	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.3.3.8. +RESP:GTIOS

After the device receives the command **AT+GTRTO** to get all the IO ports status, it will send the status to the backend server by the message **+RESP:GTIOS**.

#### ➤ +RESP:GTIOS,

##### Example:

**+RESP:GTIOS,ED0101,862170019025640,,0,1200,1300,00,00,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
IO Mode	1	0-F	
Analog Input VCC1	<=4	0 – 32000 mV	
Reserved			
Digital Input	2	00 – 1F	
Digital Output	2	00 – 0F	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.3.3.9. +RESP:GTTMZ

After the device receives the command **AT+GTRTO** to get the time zone settings, it will send the time zone information by the message **+RESP:GTTMZ** to the backend server.

#### ➤ +RESP:GTTMZ,

Example: +RESP:GTTMZ,ED0101,862170019025640,,+0800,0,20090214093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Time Zone Offset	5	±HHMM	
Daylight Saving	1	0 1	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.3.3.10. +RESP:GTAIF

After the device receives the command **AT+GTRTO** to get the **AIF**, it will send the information by the message **+RESP:GTAIF** to the backend server. The **+RESP:GTAIF** does not support the HEX report.

#### ➤ +RESP:GTAIF,

Example: +RESP:GTAIF,ED0101,862170019025640,,,ctnet@mynet.cn,vnet.mobi,,,,,20,0,0358,10.194.113.168,211.138.180.2,211.136.17.108,,,,,20140511093254,0181\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
APN	<=40		
APN User Name	<=30		
APN Password	<=30		

Backup APN	<=40		
Backup APN User Name	<=30		
Backup APN Password	<=30		
ICCID	20		
CSQ RSSI	<=2	0 – 31	
CSQ FER	<=2	0 – 7	
Cell ID	0 4 8		
IP addr	<=15	0.0.0.0	
Reserved			
Reserved			
Reserved			
Reserved			
Reserved			
Network Type	1	0,,2	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <CSQ RSSI>: The signal strength level.

CSQ RSSI	Signal Strength (dBm)
0	<-133
1	-111
2 – 30	-109 – -53
31	>-51

✧ <CSQ FER>: The quality of the network signal. The range is 0-7.

✧ <Cell ID>: Cell ID in hex format.

✧ <IP addr>: The IP address of the device.

✧ <Network Type>: Type of current registered mobile network.

- 0: 2G
- 2: LTE-4G/CAT-M1/NB1
- other: Unregistered.

### 3.3.3.11. +RESP:GTALS

After the device receives the command **AT+GTRTO** to get sub AT command configuration information, it will send the configuration information to the backend server by the message **+RESP:GTALS**. Different AT Command gets different configuration information. For example, to

get FRI configuration: **AT+GTRTO=gv600m,2,FRI,,,,,0015\$**

➤ **+RESP:GTALS,**

<b>Example:</b> <b>+RESP:GTALS,ED0101,862170019025640,gv600m,FRI,1,0,,0,0000,0000,,30,1000,1000,,40,60,00000000,,,,20140511093254,00C3\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' ' ' '_'	
Sub AT Command	3	'a' – 'z' 'A' – 'Z' ' '	
Mode	1	0 – 4	
Discard No Fix	<=2	0 1	
Reserved	0		
Period Enable	1	0 1	
Start Time	4	HHMM	
End Time	4	HHMM	
Reserved	0		
Send Interval	<=5	5 – 86400sec	
Distance	<=5	50 – 65535m	
Mileage	<=5	50 – 65535m	
Reserved	0		
Corner Report	<=3	0 – 180	
IGF Report Interval	<=5	0 5-86400sec	
ERI Mask	8	00000000-FFFFFFFF	00000000
Reserved	0		
Reserved	0		
Reserved	0		
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

### 3.3.3.12. +RESP:GTGSV

After the device receives the command AT+GTRTO to get the satellites information, it will send the satellites information by the message +RESP: GTGSV to the backend server.

#### ➤ +RESP:GTGSV,

Example:

+RESP:GTGSV,ED0101,862170019025640,,11,30,24,31,30,32,28,32,29,12,0,14,17,16,18,20,0,22,24,24,0,25,0,20140511093254,000F\$

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device name	20		
SV count	2	0-16	
SV id	2	> =0	
SV power	2	> =0	
.....			
SV id	2	> =0	
SV power	2	> =0	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <SV count>: Number of satellites the GPS found.
- ✧ <SV id>: Satellite id, when no satellites, zero used as special number to fill.
- ✧ <SV power>: Satellite power, when no satellites, zero used as special number to fill.

### 3.3.4. Event Report

The following event reports are triggered when certain events occur

**+RESP:GTPNA:** Power on report

**+RESP:GTPFA:** Power off report

**+RESP:GTMPN:** The report for connecting main power supply

**+RESP:GTMPF:** The report for disconnecting main power supply

**+RESP:GTBTC:** Backup battery starts charging report

**+RESP:GTSTC:** Backup battery stops charging report

**+RESP:GTBPL:** Backup battery low

- +RESP:GTSTT:** Device motion state indication when the motion state is changed
- +RESP:GTPDP:** GPRS connection establishment report
- +RESP:GTIGN:** Ignition on report
- +RESP:GTIGF:** Ignition off report
- +RESP:GTIDN:** Enter into idling status
- +RESP:GTIDF:** Leave idling status
- +RESP:GTGPI:** GPS jamming status
- +RESP:GTGSM:** The report for the information of the serving cell and the neighbor cells, this report does not support the HEX format
- +RESP:GTGSS:** GPS signal status
- +RESP:GTSTR:** Vehicle enters into start status
- +RESP:GTSTP:** Vehicle enters into stop status
- +RESP:GTLSP:** Vehicle enters into long stop status.
- +RESP:GTFLA:** Unusual fuel consumption alarm
- +RESP:GTDOS:** Output status change with waveform 1
- +RESP:GTTMP:** Temperature alarm
- +RESP:GTRMD:** The report for entering or leaving GSM roaming state
- +RESP:GTUPC:** Reporting information about UPC
- +RESP: GTVGN:** Ignition on report
- +RESP: GTVGF:** Ignition off report
- +RESP:GTEXP:** Reporting malfunction information of digital fuel sensor

In **+RESP:GTMPN**, **+RESP:GTMPF**, **+RESP:GTBTC**, **+RESP:GTSTC**, **+RESP:GTBPL**, **+RESP:GTSTT**, **+RESP:GTIGN**, **+RESP:GTIGF**, **+RESP:GTVGN**, **+RESP:GTVGF**, **+RESP:GTIDN**, **+RESP:GTIDF**, **+RESP:GTGSS**, **+RESP:GTSTR**, **+RESP:GTSTP**, **+RESP:GTLSP**, **+RESP:GTFLA**, **+RESP:GTDOS** and **+RESP:GTTMP** event reports, the last known GPS information and the current network information are included.

- **+RESP:GTPNA**,
- **+RESP:GTPFA**,
- **+RESP:GTPDP**,

**Example:**

```
+RESP:GTPNA,ED0101,862170019025640,,20140511093254,11F0$
+RESP:GTPFA,ED0101,862170019025640,,20140511093254,11F0$
+RESP:GTPDP,ED0101,862170019025640,,20150911093254,11F0$
```

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Send Time	0 14	YYYYMMDDHHMMSS	

Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- +RESP:GTMPN,
- +RESP:GTMPF,
- +RESP:GTBTC,

**Example:**

```
+RESP:GTMPN,ED0101,862170019025640,,0,4.3,92,70.0,121.354335,31.222073,20140511093
254,0460,0003,36100010,014B,00,20140511093254,11F0$
+RESP:GTMPF,ED0101,862170019025640,,0,4.3,92,70.0,121.354335,31.222073,201405110932
54,0460,0003,36100010,014B,00,20140511093254,11F0$
+RESP:GTBTC,ED0101,862170019025640,,0,4.3,92,70.0,121.354335,31.222073,2014051109325
4,0460,0003,36100010,014B,00,20140511093254,11F0$
```

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$



➤ **+RESP:GTGPJ,****Example:**
**+RESP:GTGPJ,ED0101,862170019025640,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
CW Jamming Value	1	0-255	
GPS Jamming State	1	0-3	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ &lt;CW Jamming Value&gt;: Current continuous wave jamming value.

✧ &lt;GPS Jamming State&gt;: Current jamming state.

- 0: Unknown or feature disabled.
- 1: (Ok) no significant jamming.
- 2: (Warning) interference visible but fixing OK.
- 3: (Critical) interference visible and no fix.

➤ **+RESP:GTSTC,****Example:**
**+RESP:GTSTC,ED0101,862170019025640,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Reserved	0		
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

➤ **+RESP:GTBPL,****Example:**
**+RESP:GTBPL,ED0101,862170019025640,,3.53,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	

Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Backup Battery VCC	<=4	0.00 – 4.50 V	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

➤ **+RESP:GTSTT,****Example:**

**+RESP:GTSTT,ED0101,862170019025640,,16,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
State	2	11 12 21 22 41 42 16	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	

Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <State>: The current movement state of the device.

- 16 (Tow): The device attached vehicle is ignition off and it is towed.
- 11 (Ignition Off Rest): The device attached vehicle is ignition off and it is motionless.
- 12 (Ignition Off Motion): The device attached vehicle is ignition off and it has been moving before it is regarded as being towed.
- 21 (Ignition On Rest): The device attached vehicle is ignition on and it is motionless.
- 22 (Ignition On Motion): The device attached vehicle is ignition on and it is moving.
- 41 (Sensor Rest): The device attached vehicle is motionless without ignition signal detected.
- 42 (Sensor Motion): The device attached vehicle is moving without ignition signal detected.

➤ +RESP:GTIGN, +RESP:GTVGN,

**Example:**

**+RESP:GTIGN,ED0101,862170019025640,,1200,0,4,3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00, 12345:12:34,2000.0,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Duration of Ignition Off	<=6	0 – 999999 sec	
GPS Accuracy	<=2	0	0, Last known

Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Hour Meter Count	11	HHHHH:MM:SS	
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ *<Duration of Ignition Off>*: Duration since last time when the ignition is off. If it is greater than 999999 seconds, report 999999 seconds.
- ✧ *<Hour Meter Count>*: If hour meter counter function is enabled by the command **AT+GTHMC**, total hours counted when engine is on will be reported in this field. If the function is disabled, this field will be reserved. It is formatted with 5 hour digits and 2 minute digits and 2 second digits and ranges from 00000:00:00–99999:00:00.

➤ **+RESP:GTIGF, +RESP:GTVGF**

<b>Example:</b> <b>+RESP:GTIGF,ED0101,862170019025640,,1200,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00, 12345:12:34,2000.0,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Duration of Ignition On	<=6	0 – 999999 sec	

GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Hour Meter Count	11	HHHHH:MM:SS	
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ *<Duration of Ignition On>*: Duration since last time when the ignition is on. If it is greater than 999999 seconds, report 999999 seconds.
- ✧ *<Hour Meter Count>*: If hour meter counter function is enabled by the command **AT+GTHMC**, total hours counted when engine is on will be reported in this field. If the function is disabled, this field will be filled with '00'. It is formatted with 5 hour digits and 2 minute digits and 2 second digits and ranges from 00000:00:00–99999:00:00.

➤ **+RESP:GTIDN,**

**Example:**

**+RESP:GTIDN,ED0101,862170019025640,,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	

Reserved	0		
Reserved	0		
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

➤ **+RESP:GTIDF,****Example:**

**+RESP:GTIDF,ED0101,862170019025640,,22,300,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Motion State	2	11 12 16 22	
Duration of Idling Status	<=6	0 – 999999 sec	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	

Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Motion State>: The current motion state when the vehicle exits idling status.
- ✧ <Duration of Idling Status>: The time that the vehicle has been in idling status. If it is greater than 999999 seconds, report 999999 seconds.

➤ **+RESP:GTGSM**

**Example:**

**+RESP:GTGSM,ED0101,862170019025640,FRI,0460,0000,1878,0871,20,,0460,0000,1878,0152,16,,,,,,,,,,,,,0460,0000,1878,0873,57,00,20090214093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A'-'Z','0'-'9'}	
Unique ID	15	IMEI	
Fix Type	3	SOS RTL LBC TOW FRI GIR  ERI	
MCC1	4	0XXX	
MNC1	4	0XXX	
LAC1	4		
Cell ID1	0 4 8		
RX Level1	2	0-91	



Reserved	0		
MCC2	4	0XXX	
MNC2	4	0XXX	
LAC2	4		
Cell ID2	0 4 8		
RX Level2	2	0-91	
Reserved	0		
MCC3	4	0XXX	
MNC3	4	0XXX	
LAC3	4		
Cell ID3	0 4 8		
RX Level3	2	0-91	
Reserved	0		
MCC4	4	0XXX	
MNC4	4	0XXX	
LAC4	4		
Cell ID4	0 4 8		
RX Level4	2	0-91	
Reserved	0		
MCC5	4	0XXX	
MNC5	4	0XXX	
LAC5	4		
Cell ID5	0 4 8		
RX Level5	2	0-91	
Reserved	0		
MCC6	4	0XXX	
MNC6	4	0XXX	
LAC6	4		
Cell ID6	0 4 8		
RX Level6	2	0-91	

Reserved	0		
MCC	4	0XXX	
MNC	4	0XXX	
LAC	4		
Cell ID	0 4 8		
RX Level	2	0-91	
Reserved	2	00	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ **<Fix Type>**: A string to indicate the type of GPS fixing this cell information is for.
  - "SOS": This cell information is for SOS requirement.
  - "RTL": This cell information is for RTL requirement.
  - "LBC": This cell information is for LBC requirement.
  - "TOW": This cell information is for TOW requirement.
  - "FRI": This cell information is for FRI requirement.
  - "GIR": This cell information is for sub command "C" in **AT+GTRTO** command.
  - "ERI": This cell information is for ERI requirement.
- ✧ **<MCC(i)>**: MCC of the neighbor cell *i* (*i* is the index of the neighbor cell).
- ✧ **<MNC(i)>**: MNC of the neighbor cell *i*.
- ✧ **<LAC(i)>**: LAC in hex format of the neighbor cell *i*.
- ✧ **<Cell ID(i)>**: Cell ID in hex format of the neighbor cell *i*.
- ✧ **<RX Level(i)>**: The signal strength of the neighbor cell *i*. This parameter is of 6-bit.
- ✧ **<MCC>**: MCC of the serving cell.
- ✧ **<MNC>**: MNC of the serving cell.
- ✧ **<LAC>**: LAC in hex format of the serving cell.
- ✧ **<Cell ID>**: Cell ID in hex format of the serving cell.
- ✧ **<RX Level>**: The signal strength of the serving cell.

**Note:**

- It may include information of several neighbor cells. If no neighbor cell is found, all the fields of the neighbor cell will be empty.
- "ffff" in the field of **<LAC(i)>**, **<Cell ID(i)>** means the terminal doesn't know the value.
- This message cannot be sent via SMS.

➤ **+RESP:GTGSS**

**Example:**

**+RESP:GTGSS,ED0101,862170019025640,,1,9,11,,0,4.3,92,70.0,121.354335,31.222073,201405**

11093254,0460,0003,36100010,014B,00,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
GPS Signal Status	1	0   1	
Satellite Number	2	0 - 24	
Device State	2	11 12 21 22 41 42 16	
Reserved	0		
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <GPS Signal Status>: 0 means GPS signal is lost or no successful GPS fix; 1 means GPS signal has recovered and GPS fix succeeded.
- ✧ <Satellite Number>: The number of the visible satellites when fix succeeded. If fix failed, the parameter is reserved.
- ✧ <Device State>: The current movement state of the device.
  - 16 (Tow): The device attached vehicle is ignition off and it is towed.
  - 11 (Ignition off Rest): The device attached vehicle is ignition off and it is motionless.

- 12 (Ignition off Motion): The device attached vehicle is ignition off and it has been moving before it is regarded as being towed.
- 21 (Ignition On Rest): The device attached vehicle is ignition on and it is motionless.
- 22 (Ignition On Motion): The device attached vehicle is ignition on and it is moving.
- 41 (Sensor Rest): The device attached vehicle is motionless without ignition signal detected.
- 42 (Sensor Motion): The device attached vehicle is moving without ignition signal detected.

➤ +RESP:GTSTR,

➤ +RESP:GTSTP,

➤ +RESP:GTLSP,

Example:

+RESP:GTSTR,ED0101,862170019025640,,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

+RESP:GTSTP,ED0101,862170019025640,,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

+RESP:GTLSP,ED0101,862170019025640,,,,0,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,20140511093254,11F0\$

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Reserved	0		
Reserved	0		
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	

Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Mileage	<=9	0.0 – 4294967.0 km	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

➤ **+RESP:GTFLA**

**Example:**  
**+RESP:GTFLA,ED0101,862170019025640,,2,92,70,0,4.3,92,70.0,121.354335,31.222073,20090214013254,0460,0000,18d8,6141,00,20090214093254,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Input ID	1	0 1	
Last Fuel Level	<=3	0 – 100	
Current Fuel Level	<=3	0 – 100	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	4	0XXX	
MNC	4	0XXX	
LAC	4	XXXX	
Cell ID	0 4 8	XXXX	
Reserved	2	00	00
Send Time	14	YYYYMMDDHHMMSS	

Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Input ID>: ID of the input to which the fuel sensor is connected. 0 means “Connected to serial port”.
- ✧ <Last Fuel Level>: The fuel level saved before last ignition off when FLA event occurs.
- ✧ <Current Fuel Level>: The fuel level when the FLA event occurs.

➤ **+RESP:GTDOS**

**Example:**  
**+RESP:GTDOS,ED0101,862170019025640,,1,0,0,4.3,92,117.201371,31.833041,2014051109325**  
**4,0460,0003,36100010,014B,00,20140511093254,0149\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Wave1 Output ID	1	1-4	
Wave1 Ouptut Active	1	0 1	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	

Tail Character	1	\$	\$
----------------	---	----	----

- ✧ <Wave1 Output ID>: ID of the output with waveform 1
- ✧ <Wave1 Output Active>: The output status with waveform 1

➤ **+RESP:GTTMP**

**Example:**

**+RESP:GTTMP,ED0101,862170019025640,,,0,01, ,0,0,0,0,39.0,117.201299,31.833024,20140511093254,0460,0000,5678,2D7E,00,0,0,,0,0,01,01,,,,28131A4103000056,,28,20140511093254,0028\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
External Power VCC	<=5	0 – 32000 mV	
External Power VCC2	<=5	0 – 32000 mV	
Report ID/Report Type	2	X(0-3)X(0-1)	
Number	1	0 – 1	
GPS Accuracy	<=2	0	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
Mileage	<=9	0.0 – 4294967.0 km	
Hour Meter Count	11	HHHHH:MM:SS	

Analog Input VCC1	<=5	0 – 32000 mV	
Reserved			
Digital Input	2	00 – 1F	
Digital Output	2	00 – 0F	
Reserved	0		
Reserved	0		
Reserved	0		
Temperature Sensor device ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	0		
Temperature Sensor device DATA	<=3	-55 – 125°C	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Report ID/Report Type>: The report ID and the type are in hex format. 4 high bits mean report ID and 4 low bits means report type.

Report ID: The ID of temperature sensor, the range is 0-7.

Report type: 0 means beyond the predefined temperature range. 1 means within the predefined temperature range.

✧ <Temperature Sensor device ID>: The ID of the temperature sensor.

✧ <Temperature Sensor device DATA>: The current temperature detected by the sensor.

#### ➤ +RESP:GTBST

##### Example:

+RESP:GTBST,ED0102,866425030804035,GV600M,0,0,10,1,0,0,0,0,47.3,114.022048,22.536162,20181106032116,0460,0000,27BD,122B,,1,DD330A001176,26,3183,20181106032554,0030\$

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' ' ' ' _ '	
External Power VCC	<=5	0 – 32000 mV	
External Power VCC2	<=5	0 – 32000 mV	



Report ID/Report Type	2	X(1-2)X(0)	
Number	1	0 – 1	
GPS Accuracy	<=2	0	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
BLE Sensor Num	<=2	0-10	
BIE Sensor1 MAC ID	12	'0' – '9' 'a' – 'f' 'A' – 'F'	
BLE Sensor1 Tem Data	<=3	-40 – 80℃	
BLE Sensor1 Voltage	4	0000-5000mv	
⋮	⋮	⋮	
BIE SensorN MAC ID	12	'0' – '9' 'a' – 'f' 'A' – 'F'	
BLE SensorN Tem Data	<=3	-40 – 80℃	
BLE SensorN Voltage	4	0000-5000mv	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ <Report ID/Report Type>: The report ID and the type are in hex format. 4 high bits mean report ID and 4 low bits means report type.  
Report ID: 1 (the <Mode> of **AT+GTBTE** is 1)  
Report Type: 0 (by default)
- ✧ <BLE Sensor Num>: The total number of BLE sensors. Every BLE sensor corresponds to a group data. Each group data includes <BLE Sensor MAC ID>, <BLE Sensor Tem Data> and <BLE Sensor Voltage>. Maximum 10 sensors are supported.

- ✧ <BLE Sensor MAC ID>: MAC address of BLE sensor.
- ✧ <BLE Sensor Tem Data>: Current temperature of BLE sensor.
- ✧ <BLE Sensor Voltage>: Current voltage of BLE sensor.
- ✧ < : >: This symbol means that the BLE sensor data group is variable. For example, if the <BLE Sensor Num> is 3, there are 3 group data following the <BLE Sensor Num> field.

➤ **+RESP:GTBTA**

<b>Example:</b> <b>+RESP:GTBTA,ED0102,866425030804035,GV600M,0,0,11,1,0,0,0,0,47.3,114.022048,22.536162,20181106032116,0460,0000,27BD,122B,,DD330A001176,26,3183,20181106032554,0031\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
External Power VCC	<=5	0 – 32000 mV	
External Power VCC2	<=5	0 – 32000 mV	
Report ID/Report Type	2	X(1-2)X(0-2)	
Number	1	0 – 1	
GPS Accuracy	<=2	0	
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	
MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	
BIE Sensor MAC ID	16	'0' – '9' 'a' – 'f' 'A' – 'F'	
BLE Sensor Tem DATA	<=3	-55 – 125℃	

BLE Sensor Voltage	4		
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ *<Report ID/Report Type>*: The report ID and the type are in hex format. 4 high bits mean report ID and 4 low bits means report type.

Report ID: 1 (the *<Mode>* of **AT+GTBTE** is 1)

Report type: 0 (voltage low)/1 (temperature outside the range)

✧ *< BLE Sensor MAC ID >*: MAC address of BLE sensor, for example: 112233445566.

✧ *< BLE Sensor Tmp Data >*: Current temperature of BLE sensor.

✧ *< BLE Sensor Voltage >*: Current voltage of BLE sensor.

➤ **+RESP:GTRMD,**

**Example:**

**+RESP:GTRMD,ED0101,862170019025640,,1,0,0,0,0,83.9,117.201281,31.833017,20130917071326,0460,0000,5678,2079,00,20130917071330,00A4\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Roaming State	1	0-3	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	4	0XXX	
MNC	4	0XXX	
LAC	4	XXXX	
Cell ID	0 4 8	XXXX	

Reserved	2	00	00
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ **<Roaming State>**: A numeral to indicate the roaming state.

- 0: Home
- 1: Known roaming
- 2: Unknown roaming
- 3: Blocking report

➤ **+RESP:GTEXP,**

This report is used for reporting the malfunction information of digital fuel sensor.

<b>Example:</b> <b>+RESP:GTEXP,ED2001,135790246811220,,2,,0,0004,0,0,0,0,74.1,117.201527,31.832957,20160510012210,0460,0000,5665,47A1,00,20160510012212,0063\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000–XXXXXX, X ∈ {'A'–'Z', '0'–'9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Digital Fuel Sensor Type	1	2/4	
Reserved			
Reserved			
HW Fault Code	4	0 – FFFF	
GPS Accuracy	<=2	0/1 – 50	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(–)xxxxx.x m	
Longitude	<=11	(–)xxx.xxxxxx	
Latitude	<=10	(–)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	4	0XXX	

MNC	4	0XXX	
LAC	4	XXXX	
Cell ID	0/4/8	XXXXXXXX	
Reserved	2	00	00
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Digital Fuel Sensor Type>: For details, please refer to <Digital Fuel Sensor Type> in **AT+GTURT**.

✧ <HW Fault Code>: The malfunction code has different meanings for different digital fuel sensors.

UFSxxx:

- Bit 0: The detector of the fuel sensor is not connected or the signal extension cable is broken.
- Bit 1: The detector of the fuel sensor is detached from the fuel tank.
- Bit 2: The input power supply is too low.
- Bit 3: Abnormal reset of the system.
- Bit 4: The value of analog output is abnormal.
- Bit 5: The current fuel level is in the blind zone.
- Bit 6 - 15: Reserved.

➤ **+RESP:GTUFS:**

Example:			
+RESP:GTUFS,ED2001,862170019025640,,100,,20150201000000,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Reserved			
Result	3	100 101 102 103 200 201  202 300 301 302	
Reserved			
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ **<Result>**: A numeral to indicate whether the configuration is updated successfully.

- 100: The update command is starting.
- 101: The update command is confirmed by the device.
- 102: The update command is refused by the device.
- 103: The update process is refused because the battery is low.
- 200: The device starts to download the package.
- 201: The device finishes downloading the package successfully.
- 202: The device fails to download the package.
- 300: The device starts to update the device configuration.
- 301: The device finishes updating the device configuration successfully.
- 302: The device fails to update the device configuration.

➤ **+RESP:GTUPC:**

**Example:**

**+RESP:GTUPC,ED0101,862170019025640,,1,http://www.queclink.com/configure.ini,20150201000000,11F0\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z'	
Command ID	<=3		
Result	3	100 101 102 103 200 201  202 300 301 302	
Download URL	<=100	Complete URL	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ **<Command ID>**: The command ID in the update configuration file. It is always 0 before the device starts to update the configuration. It is the total number of the commands when the response code is 301. It is wrong format of command ID when the response code is 302.

✧ **<Result>**: A numeral to indicate whether the configuration is updated successfully.

- 100: The update command is starting.
- 101: The update command is confirmed by the device.
- 102: The update command is refused by the device.
- 103: The update process is refused because the battery is low.
- 200: The device starts to download the package.

- 201: The device finishes downloading the package successfully.
- 202: The device fails to download the package.
- 300: The device starts to update the device configuration.
- 301: The device finishes updating the device configuration successfully.
- 302: The device fails to update the device configuration.

✧ <Download URL>: The complete URL to download the configuration. It includes the file name.

### 3.3.5. Data Report

The following report will be triggered when certain data needs to be sent.

#### ➤ +RESP:GTFSD,

This report is used for reporting fuel sensor data.

Example:			
+RESP:GTFSD,ED2001,862170016790444,,39,*QL,407D,01,00000,0132,0014,00000,0229#,,,,,20141021021206,0018\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF,X ∈ {'A' – 'Z','0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Data Length	2		
Sensor Data	<=128	ASCII Code	
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Characters	1	\$	\$

✧ <Data Length>: The length of <Sensor Data>.

✧ <Sensor Data>: The fuel data from fuel sensor. It starts with '\*QL' and ends with '#'.

### 3.3.6. Buffer Report

If the buffer report function is enabled by command **AT+GTSRI**, the terminal will save the messages in a local buffer when the following occurs.

- ✧ No network signal.
- ✧ Failed to activate network context for the TCP or UDP connection.

✧ Network Failed to establish the TCP connection with the backend server.

These messages will be sent to the backend server when connection to the server recovers. The buffer reports are saved to the built-in non-volatile memory in case the device is reset. The terminal can buffer up to 10000 messages.

Detailed information about buffer report is listed below.

- ✧ Only **+RESP** messages are buffered.
- ✧ In the buffer report, the original header string “**+RESP**” is replaced by “**+BUFF**”. Other contents such as the original sending time and count number will be kept the same.
- ✧ Buffered messages will be sent only via network by TCP or UDP protocol. They cannot be sent via SMS. If the current report mode is Force on SMS, the buffered messages will not be sent until the report mode is changed to TCP or UDP.
- ✧ The buffered messages will be sent after other normal messages if *<Buffer Mode>* in **AT+GTSRI** is set to 1.
- ✧ The buffered messages will be sent before other normal messages if *<Buffer Mode>* in **AT+GTSRI** is set to 2. The SOS message has the highest priority and is sent before the buffered messages.

#### Example:

The following is an example of the buffered message:

```
+BUFF:GTFRI,ED0101,862170019025640,,,00,,1,4.3,92,70.0,121.354335,31.222073,20140511093254,0460,0003,36100010,014B,00,2000.0,12345:12:34,,,80,210100,,,,,20140511093254,11F0$
```

### 3.3.7. Transparent Data Transmission

The device supports transparent transfer between the backend server and the peripheral device connected to its second serial port. GV600M supports bi-directional data transmission. In both directions, the data is transmitted to the device via transparent transfer.

a) Transfer data from the peripheral device to the backend server

According to the *<working mode>* of the command **AT+GTMUT**, there are two ways for the peripheral device communicates with GV600M.

If the peripheral device supports **AT+GTDAT** command, it can transfer data via this command. The peripheral device can send command **AT+GTDAT** with the data to the serial port. According to the *<Command Type>* of **AT+GTDAT**, The device wraps the corresponding data format into backend server with **+RESP: GTDAT** message either in short format or in long format.

b) Transfer data from the backend server to the peripheral device

If the backend server needs to send data to the peripheral device, it can send command **AT+GTDAT** with the data to GV600M and GV600M will pick out the pure data and send it to the second serial port. In this way the peripheral device can get the data from the serial port.

Data to the backend server

➤ **+RESP:GTDAT (Short Format),**

#### Example:

```
+RESP:GTDAT,ED0101,862170019025640,,data,20140511093254,0017$
```



Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Data to the Backend Server	<=1280	ASCII Code	
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

➤ **+RESP:GTDAT (Long Format)**

**Example:**

**+RESP:GTDAT,ED0101,862170019025640,,3,,,1645026150,0,0.5,0,29.4,121.390923,31.164295,20111222022935,0460,0003,36100010,014B,00,,,,,20140511093254,001A\$**

Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXFFFF, $X \in \{'A' - 'Z', '0' - '9'\}$	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Report Type	1	0 1 2	
Reserved	0		
Reserved	0		
Data to the Backend Server	<=1280	ASCII Code	
GPS Accuracy	<=2	0	0, Last known
Speed	<=5	0.0 – 999.9 km/h	
Azimuth	<=3	0 – 359	
Altitude	<=8	(-)xxxxx.x m	
Longitude	<=11	(-)xxx.xxxxxx	
Latitude	<=10	(-)xx.xxxxxx	
GPS UTC Time	14	YYYYMMDDHHMMSS	
MCC	0 4	0XXX	

MNC	0 4	0XXX	
LAC	0 4	XXXX	
Cell ID	0 4 8	XXXXXXXX	
Reserved	0 2	00	00
Reserved	0		
Reserved	0		
Reserved	0		
Reserved	0		
Send Time	0 14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <Report Type>: The value of <Report Type> refers to <Working Mode> of **AT+GTMUT**.

- 0: Disable the second serial port.
- 1: AT+GTDAT.
- 2: Reserve.

Data to the second serial port starts with a new line and ends with '\r\n'.

**Example:**

**Data to the serial port**

### 3.3.8. Report Google Maps Hyperlink

According to the setting of the command **AT+GTGLM** or SMS position request message via SMS, the device can send a SMS with Google Maps hyperlink to a mobile phone.

If the device receives SMS position request message via SMS, GV600M will send its current position to the original number via SMS with a Google Maps hyperlink if the original number is a direct number (please refer to <Direct Number List> in the Chapter 3.2.7.6) or a number in the white list (please refer to <White List> in the Chapter 3.2.7.5)

GV600M will send an SMS with a Google Maps hyperlink to the direct phone numbers after the messages +RESP:GTSOS and +RESP:GTGIN/+RESP:GTGOT.

#### ➤ Google Maps Hyperlink

**Example:**

**LBC:gv600m**

**<http://maps.google.com/maps?q=31.222073,121.354335>**

F1 D2009/01/01 T00:00:00 B0% I1 S0.0			
Parameter	Length (Byte)	Range/Format	Default
SMS Header	<=30	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' ' ' '_'	
Google Maps Hyperlink Header	30	http://maps.google.com/maps?q=	http://maps.google.com/maps?q=
Latitude	<=10	(-)xx.xxxxxx	
Longitude	<=11	(-)xxx.xxxxxx	
GPS Fix	<=3	F0 F1	
GPS UTC Time	20	DYYYY/MM/DDTHH:MM:SS	
Battery Percentage	<=6	B0%-B100%	
Ignition Status	2	I0 I1	
Speed	<=6	S0.0 – S999.9 km/h	

- ✧ <SMS Header>: A string that includes the terminal name and GPS fix type ("SOS", "IN GEO-i", "OUT GEO-i", "LBC").
- ✧ <Google Maps Hyperlink>: A string of a Google Maps hyperlink.
- ✧ <GPS Fix>: The accuracy of the location information. F0 means no GPS fix.
- ✧ <Battery Percentage>: The percentage of the backup battery.
- ✧ <Ignition Status>: The status of ignition. 0 means ignition off and 1 means ignition on.
- ✧ <Speed>: The current speed. Unit: km/h.

### 3.4. Heartbeat

Heartbeat is used to maintain the contact between the device and the backend server via network. The heartbeat package is sent to the backend server at the interval defined by *<Heartbeat Interval>* in **AT+GTSRI** command.

#### ➤ +ACK:GTHBD

Example: +ACK:GTHBD,ED0101,862170019025640,,20140511093254,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

Whenever the backend server receives a heartbeat package, it should reply an acknowledgement to the device.

#### ➤ +SACK:GTHBD

Example: +SACK:GTHBD,ED0101,11F0\$ +SACK:GTHBD,,11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ *<Protocol Version>*: The device type and the protocol version that the backend server supports. This field is optional. The backend server can send an empty field to decrease the length of the heartbeat data acknowledgement.
- ✧ *<Count Number>*: Extracted from the heartbeat package from the device as the *<Count Number>* of the server acknowledgement of the heartbeat.

### 3.5. Server Acknowledgement

If server acknowledgement is enabled by **AT+GTSRI** command, the backend server will reply to the device whenever it receives a message from the device.

➤ **+SACK:**

Example: +SACK:11F0\$			
Parameter	Length (Byte)	Range/Format	Default
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

- ✧ *<Count Number>*: The backend server uses the *<Count Number>* extracted from the received message as the *<Count Number>* in the server acknowledgement.

## 4. HEX Format Report Message

From this version, the @Tracker protocol supports messages in HEX format. For all the commands, they still use the ASCII format as described above. By default the device uses ASCII format messages. The backend server could use **AT+GTQSS** or **AT+GTSRI** command to enable the HEX format messages by setting the *<Protocol Format>* to 1.

All the messages are sorted into 5 categories (acknowledgement to command (**+ACK**), location report (**+RSP**), event report (**+EVT**), information report (**+INF**) and the heartbeat packet data (**+HBD**)). Reports of the same category have the same header string.

The composition of the HEX message could be customized by **AT+GTHRM** command. The actual length of each HEX report depends on the setting of the masks in **AT+GTHRM**.

The device uses CRC-CCITT (0xFFFF) method to calculate the checksum of the report data and appends the checksum to the end of the data. The backend server could use this checksum to verify the integrity of the received data.

At the end of each HEX message, the device uses 0x0D and 0x0A as the end.

The HEX messages are transmitted in network byte order (big-endian).

#### 4.1. Hex Report Mask

AT+GTHRM command uses <+ACK Mask>, <+RSP Mask>, <+EVT Mask>, <+INF Mask> and <+HBD Mask> to control the composition of the corresponding HEX message. In each HEX message, the corresponding mask for the report is included to indicate which part is reported.

##### ➤ AT+GTHRM=

Example: AT+GTHRM=gv600m,,,7F,FFFFFF,FFFFFF,2F7F,FF,,7F,,,0018\$			
Parameter	Length (Byte)	Range/Format	Default
Password	4 – 7	'0' – '9' 'a' – 'z' 'A' – 'Z'	gv600m
Reserved	0		
Reserved	0		
+ACK Mask	2	00 – FF	7F
+RSP Mask	8	00000000 – FFFFFFFF	FFFFFF
+EVT Mask	8	00000000 – FFFFFFFF	FFFFFF
+INF Mask	<=8	00000000 – FFFFFFFF	2F7F
+HBD Mask	2	00 – FF	FF
+DAT Mask	<=8	00000000 – FFFFFFFF	7F
Reserved	4	0000–FFFF	7F
Reserved	0	00000000 – FFFFFFFF	7FF
Reserved	0		
Serial Number	4	0000 – FFFF	
Tail Character	1	\$	\$

✧ <+ACK Mask>: Component mask of the acknowledgement received.

Bit	Item to Mask
Bit 7	Reserved
Bit 6	<Count Number>
Bit 5	<Send Time>
Bit 4	<Device Name>
Bit 3	<Firmware Version>

<b>Bit 2</b>	<i>&lt;Protocol Version&gt;</i>
<b>Bit 1</b>	<i>&lt;Device Type&gt;</i>
<b>Bit 0</b>	<i>&lt;Length&gt;</i>

✧ *<+RSP Mask>*: Component mask of the location message.

<b>Bit</b>	<b>Item to Mask</b>
<b>Bit 31</b>	Reserved
<b>Bit 30</b>	Reserved
<b>Bit 29</b>	Reserved
<b>Bit 28</b>	Reserved
<b>Bit 27</b>	Reserved
<b>Bit 26</b>	Reserved
<b>Bit 25</b>	Reserved
<b>Bit 24</b>	Reserved
<b>Bit 23</b>	<i>&lt;Total Hour Meter Count&gt;</i>
<b>Bit 22</b>	<i>&lt;Current Hour Meter Count&gt;</i>
<b>Bit 21</b>	<i>&lt;Total Mileage&gt;</i>
<b>Bit 20</b>	<i>&lt;Current Mileage&gt;</i>
<b>Bit 19</b>	<i>&lt;GPS Satellites Information&gt;</i>
<b>Bit 18</b>	<i>&lt;Motion Status&gt;</i>
<b>Bit 17</b>	<i>&lt;Digital IO Status&gt;</i>
<b>Bit 16</b>	Reserved
<b>Bit 15</b>	<i>&lt;External Power Supply2 Voltage&gt;</i>
<b>Bit 14</b>	<i>&lt;Analog Input1 Voltage&gt;</i>
<b>Bit 13</b>	<i>&lt;Analog Input Mode&gt;</i>
<b>Bit 12</b>	<i>&lt;External Power Supply Voltage&gt;</i>
<b>Bit 11</b>	<i>&lt;Battery Level&gt;</i>
<b>Bit 10</b>	<i>&lt;Firmware Version&gt;</i>
<b>Bit 9</b>	<i>&lt;Protocol Version&gt;</i>
<b>Bit 8</b>	<i>&lt;Device Type&gt;</i>
<b>Bit 7</b>	<i>&lt;Length&gt;</i>



<b>Bit 6</b>	<i>&lt;Device Name&gt;</i>
<b>Bit 5</b>	<i>&lt;Count Number&gt;</i>
<b>Bit 4</b>	<i>&lt;Send Time&gt;</i>
<b>Bit 3</b>	<i>&lt;network data&gt;</i>
<b>Bit 2</b>	<i>&lt;Altitude&gt;</i>
<b>Bit 1</b>	<i>&lt;Azimuth&gt;</i>
<b>Bit 0</b>	<i>&lt;Speed&gt;</i>

✧ *<+EVT Mask>*: Component mask of the event message.

<b>Bit</b>	<b>Item to Mask</b>
<b>Bit 31</b>	Reserved
<b>Bit 30</b>	Reserved
<b>Bit 29</b>	Reserved
<b>Bit 28</b>	Reserved
<b>Bit 27</b>	Reserved
<b>Bit 26</b>	Reserved
<b>Bit 25</b>	Reserved
<b>Bit 24</b>	Reserved
<b>Bit 23</b>	<i>&lt;Total Hour Meter Count&gt;</i>
<b>Bit 22</b>	<i>&lt;Current Hour Meter Count&gt;</i>
<b>Bit 21</b>	<i>&lt;Total Mileage&gt;</i>
<b>Bit 20</b>	<i>&lt;Current Mileage&gt;</i>
<b>Bit 19</b>	<i>&lt;GPS Satellites Information&gt;</i>
<b>Bit 18</b>	<i>&lt;Motion Status&gt;</i>
<b>Bit 17</b>	<i>&lt;Digital IO Status&gt;</i>
<b>Bit 16</b>	Reserved
<b>Bit 15</b>	<i>&lt;External Power Supply2 Voltage&gt;</i>
<b>Bit 14</b>	<i>&lt;Analog Input1 Voltage&gt;</i>
<b>Bit 13</b>	<i>&lt;Analog Input Mode&gt;</i>
<b>Bit 12</b>	<i>&lt;External Power Supply Voltage&gt;</i>

<b>Bit 11</b>	<Battery Level>
<b>Bit 10</b>	<Firmware Version>
<b>Bit 9</b>	<Protocol Version>
<b>Bit 8</b>	<Device Type>
<b>Bit 7</b>	<Length>
<b>Bit 6</b>	<Device Name>
<b>Bit 5</b>	<Count Number>
<b>Bit 4</b>	<Send Time>
<b>Bit 3</b>	<network data>
<b>Bit 2</b>	<Altitude>
<b>Bit 1</b>	<Azimuth>
<b>Bit 0</b>	<Speed>

- ✧ <+INF Mask>: Component mask of the information message. Bit 8 to Bit 15 indicate which group of items is included when sending messages other than **+RESP:GTINF**.

<b>Bit</b>	<b>Item to Mask</b>
<b>Bit 15</b>	Reserved
<b>Bit 14</b>	<b>+RESP:GTTMZ</b>
<b>Bit 13</b>	<b>+RESP:GTCSQ</b>
<b>Bit 12</b>	<b>+RESP:GTCID</b>
<b>Bit 11</b>	<b>+RESP:GTBAT</b>
<b>Bit 10</b>	<b>+RESP:GTGPS</b>
<b>Bit 9</b>	<b>+RESP:GTIOS</b>
<b>Bit 8</b>	<b>+RESP:GTVR</b>
<b>Bit 7</b>	Expand INF Mask
<b>Bit 6</b>	<Count Number>
<b>Bit 5</b>	<Send Time>
<b>Bit 4</b>	<Firmware Version>
<b>Bit 3</b>	<Protocol Version>
<b>Bit 2</b>	<Device Type>
<b>Bit 1</b>	<Device Name>

<b>Bit 0</b>	<Length>
--------------	----------

- ✧ <Expand INF Mask>: Component mask of the information message. Bit 0 to Bit 15 indicate which group of items is included when sending messages other than **+RESP: GTINF**.

Bit	Item to Mask
Bit 15	Reserved
Bit 14	Reserved
Bit 13	Reserved
Bit 12	Reserved
Bit 11	Reserved
Bit 10	Reserved
Bit 9	Reserved
Bit 8	Reserved
Bit 7	Reserved
Bit 6	Reserved
Bit 5	Reserved
Bit 4	Reserved
Bit 3	Reserved
Bit 2	Reserved
Bit 1	Reserved
Bit 0	<b>+RESP:GTGSV</b>

- ✧ <+HBD Mask>: Component mask of the heartbeat data.

Bit	Item to Mask
Bit 7	<UID>
Bit 6	<Count Number>
Bit 5	<Send Time>
Bit 4	<Device Name>
Bit 3	<Firmware Version>
Bit 2	<Protocol Version>

<b>Bit 1</b>	<Device Type>
<b>Bit 0</b>	<Length>

✧ <+DAT Mask>: Component mask of data message.

Bit	Item to Mask
<b>Bit 31</b>	Reserved
<b>:</b>	Reserved
<b>Bit 7</b>	Reserved
<b>Bit 6</b>	<Count Number>
<b>Bit 5</b>	<Send Time>
<b>Bit 4</b>	<Device Name>
<b>Bit 3</b>	<Firmware Version>
<b>Bit 2</b>	<Protocol Version>
<b>Bit 1</b>	<Device Type>
<b>Bit 0</b>	<Length>

The acknowledgment message of **AT+GTHRM** command:

➤ **+ACK:GTHRM,**

Example: <b>+ACK:GTHRM,ED0101,862170019025640,,0019,20140511093254,11F0\$</b>			
Parameter	Length (Byte)	Range/Format	Default
Protocol Version	6	XX0000 – XXXFFF, X ∈ {'A' – 'Z', '0' – '9'}	
Unique ID	15	IMEI	
Device Name	<=20	'0' – '9' 'a' – 'z' 'A' – 'Z' '-' '_'	
Serial Number	4	0000 – FFFF	
Send Time	14	YYYYMMDDHHMMSS	
Count Number	4	0000 – FFFF	
Tail Character	1	\$	\$

## 4.2. Acknowledgement +ACK

➤ +ACK,

**Example:**

2B 41 43 4B 20 7F 24 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 13 07 DE 01 0D 09 1F 0B 00 2F  
CA D2 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+ACK	+ACK
Message Type	1		
Report Mask	1	00 – FF	
Length	1		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	0101
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
ID	1		
Serial Number	2	0000 – FFFF	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Message Type>: The ID of the command that the device received.

Command	ID
AT+GTBSI	0
AT+GTSRI	1
AT+GTQSS	2
Reserved	3
AT+GTCFG	4
AT+GTTOW	5
AT+GTEPS	6

AT+GTDIS	7
AT+GTOUT	8
AT+GTIOB	9
AT+GTTMA	10
AT+GTFRI	11
AT+GTGEO	12
AT+GTSPD	13
AT+GTSOS	14
Reserved	15
AT+GTRTO	16
Reserved	17
Reserved	18
Reserved	19
Reserved	20
AT+GTUPD	21
AT+GTPIN	22
AT+GTDAT	23
AT+GTOWH	24
AT+GTDOG	25
AT+GTAIS	26
Reserved	27
AT+GTIDL	28
Reserved	29
AT+GTHMC	30
Reserved	31
Reserved	32
Reserved	33
AT+GTWLT	34
AT+GTHRM	35
AT+GTFFC	36

Reserved	37
AT+GTSSR	38
Reserved	39
Reserved	40
AT+GTEFS	41
Reserved	42
AT+GTIDA	43
AT+GTACD	44
AT+GTPDS	45
Reserved	46
AT+GTBZA	47
AT+GTSPA	48
AT+GTMUT	49
Reserved	50
AT+GTTMP	51
AT+GTFSC	52
AT+GTRMD	53
AT+GTPEO	54
Reserved	55 - 64
AT+GTCMD	61
AT+GTUDF	62
AT+GTGPJ	65
AT+GTGAM	66
AT+GTOEX	Reserved
AT+GTIEX	Reserved
AT+GTUPC	70
AT+GTGLM	79
AT+GTBTE	88

- ✧ <Report Mask>: It refers to the <+ACK Mask> in **AT+GTHRM**.
- ✧ <Length>: The length of the acknowledgement message (total characters from header to the tail).

- ✧ **<Unique ID>**: If Bit 4 of **<+ACK Mask>** is 0, IMEI of the device will be used as the unique ID of the device. IMEI is a 15-digit string. In the HEX format message, every 2 digits are encoded into one byte as an integer.

IMEI	13	57	90	24	68	11	22	0
HEX	0D	39	5A	18	44	0B	16	00

If the Bit 4 of **<+ACK Mask>** is 1, the device name is used as the unique ID of the device. Refer to the **<Device Name>** in **AT+GTCFG** for the device name. Device name is an 8-byte string. If the length of the **<Device Name>** is more than 8 bytes, only the first 8 bytes will be acquired. In the Hex format message, each byte is encoded into one byte as an integer. If the device name is less than 8 bytes, the empty bytes will be set to 0.

Device Name	g	v	6	0	0	w		
HEX	67	76	36	30	30	77	00	00

- ✧ **<ID>**: Sub-command ID of **AT+GTRTO** or the ID of **AT+GTIOB** and **AT+GTGEO**. Set it to 0 for other reports.
- ✧ **<Send Time>**: The local time to send the acknowledgement message. Total 7 bytes. The first 2 bytes are for year, the rest 5 bytes are for month, day, hour, minute and second respectively.

Send Time	2011		01	31	06	29	11
HEX	07	DB	01	1F	06	1D	0B

- ✧ **<Checksum>**: The CRC-CCITT (0xFFFF) checksum for data from **<Message Type>** to **<Count Number>**.



### 4.3. Location Report +RSP

Location messages (including **+RESP:GTPNL**, **+RESP:GTTOW**, **+RESP:GTAIS**, **+RESP:GTDIS**, **+RESP:GTIOB**, **+RESP:GTFRI**, **+RESP:GTSPD**, **+RESP:GTRTL**, **+RESP:GTDOG** , **+RESP:GTIGL**, and **+RESP:GTEPS**) use this format.

➤ **+RSP,**

**Example:**

2B5253500F00FFFFFF0067FC0101011267763630307700000031B60D01312131B6010422080501  
010000020000002806CBD65B0157DF3F07E1021002392004600001253D0000989600000000000  
0000100000000000000000000007E1021002392155742DF10D0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+RSP	+RSP
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		

Report ID/Report Type	1		
Number	1	1	1
GPS Accuracy	1	0 1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Message Type>: The ID of location message.

Command	ID
<b>+RESP:GTPNL</b>	0
<b>+RESP:GTTOW</b>	1
<b>Reserved</b>	2
<b>+RESP:GTLBC</b>	3
<b>+RESP:GTEPS</b>	4

+RESP:GTDIS	5
+RESP:GTIOB	6
+RESP:GTFRI	7
Reserved	8
+RESP:GTSPD	9
+RESP:GTSOS	10
+RESP:GTRTL	11
+RESP:GTDOG	12
Reserved	13
+RESP:GTAIS	14
Reserved	15
+RESP:GTIGL	16
+RESP:GTIDA	17
+RESP:GTERI	18
Reserved	19
+RESP:GTGIN	20
+RESP:GTGOT	21

- ✧ <Report Mask>: It refers to the <+RSP Mask> in **AT+GTHRM**.
- ✧ <Unique ID>: If the Bit 6 of <+RSP Mask> is 0, IMEI of the device is used as the unique ID of the device. IMEI is a 15-digit string. In the HEX format message, every 2 digits are encoded into one byte as an integer.

IMEI	13	57	90	24	68	11	22	0
HEX	0D	39	5A	18	44	0B	16	00

If the Bit 6 of <+RSP Mask> is 1, the device name is used as the unique ID of the device. Refer to the <Device Name> in **AT+GTCFG** for the device name. Device name is an 8-byte string. If the length of the <Device Name> is more than 8 bytes, only the first 8 bytes will be acquired. In the Hex format report, each byte is encoded into one byte as an integer. If the device name is less than 8 bytes, the empty bytes will be set to 0.

Device Name	g	v	6	0	0	w		
HEX	67	76	36	30	30	77	00	00

- ✧ <Digit & Analog Input Mode>: The mode of the digital and analog input ports, the high byte is for digital IO mode and the low 4 bits of the low byte are for the analog input 1.
- ✧ <Digital Input Status>: The mask of digital input1, digital input2, digital input3 and digital

input4 status.

Input status mask	ID
Ignition Detection	0x01
Digital Input1	0x02
Digital Input2	0x04
Digital Input3	0x08
Digital Input4	0x10

- ✧ <Digital Output Status>: The mask of digital output1, digital output2, digital output3 and relay output status.

Input status mask	ID
Digital Output1	0x01
Digital Output2	0x02
Digital Output3	0x04
Digital Output4	0x08

- ✧ <Satellites>: Number of GPS Satellites.
- ✧ <Report ID/Report Type>: The high nibble is for <Report ID> and the low nibble is for <Report Type>.
- ✧ <Speed>: Total 3 bytes. The first two bytes are for the integer part of the speed and the last byte is for the fraction part. The fraction part has only 1 digit.
- ✧ <Longitude>: The longitude of the current position. Total 4 bytes. The longitude is converted to an integer with 6 implicit decimals and this integer is reported in HEX format. If the value of the longitude is negative, it is represented in 2's complement format.

Longitude	121390847			
121.390847				
HEX	07	3C	46	FF

- ✧ <Latitude>: The latitude of the current position. Total 4 bytes. The latitude is converted to an integer with 6 implicit decimals and this integer is reported in HEX format. If the value of the latitude is negative, it is represented in 2's complement format.

Latitude	31164503			
31.164503				
HEX	01	DB	88	57

- ✧ <GPS UTC Time>: The UTC time from the GPS chip. Total 7 bytes. The first 2 bytes are for year, the rest 5 bytes for month, day, hour, minute and second respectively.

GPS UTC Time	2011		07	14	08	24	13
HEX	07	DB	07	0E	08	18	0D

- ✧ <Current Mileage>: Total 3 bytes. The first 2 bytes are for the integer part of the current mileage and the last byte is for the fraction part. The fraction part has only 1 digit.

Current Mileage	0		0
HEX	00	00	00

- ✧ <Total Mileage>: Total 5 bytes. The first 4 bytes are for the integer part of the total mileage and the last byte is for the fraction part. The fraction part has only 1 digit.

Total Mileage	0				0
HEX	00	00	00	00	00

- ✧ <Total Hour Meter Count>: Total 6 bytes. The first 4 bytes are the hour part. The fifth byte is the minute part. The sixth byte is the second part.

Total Hour Meter Count	0				0	0
HEX	00	00	00	00	00	00

Location message for **+RESP:GTSOS** uses below format.

➤ **+RSP,**

**Example:**

2B 52 53 50 0A 00 FE FF FF 00 68 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 08 00 1A 13 30 00 01 03 00 00 05 00 00 00 00 07 3C 46 81 01 DB 88 03 07 DE 01 0D 01 32 36 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 32 35 00 62 90 82 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+RSP	+RSP
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		

Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Report ID/Report Type	1		
Reserved	1		
Number	1	1	1
GPS Accuracy	1	0   1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	

Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Location report **+RESP:GTIDA** uses the format below.

➤ **+RSP,**

**Example:**

**2B 52 53 50 11 01 FE DF FF 00 71 25 08 03 09 09 67 76 33 30 30 2D 41 30 64 2F 7A 00 05 00 18 01  
02 22 14 00 08 01 E2 52 0B 16 00 00 63 01 01 00 00 00 06 01 00 00 60 07 3C 4B D0 01 DB 87 53  
07 E0 07 1D 09 28 20 04 60 00 01 14 4B 3E 5B 00 01 25 02 00 00 00 04 03 00 15 1E 00 00 00 03 27  
2F 00 00 00 00 07 E0 07 1D 11 28 21 07 60 24 3C 0D 0A**

Parameter	Length (Byte)	Range/Format	Default
Report Header	4	+RSP	+RSP
Report Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 3F	
Digital Output Status	1	00 – 1F	
Motion Status	1	0x11/0x12 0x21/0x22 0x41/0x42 0x16/0x1A	
Satellites in View	1		
Report ID/Report Type	1	00	00
ID Length	1		

ID	<=20	'0' – '9' 'A' – 'Z'	
ID Report Type	1	0/1/2	
Number	1	1	
GPS Accuracy	1	0/1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ <ID>: The ID that is currently being read.
- ✧ <ID Report Type>: The type of reported ID.
  - 0: The ID is unauthorized.
  - 1: The ID is authorized.
  - 2: The ID has logged out.

Location message for **+RESP:GTERI** uses below format.

➤ **+RSP,**

**Example:**



2B 52 53 50 12 00 FE 2F FF 00 00 00 03 00 69 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00  
 01 22 17 10 02 00 00 00 01 01 00 00 00 00 00 FF F4 07 3C 47 31 01 DB 88 79 07 DE 01 0D 01 2C 38  
 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D  
 09 2D 00 00 5D F1 B4 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+RSP	+RSP
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
ERI Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Report ID/Report Type	1		
Reserved	1	0	
1-Wire Device Number (optional)	1	0-8	
1-Wire Devices ID (optional)	8		
1-Wire Devices TYPE (optional)	1		
Data Length (optional)	1		

1-Wire Device Data (optional)	N		
Fuel Sensor number (Optional)	1	0-1	
Sensor Type	1	0 – 6	
Percentage (Optional)	1	0 –100	
Volume (Optional)	2	0 –65535	
Number	1	1	1
GPS Accuracy	1	0 1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 –65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ <UART Device Type>: Type of device connected to the second serial port.
  - 0: No device connect
- ✧ <1-Wire Devices ID>: Means the 1-Wire device ID read from the device.
- ✧ <1-Wire Devices TYPE>: Means the 1-Wire device type.
  - 1: Temperature sensor.
- ✧ <Device Data Length>: It indicates the length of <1-Wire Devices DATA>.

- ✧ <1-Wire Devices DATA>: Means the data read from the 1-Wire devices. If the value of <1-Wire Devices Type> is the temperature sensor, this indicates the temperature value. To convert the value of the two bytes in hex to decimal, multiply it by 0.0625 to get the temperature value in Celsius degrees. If the first 5 bits of the high byte are 1, the temperature value is below zero Celsius degrees and the value is represented in two's complement format. To obtain the temperature in decimal, plus the hexadecimal data by 1 and then multiply it by 0.0625 to get the value in Celsius degrees.

**Note:** The key word (optional) means the item is controlled by the parameter <ERI Mask>.

Location messages for **+RESP:GTGIN** and **+RESP:GTGOT** use this format.

➤ **+RSP,**

<b>Example:</b> <b>2B4556541B00FEFFFF0068FC0101011267763630307700000031AD0D00000031AD0108210C030001010000000000002806CBD6580157DF2A07E1021003380904600001253D000098960000000000000001000000000000000000000007E1021003380B574318C90D0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+RSP	+RSP
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42	

		0x16   0x1A	
Satellites in View	1		
Area Type	1	0 1	
Group Mask	1	01-1F	
GEO ID Group	8	64bit 0000000000000001-0000 0000000FFFFF (GEOID 0 - 19)	
Number	1	1	1
GPS Accuracy	1	0 1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ <Area Type>: This text belongs to Polygon or circle area, 0 means Polygon.
- ✧ <Group Mask>: The bitwise mask to confirm the reported <GEO ID Group>. For GV600M, only bit 0 is valid and it should be set to 1.
- ✧ <GEO ID Group>: The bitwise mask for trigger condition composition of the corresponding

GEO ID. For GV600M, only the lowest 20 bits are valid. Each bit, from bit 0 to bit 19, represents the logical status of the corresponding GEO ID to trigger the entering or exiting event. 1 means that the event of the GEO ID set has been triggered and 0 means has not.

Location message for **+RESP:GTLBC** uses below format.

➤ **+RSP,**

**Example:**

**2B 52 53 50 03 00 FE FF FF 00 6E 29 03 03 03 05 67 76 33 30 30 76 63 00 64 00 00 00 00 00 00 00 00 00 00 11 17 00 70 13 61 17 10 64 7F 01 01 00 00 00 00 00 00 00 2C 07 3C 45 E4 01 DB 87 E9 07 DF 0A 14 02 11 05 04 60 00 03 36 10 00 10 41 23 00 00 00 00 00 00 00 00 7B 04 00 00 00 00 00 00 00 00 00 07 DF 0A 14 0A 11 06 22 AD 0C E9 0D 0A**

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+RSP	+RSP
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Report ID/Report Type	1		

Number Length/ Number Type	1		
Phone Number	<=10		
Number	1	1 – 15	
GPS Accuracy	1	0 1 – 50	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ <Number Length/Number Type>: The high nibble is for <Number Length> and the low nibble is for <Number Type>. <Number Length> is the number of bytes used to represent the phone number. <Number Type> indicates if there is a '+' sign before the phone number. 1 means there is the sign and 0 means no such a sign.

	Number Length	Number Type
HEX	7	0

- ✧ <Phone Number>: Not more than 10 bytes. Each byte uses the high nibble and low nibble to represent one digit of the phone number respectively. If the last low nibble has no digit to represent, fill in 0xF.

Phone Number 02154450293	02	15	44	50	29	3
HEX	02	15	44	50	29	3F

#### 4.4. Information Report +INF

Information messages include **+RESP:GTINF**, **+RESP:GTGPS**, **+RESP:GTCID**, **+RESP:GTC SQ**, **+RESP:GTVER**, **+RESP:GTBAT**, **+RESP:GTIOS**. These messages use the same format as below. Only **+RESP:GTINF** includes all the items. The other reports only include information related to them.

➤ **+INF,**

<b>Example:</b> <b>2B 49 4E 46 01 2F 7F 00 58 67 76 33 30 30 63 00 00 29 01 01 01 02 01 02 00 00 01 01 00 00 00</b> <b>00 00 00 00 00 00 00 00 00 00 00 00 01 11 00 16 20 07 DE 01 0D 01 25 14 00 01 00 7F 00 1E 02 58</b> <b>00 00 00 00 00 90 00 00 00 00 00 00 1F 00 07 DE 01 0D 09 27 2B 00 48 F0 07 0D 0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+INF	+INF
Message Type	1		
Report Mask	2	0000 – FFFF	
Expand INF Mask	2	0000 - FFFF	
Length	2		
Unique ID	8	IMEI/Device Name	
Device Type	1	ED	
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Hardware Version	2	0000 – FFFF	
Reserved	2	0000	<b>+RESP:GTVER</b>
Reserved	2	0000	
Reserved	2	0000	
Analog Input Mode	1		<b>+RESP:GTIOS</b>
Analog Input1 Voltage	2		
Reserved	2	0000	
Reserved	1	00	
Reserved	2	0000	
Reserved	2	0000	
Reserved	2	0000	
Digital Input Status	1	00 – 1F	



Digital Output Status	1	00 – 0F	
IO mode	1	0-F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	<b>+RESP:GTGPS</b>
Reserved	1	00	
Satellites in View	1		
Power Saving Enable/OWH Mode/Outside Working Hour/AGPS	1		
Last Fix UTC Time	7	YYYYMMDDHHMMSS	
Reserved	1	00	
FRI Discard No Fix	1	0 1	
Response Report Items Mask	2		
IGN Interval	2		
IGF Interval	2		
Reserved	4	00000000	
Reserved	1	00	
Main Supply/Backup Battery On/Charging/LED On/Backup Battery Charge Mode	1		<b>+RESP:GTBAT</b>
External Power Supply VCC	2	0	
External Power Supply2 VCC	2	0	
Backup Battery VCC	2	0 – 4500mV	
Backup Battery Level	1	00	
ICCID	10	ICCID	<b>+RESP:GTCID</b>
CSQ RSSI	1	0 – 31	<b>+RESP:GTCSQ</b>
CSQ FER	1	0 – 7	
Time Zone Offset Sign/Enable Daylight Saving	1		<b>+RESP:GTTMZ</b>
Time Zone Offset	2	HHMM	
SV Count	1		<b>+RESP:GTGSV</b>

SV id	1		
SV Power	1		
.....			
SV id	1		
SV Power	1		
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Message Type>: The ID of information message.

Command	ID
+RESP:GTINF	1
+RESP:GTGPS	2
Reserved	3
+RESP:GTCID	4
+RESP:GTCSQ	5
+RESP:GTVAR	6
+RESP:GTBAT	7
+RESP:GTIOS	8
+RESP:GTTMZ	9
Reserved	10
+RESP:GTGSV	11

✧ <Report Mask>: It refers to the <+INF Mask> in **AT+GTHRM**.

✧ <Unique ID>: If the Bit 1 of <+INF Mask> is 0, IMEI of the device is used as the unique ID. IMEI has 14 bytes in hexadecimal format. In the Hex format message, every two bytes are encoded into one byte as an integer. The 8th byte is reserved and its value is 0x00.

IMEI	13	57	90	24	68	11	22	0
HEX	0D	39	5A	18	44	0B	16	00

If the Bit 1 of <+INF Mask> is 1, the device name is used as the unique ID of the device. Refer to the <Device Name> in **AT+GTCFG** for the device name. Device name is an 8-byte string. If

the length of the <Device Name> is more than 8 bytes, only the first 8 bytes will be acquired. In the Hex format report, each byte is encoded into one byte as an integer. If the device name is less than 8 bytes, the empty bytes will be set to 0.

Device Name	g	v	6	0	0	w		
HEX	67	76	36	30	30	77	63	00

- ✧ <Power Saving Enable/OWH Mode/Outside Working Hours/GPS Antenna Status>: The highest bit, bit 7 is reserved. Bit 5 and bit 6 are for <Power Saving Enable>, bit 4 and bit 3 are for <OWH Mode>, bit 2 is for <Outside Working Hours> and bit 0 is for <AGPS>. <Outside Working Hours> is used to indicate whether the device is currently outside the working hours. 1 means it is outside the working hours.
- ✧ <Main Supply/Backup Battery On/Charging/LED On/Backup Battery Charge Mode>: The highest bit, bit 7 is for <Main Supply> to indicate whether the external power supply is connected to the device. Bit 6 is for <Backup Battery On> to indicate whether the backup battery is working. Bit 5 is for <Charging> to indicate whether the backup battery is currently charging. Bit 4 is for <LED On> to indicate whether the LEDs are turned on. Bit 0 is for <Backup Battery Charge Mode>.
- ✧ <ICCID>: ICCID is a 20-digit string. In the HEX format message, every 4 bits are used to represent one digit of the ICCID.

ICCID	89	86	00	00	09	09	17	21	49	53
HEX	89	86	00	00	09	09	17	21	49	53

- ✧ <Time Zone Offset Sign/Enable Daylight Saving>: Bit 1 is for <Enable Daylight Saving> which indicates whether the daylight saving function is currently enabled. Bit 0 is for <Time Zone Offset Sign> which indicates the positive or negative offset of the local time to UTC. 1 means "negative offset".
- ✧ <Cell Number>: It represents the number of the IMSI. The IMSI consists of MCC, MNC, LAC, and Cell ID.

#### 4.5. Event Report +EVT

Event messages (+RESP:GTPNA, +RESP:GTPFA, +RESP:GTMPN, +RESP:GTMPF, +RESP:GTBTC, +RESP:GTSTC, +RESP:GTSTT, +RESP:GTGPJ, +RESP:GTPDP, +RESP:GTIDN, +RESP:GTSTR, +RESP:GTSTP, +RESP:GTLSP, +RESP:GTBST, +RESP:GTBTA) use this format.

➤ +EVT,

<b>Example:</b> 2B 45 56 54 09 00 FE FF FF 00 66 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 02 01 21 17 01 00 00 00 00 00 00 00 FF F4 07 3C 47 31 01 DB 88 79 07 DE 01 0D 01 2D 32 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 2D 35 00 5E 1A A5 0D 0A			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	

Satellites in View	1		
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Message Type>: The ID of event message.

Command	ID
<b>+RESP:GTPNA</b>	1
<b>+RESP:GTPFA</b>	2
<b>+RESP:GTMPN</b>	3
<b>+RESP:GTMPF</b>	4
<b>Reserved</b>	5

<b>+RESP:GTBPL</b>	6
<b>+RESP:GTBTC</b>	7
<b>+RESP:GTSTC</b>	8
<b>+RESP:GTSTT</b>	9
<b>Reserved</b>	10
<b>Reserved</b>	11
<b>+RESP:GTPDP</b>	12
<b>+RESP:GTIGN</b>	13
<b>+RESP:GTIGF</b>	14
<b>+RESP:GTUPD</b>	15
<b>+RESP:GTIDN</b>	16
<b>+RESP:GTIDF</b>	17
<b>+RESP:GTDAT</b>	18
<b>Reserved</b>	19
<b>Reserved</b>	20
<b>+RESP:GTGSS</b>	21
<b>+RESP:GTFLA</b>	22
<b>+RESP:GTSTR</b>	23
<b>+RESP:GTSTP</b>	24
<b>Reserved</b>	25
<b>Reserved</b>	26
<b>+RESP:GTDOS</b>	27
<b>+RESP:GTGES</b>	28
<b>+RESP:GTLSP</b>	29
<b>+RESP:GTTMP</b>	30
<b>+RESP:GTRMD</b>	33
<b>+RESP:GTEXP</b>	35
<b>+RESP:GTUFS</b>	37
<b>+RESP:GTUPC</b>	39
<b>+RESP:GTGPJ</b>	40

<b>+RESP:GTVGN</b>	45
<b>+RESP:GTVGF</b>	46
<b>Reserved</b>	47
<b>+RESP:GTBST</b>	48
<b>+RESP:GTBTA</b>	49

- ✧ **<Report Mask>**: It refers to the **<+EVT Mask>** in **AT+GTHRM**.
- ✧ **<Unique ID>**: If the Bit 6 of **<+EVT Mask>** is 0, IMEI of the device is used as the unique ID of the device. IMEI is a 15-digit string. In the HEX format message, every 2 digits are encoded into one byte as an integer.

<b>IMEI</b>	<b>13</b>	<b>57</b>	<b>90</b>	<b>24</b>	<b>68</b>	<b>11</b>	<b>22</b>	<b>0</b>
<b>HEX</b>	<b>0D</b>	<b>39</b>	<b>5A</b>	<b>18</b>	<b>44</b>	<b>0B</b>	<b>16</b>	<b>00</b>

If the Bit 6 of **<+EVT Mask>** is 1, the device name is used as the unique ID of the device. Refer to the **<Device Name>** in **AT+GTCFG** for the device name. Device name is an 8-byte string. If the length of the **<Device Name>** is more than 8 bytes, only the first 8 bytes will be acquired. In the Hex format report, each byte is encoded into one byte as an integer. If the device name is less than 8 bytes, the empty bytes will be set to 0.

<b>Device Name</b>	<b>g</b>	<b>v</b>	<b>6</b>	<b>0</b>	<b>0</b>	<b>w</b>		
<b>HEX</b>	<b>67</b>	<b>76</b>	<b>36</b>	<b>30</b>	<b>30</b>	<b>77</b>	<b>00</b>	<b>00</b>

Event message **+RESP:GTBPL** uses this format.

➤ **+EVT,**

<b>Example:</b> <b>2B 45 56 54 06 00 FE FF FF 00 68 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 11 16 00 00 01 00 00 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 0D 01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 1F 24 00 31 FC 86 0D 0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	

Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Backup Battery VCC	2	0 – 4500 mV	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	



Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTIGN/+RESP:GTVGN** and **+RESP:GTIGF/+RESP:GTVGF** use this format. For these two messages, the *<Mileage>* field will always be present regardless the *<Report Items Mask>* setting.

➤ **+EVT,**

**Example:**

[illegible]

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	

Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Duration of Ignition On or Ignition Off	4	0 – 999999 sec	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTUPD** uses this format. For this message, the *<Protocol Version>* and *<Firmware Version>* will always be present regardless the *<Report Items Mask>* setting

➤ **+EVT,**

**Example:**

2B 45 56 54 0F 00 FE FF FF 00 69 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 00 00 11 16 00 64 00 01 00 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 0D 01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 1F 1B 00 36 DD 17 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Code	2		
Retry	1		
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	

Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTUPC** uses this format.

**Example:**

```
2B 45 56 54 0F 00 FE FF FF 00 69 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00  
00 00 00 11 16 00 64 00 01 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 OD 01 1F  
16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01  
OD 09 1F 1B 00 36 DD 17 OD 0A
```

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	

Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Command ID	1		
Result	2	100 101 102 103 200 201 202 300 301 302	
URL Length	1		
Download URL	<=60	Complete URL	1
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	

Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ **<Command ID>**: The command ID in the update configuration file. It is always 0 before the device starts to update the configuration. It indicates the total number of the successfully executed commands when the result code is 301. And it is the number of the commands which have failed to execute when the result code is 302.
- ✧ **<Result>**: A numeral to indicate whether the configuration is updated successfully.
  - 100: The update command is starting.
  - 101: The update command is confirmed by the device.
  - 102: The update command is refused by the device.
  - 103: The update process is refused because the battery is low.
  - 200: The device starts to download the package.
  - 201: The device finishes downloading the package successfully.
  - 202: The device fails to download the package.
  - 300: The device starts to update the device configuration.
  - 301: The device finishes updating the device configuration successfully.
  - 302: The device fails to update the device configuration.
- ✧ **<URL Length>**: The length of complete URL.
- ✧ **<Download URL>**: The complete URL to download the configuration. It includes the file name.

Event message **+RESP:GTUPD** uses this format.

**Example:**

2B 45 56 54 0F 00 FE FF FF 00 69 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 00 00 11 16 00 64 00 01 00 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 0D 01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 1F 1B 00 36 DD 17 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT

Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Code	2		
Retry	1		
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	

MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 –65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTIDF** uses this format.

➤ +EVT,

**Example:**

[illegible]

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		



Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Duration of Idling	4		
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	

Tail Characters	2	0x0D 0x0A	0x0D 0x0A
-----------------	---	-----------	-----------

Event message **+RESP:GTDAT** uses this format.

➤ **+EVT,**

**Example:**

**2B4556541200FEFFFF0071FC01010112677636303077000000361B00030064361B010021090009  
31323334353637383901010000000000002C06CBD6470157DF4207E1021008272704600001A531  
0162447B0000000000041893400000000000000000000007E1021008272500F9290F0D0A**

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Data Length	2		
data			
Number	1	1	1

- ✧ *<Data Length>*: It indicates the length of *<data>* parameter.

➤ **+EVT,**

```
2B 45 56 54 15 00 FE FF FF 00 6B 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00  
00 00 00 11 16 01 00 00 00 00 01 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 OD  
01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07  
DE 01 OD 09 1F 33 00 34 AE 3F OD 0A
```

- 235 -

Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
GPS Signal Status	1	0   1	
Reserved	4	00000000	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	

MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

<GPS Signal Status>: 0 means GPS signal is lost or no successful GPS fix; 1 means GPS signal recovered and GPS fix succeeded.

Event message **+RESP:GTFLA** uses this format.

➤ **+EVT,**

**Example:**

2B 45 56 54 1B 00 FE FF FF 00 68 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 00 11 16 00 00 01 00 00 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 0D 01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 1F 38 00 35 69 C8 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	

Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Input ID	1	0 1 2	
Last Fuel Level	1	0 – 100	
Current Fuel Level	1	0 – 100	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00

Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event report **+RESP:GTEXP** uses the format below.

➤ **+EVT,**

<b>Example:</b> <b>2B 45 56 54 23 01 FE DF FF 00 6A 25 03 07 0D 05 67 76 33 30 30 00 00 00 00 00 00 00 00 01</b> <b>00 21 1B 00 00 33 31 01 00 00 00 00 00 42 00 3D 06 FC 5A 08 01 E5 BB FC 07 DE 06 13 07 02 1E</b> <b>04 60 00 01 55 04 67 F3 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE</b> <b>06 13 07 02 20 05 21 CE 98 0D 0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Report Header	4	+EVT	+EVT
Report Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	F8	F8
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	

Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Digital Fuel Sensor Type	1	2/4	
Reserved	1		
Reserved	1		
HW Fault Code	1		
Number	1	1	
GPS Accuracy	1	0/1 – 50	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A



Event report **+RESP:GTUFS** uses the format below.

➤ **+EVT,**

<b>Example:</b> <b>2B 45 56 54 25 01 FE FF FF 00 68 25 04 04 05 0D 67 76 33 30 30 6E 31 30 63 00 00 00 00 00 00 00 00 00 00 11 17 01 00 00 00 00 00 00 00 00 31 06 FC 5A 1B 01 E5 BC 3D 07 DF 06 03 03 1D 16 04 60 00 01 55 04 58 2B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DF 06 03 03 1D 18 01 D5 7F C0 0D 0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Report Header	4	+EVT	+EVT
Report Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	F8	F8
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Code	2		
Reserved	1		0
Number	1	1	
GPS Accuracy	1	0/1 – 50	0
Speed	3	0.0 – 999.9km/h	

Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTGPJ** uses this format.

➤ **+EVT,**

**Example:**

**2B4556542800FEFFFF0068FC0101011267763630307700000031A40D01310D31A4010122060503  
01000005050000002606CBD6770157DF4307E1021003212504600001253D000098960000000000  
0000001000000000000000000000000007E1021003212E56A9D68A0D0A**

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED

Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
CW Jamming Value	1	0-255	
GPS Jamming State	1	0-3	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	

Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <CW Jamming Value>: Current continuous wave jamming value.

✧ <GPS Jamming State>: Current jamming state.

- 0: Unknown or feature disabled.
- 1: (OK) no significant jamming.
- 2: (Warning) interference visible but fix OK.
- 3: (Critical) interference visible and no fix.

Event message **+RESP:GTDOS** uses this format.

➤ **+EVT,**

**Example:**

2B 45 56 54 1B 00 FE FF FF 00 68 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00 00 00 00 00 00 11 16 00 00 01 00 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB 87 C2 07 DE 01 0D 01 1F 16 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 07 DE 01 0D 09 1F 38 00 35 69 C8 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply	2		

Voltage			
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Wave1 Output ID	1	1-4	
Wave1 Ouptut Active	1	0 1	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	

Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

Event message **+RESP:GTGES** uses this format.

➤ +EVT,

**Example:**

```
2B 45 56 54 1C 00 FE FF FF 00 72 29 01 01 01 02 67 76 33 30 30 63 00 00 00 00 00 00 00 00 00  
00 00 00 11 16 00 00 00 00 00 00 00 32 00 00 00 06 01 00 00 00 00 00 00 00 17 07 3C 47 17 01 DB  
87 C2 07 DE 01 0D 01 25 06 04 60 00 03 36 10 00 10 01 4B 00 00 00 00 00 00 00 00 00 00 00 00  
00 00 00 00 00 07 DE 01 0D 09 25 10 00 42 23 C5 0D 0A
```

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22	

		0x41   0x42 0x16   0x1A	
Satellites in View	1		
Trigger GEO ID	2	0-19	
Trigger GEO Enable	1	0 1	
Trigger Mode	1	0 21 22	
Radius	4	50 – 6000000m	
Check Interval	4	0 5 – 86400sec	
Number	1	1	1
GPS Accuracy	1	0 1	
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Trigger GEO ID>: The ID of Geo-Fence. The range is 0 – 19.

✧ <Trigger GEO Enable>: Current Parking-Fence is active or inactive.

● 0 Current Parking-Fence is inactive.

- 1 Current Parking-Fence is active.

Event message **+RESP:GTTMP** uses this format.

➤ **+EVT,**

<b>Example:</b> <b>2B4556541E00FEFFFF0073FC0101011267763630307700000031AD0D013103319B0100210A0001</b> <b>2816A5DA060000DD00001901010000000000002A06CBD6530157DF4907E10210030420046000</b> <b>01253D000098960000000000000000010000000000000000000007E1021003041F559F28090D0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Temperature Alarm ID	1	0 – 7	
Temperature Status	1	0 1	



Temperature Sensor Device ID	8	'0' – '9' 'a' – 'f' 'A' – 'F'	
Reserved	1	00	00
Temperature Sensor Device DATA	2	-55 – 125°C	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ <Temperature Alarm ID>: The ID of temperature alarm.
- ✧ <Temperature Status>: The status of current temperature. 0 means beyond the predefined temperature range. 1 means within the predefined temperature range.
- ✧ <Temperature Sensor device ID>: The ID of the temperature sensor.
- ✧ <Temperature Sensor device DATA>: The current temperature detected by the sensor.

Event message **+RESP:GTBST** uses this format.

## ➤ +EVT,

Example:			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
<i>Report ID/Report Type</i>	1		
BLE Sensor Num	1	0-10	
BLE Sensor MAC ID	6	'0' – '9' 'a' – 'f' 'A' – 'F'	
BLE Sensor Tem DATA	1	-40 – 80℃	
BLE Sensor Voltage	2	0-5000mv	
Number	1	1	1

GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Report ID/Report Type>: The report ID and the type are in hex format. 4 high bits mean report ID and 4 low bits means report type.

Report ID: 1 (the <Mode> of **AT+GTBTE** is 1)

Report type: 0 (by default)

✧ <BLE Sensor Num>: The total number of BLE sensors. Maximum 10 sensors are supported.

✧ <BLE Sensor MAC ID>: MAC address of BLE sensor.

✧ <BLE Sensor Tem DATA>: Current temperature of BLE sensor.

✧ <BLE Sensor voltage>: Current voltage of BLE sensor.

Event message **+RESP:GTBTA** uses this format.

➤ **+EVT,**

Example:			
Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT

Message Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
<i>Report ID/Report Type</i>	1		
BLE Sensor mac ID	6	'0' – '9' 'a' – 'f' 'A' – 'F'	
BLE Sensor tmp DATA	1	-40 – 80℃	
BLE Sensor voltage	2	0-5000mv	
Number	1	1	1
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		

Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	
LAC	2	0000 – FFFF	
Cell ID	4	00000000 – FFFFFFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Report ID/Report Type>: The report ID and the type are in hex format. 4 high bits mean report ID and 4 low bits means report type.

Report ID: GTBTE Open mode1.

Report type: When the voltage is low, the report type is 0. When the temperature exceeds threshold, the report type is 1.

✧ < BLE Sensor num >: The number of Bluetooth module data, when the number is greater than 1, the following three fields will be superimposed on the same time.

✧ < BIE Sensor mac ID >: Bluetooth module MAC address.

✧ < BLE Sensor tmp DATA >: Bluetooth module temperature data.

✧ < BLE Sensor voltage >: Bluetooth module voltage.

Event message **+RESP:GTRMD** uses the format below.

➤ **+EVT,**

**Example:**

2B 45 56 54 21 01 FE DF FF 00 67 25 90 06 01 0B 67 76 33 30 30 2D 41 30 64 2F 81 00 05 00 18 01  
00 22 15 02 01 00 00 00 01 00 00 00 30 07 3C 4C 17 01 DB 87 85 07 E0 07 1D 09 2A 21 04 60 00  
01 14 4B 3E 5B 00 00 00 00 00 00 00 04 03 00 00 05 00 00 00 03 29 16 00 00 00 00 07 E0 07 1D 11  
2A 24 07 7F 94 39 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+EVT	+EVT
Message Type	1		

Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI	
Battery Level	1	0~100	
External Power Supply Voltage	2		
Digit & Analog Input Mode	2		
Analog Input1 Voltage	2		
External Power Supply2 Voltage	2		
Digital Input Status	1	00 – 1F	
Digital Output Status	1	00 – 0F	
Motion Status	1	0x11   0x12 0x21   0x22 0x41   0x42 0x16   0x1A	
Satellites in View	1		
Roaming State	1	0-3	
Number	1	1	
GPS Accuracy	1	0	0
Speed	3	0.0 – 999.9km/h	
Azimuth	2	0 – 359	
Altitude	2		
Longitude	4		
Latitude	4		
GPS UTC Time	7	YYYYMMDDHHMMSS	
MCC	2	0000 – FFFF	
MNC	2	0000 – FFFF	

LAC	2	0000 – FFFF	
Cell ID	2	0000 – FFFF	
Reserved	1	00	00
Current Mileage	3	0.0 – 65535.0 km	
Total Mileage	5	0.0 – 4294967.0 km	
Current Hour Meter Count	3	HHMMSS	
Total Hour Meter Count	6	HHHHHHHHMMSS	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

#### 4.6. Data Report +DAT

Data reports **+RESP:GTPHD**, **+RESP:GTEHD** and **+RESP:GTCRG** use the format below. They are only sent via GPRS even if the report mode is Force on SMS.

➤ **+DAT,**

<b>Example:</b> <b>2B444154050000007F002CF80101011267763630307700000618000406030E07E10210091137018B7A070D0A</b>			
Parameter	Length (Byte)	Range/Format	Default
Report Header	4	+DAT	+DAT
Report Type	1		
Report Mask	4	00000000 – FFFFFFFF	
Length	2		
Device Type	1	F8	F8
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Data Length	2		+RESP:GTFSD
Sensor Data	<=128		
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

✧ <Report Type>: The ID of data report.

Command	ID
Reserved	1
<b>+RESP:GTFSD</b>	2

✧ <Report Mask>: Please refer to the <+DAT Mask> in **AT+GTHRM**.



## 4.7. Heartbeat Data +HBD

### ➤ +HBD,

**Example:**  
 2B 48 42 44 FF 20 29 01 01 01 02 67 76 33 30 30 63 00 00 07 DD 0B 1C 03 0D 23 00 07 FD 4C 0D 0A

Parameter	Length (Byte)	Range/Format	Default
Message Header	4	+HBD	+HBD
Report Mask	1	00 – FF	
Length	1		
Device Type	1	ED	ED
Protocol Version	2	0000 – FFFF	
Firmware Version	2	0000 – FFFF	
Unique ID	8	IMEI/Device Name	
Send Time	7	YYYYMMDDHHMMSS	
Count Number	2	0000 – FFFF	
Checksum	2	0000 – FFFF	
Tail Characters	2	0x0D 0x0A	0x0D 0x0A

- ✧ **<Report Mask>**: It refers to the **<+HBD Mask>** in **AT+GTHRM**.
- ✧ **<Unique ID>**: If Bit 4 of **<+HBD Mask>** is 0, IMEI of the device is used as the unique ID of the device. IMEI is a 15-digit string. In the HEX format message, every 2 digits are encoded into one byte as an integer.

IMEI	13	57	90	24	68	11	22	0
HEX	0D	39	5A	18	44	0B	16	00

If the Bit 4 of **<+HBD Mask>** is 1, the device name is used as the unique ID of the device. Refer to the **<Device Name>** in **AT+GTCFG** for the device name. Device name is an 8-byte string. If the length of the **<Device Name>** is more than 8 bytes, only the first 8 bytes will be acquired. In the Hex format report, each byte is encoded into one byte as an integer. If the device name is less than 8 bytes, the empty bytes will be set to 0.

Device Name	g	v	6	0	0	w		
HEX	67	76	36	30	30	77	00	00

If the mask of **<UID>** is set to 0 in the **<+HBD Mask>** of **AT+GTHRM**, the heartbeat message will not report device name or IMEI information. If the mask of **<UID>** is set to 1, the heartbeat message will send device name or IMEI according to the mask of **<Device Name>**.

#### 4.8. Buffer Report in HEX Format

When HEX format messages are buffered in the memory, the device will replace the second byte of the messages with 'B'. Thus, **+BSP** is buffered report for **+RSP**, **+BNF** is buffered report for **+INF** and **+BVT** is buffered report for **+EVT**. The rest part of the messages is the same.

## Appendix: Message Index

### ✧ Command and ACK

AT+GTBSI

+ACK:GTBSI

AT+GTSRI

+ACK:GTSRI

AT+GTQSS

+ACK:GTQSS

AT+GTCFG

+ACK:GTCFG

AT+GTPIN

+ACK:GTPIN

AT+GTDOG

+ACK:GTDOG

AT+GTTMA

+ACK:GTTMA

AT+GTOWH

+ACK:GTOWH

AT+GTPDS

+ACK:GTPDS

AT+GTFRI

+ACK:GTFRI

AT+GTFFC

+ACK:GTFFC

AT+GTGEO

+ACK:GTGEO

AT+GTPEO

+ACK:GTPEO

AT+GTTOW

+ACK:GTTOW

AT+GTSPD

+ACK:GTSPD

AT+GTSOS

+ACK:GTSOS

AT+GTRMD

+ACK:GTRMD

AT+GTBZA

+ACK:GTBZA

AT+GTSPA

+ACK:GTSPA

AT+GTIDL

+ACK:GTIDL

AT+GTSSR  
+ACK:GTSSR  
AT+GTTMP  
+ACK:GTTMP  
AT+GTGPJ  
+ACK:GTGPJ  
AT+GTOUT  
+ACK:GTOUT  
AT+GTEPS  
+ACK:GTEPS  
AT+GTDIS  
+ACK:GTDIS  
AT+GTIOB  
+ACK:GTIOB  
AT+GTAIS  
+ACK:GTAIS  
AT+GTMUT  
+ACK:GTMUT  
AT+GTRTO  
+ACK:GTRTO  
AT+GTDAT  
+ACK:GTDAT  
AT+GTWLT  
+ACK:GTWLT  
AT+GTGLM  
+ACK:GTGLM  
AT+GTHMC  
+ACK:GTHMC  
AT+GTUPC  
+ACK:GTUPC  
AT+GTCMD  
+ACK:GTCMD  
AT+GTUDF  
+ACK:GTDF  
AT+GTIDA  
+ACK:GTIDA  
AT+GTACD  
+ACK:GTACD

✧ Position Related Report

+RESP:GTTOW  
+RESP:GTEPS  
+RESP:GTDIS  
+RESP:GTIOB

+RESP:GTFRI  
+RESP:GTSPD  
+RESP:GTSOS  
+RESP:GTGPJ  
+RESP:GTRTL  
+RESP:GTDOG  
+RESP:GTAIS  
+RESP:GTIGL  
+RESP:GTGES  
+RESP:GTERI  
+RESP:GTGIN  
+RESP:GTGOT  
+RESP:GTLBC

✧ Device Information Report

+RESP:GTINF

✧ Report for Querying

+RESP:GTGPS  
+RESP:GTALM  
+RESP:GTCID  
+RESP:GTCSQ  
+RESP:GTVER  
+RESP:GTBAT  
+RESP:GTIOS  
+RESP:GTTMZ  
+RESP:GTAIF  
+RESP:GTALS  
+RESP:GTALC  
+RESP:GTGSV

✧ Event Report

+RESP:GTPNA  
+RESP:GTPFA  
+RESP:GTMPN  
+RESP:GTMPF  
+RESP:GTBTC  
+RESP:GTSTC  
+RESP:GTBPL  
+RESP:GTSTT  
+RESP:GTIGN  
+RESP:GTIGF  
+RESP:GTIDN  
+RESP:GTIDF

+RESP:GTGSM

+RESP:GTGSS

+RESP:GTSTR

+RESP:GTSTP

+RESP:GTLSP

+RESP:GTFLA

+RESP:GTDOS

+RESP:GTTMP

+RESP:GTPDP

+RESP:GTUPC

✧ Transparent Data Transmission

+RESP:GTDAT (Short Format)

+RESP:GTDAT (Long Format)

✧ Heartbeat

+ACK:GTHBD

+SACK:GTHBD

✧ Server Acknowledgement

✧ +SACK Hex format message

+ACK

+RSP

+EVT

+DAT

+INF

+HBD